
INCH-POUND
MIL-C-55302/25E
7 June 1993
SUPERSEDING
MIL-C-55302/25D
31 October 1988

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES RECEPTACLE, 120, 150, 160, AND 180 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (075 SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-C-55302



(E) FIGURE 1 Connectors, receptacle, .075 (1.90 mm) spacing

(E) denotes changes

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Dash 1/ numbers	Number of contacts	Type	Dimensions					Contact identification numbers
			A	B	C	D	E	
01 02 03 04	120	I II III IV	5 380 (136 65)	5 090 (129 29)	59	4 425 (112 40)	4 690 (119 13)	1 - 60 61 - 120
05 06 07 08	150	I II III IV	6 505 (165 23)	6 215 (157 86)	74	5.550 (140 97)	5 815 (147 70)	1 - 75 76 - 150
09 10 11 12	160	I II III IV	6 880 (174 75)	6 590 (167 39)	79	5 925 (150 50)	6 190 (157 23)	1 - 80 81 - 160
13 14 15 16	180	I II III IV	7 630 (193 80)	7 340 (186 44)	89	6 675 (169 55)	6 940 (176 28)	1 - 90 91 - 180

1/ Dash numbers 01 through 16 are for style 1 (internal keying) connectors

(E) FIGURE 1 Connectors, receptacle, 075 (1 90 mm) spacing - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.



STYLE 2 (EXTERNAL KEYING)

(E) FIGURE 1 Connectors, receptacle, 075 (1.90 mm) spacing - Continued


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Dash 1/ numbers	Number of contacts	Type	Dimensions					Contact identification numbers
			A	B	C	D	E	
17 18 19 20	120	I II III IV	5 380 (136 65)	5.090 (129 29)	59	4 425 (112 40)	4 690 (119 13)	1 - 60 61 - 120
21 22 23 24	150	I II III IV	6 505 (165 23)	6 215 (157 86)	74	5 550 (140 97)	5 815 (147 70)	1 - 75 76 - 150
25 26 27 28	160	I II III IV	6 880 (174 75)	6 590 (167 39)	79	5 925 (150 50)	6 190 (157 23)	1 - 80 81 - 160
29 30 31 32	180	I II III IV	7 630 (193 80)	7 340 (186 44)	89	6 675 (169 55)	6 940 (176 28)	1 - 90 91 - 180

1/ Dash numbers 17 through 32 are for style 2 (external keying) connectors

(E) FIGURE 1 Connectors, receptacle, 075 (1 90 mm) spacing - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.



(E) FIGURE 1 Connectors, receptacle, .075 (1.90 mm) spacing - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
003	0 08	0625	1 588	171	4 34
004	0 10	.063	1 60	175	4 44
005	0 13	.065	1 65	176	4 47
006	0 15	067	1.70	180	4 57
010	0 25	073	1 85	185	4 70
012	0 30	075	1 90	200	5 08
014	0 36	.080	2.03	235	5 97
015	0 38	081	2 06	242	6 15
018	0 46	083	2 11	248	6 30
019	0 48	085	2 16	250	6 35
020	0 51	087	2 21	255	6 48
022	0 56	096	2 44	260	6 60
025	0 64	101	2 57	298	7 57
027	0 69	108	2 74	300	7 62
028	0 71	109	2 77	305	7 75
030	0 76	113	2 87	315	8 00
031	0 79	125	3 18	330	8 38
032	0 81	130	3 30	332	8 43
040	1 02	135	3 43	340	8 64
045	1 14	136	3 45	400	10 16
050	1 27	140	3 56		

NOTES

1. Dimensions are in inches
2. Metric equivalents are given for general information only
3. Unless otherwise specified, tolerance is ± 005 (0.13 mm) on decimals and ±2° on angles
4. These connectors mate with connectors specified in MIL-C-55302/23
5. Use printed circuit boards with the type III receptacle
6. Minimum pad length on printed circuit board
7. Termination layout on .025 (0 64 mm) modular grid
8. (E) Numbers indicating, every 5 cavities marked or molded on side (except 10 position) Numbers indicating end cavities and lines indicating every 5 cavities molded or marked on mating face
9. Location indicators embossed on surface

(E) FIGURE 1 Connectors, receptacle, 075 (1 90 mm) spacing - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Design and construction.

Dimensions and configuration. See figure 1

Material.

(E) Insulator body Insulator material shall be in accordance with MIL-C-55302 or MIL-M-24519 type GLCP-30F

(E) Contact material Contact material shall be in accordance with MIL-C-55302 or beryllium copper alloy CDA174 in accordance with ASTM B768

Plating

Engagement area Gold per MIL-C-55302 for 100 length, over nickel all over per MIL-C-55302

Termination area Tin lead over nickel per MIL-C-55302 for the following lengths

165 minimum length for type I, 200 minimum length for type II
300 minimum length for type III, 140 minimum length for type IV

Contact identification See figure 1

Contact rating. 3 0 amperes maximum per contact, 2 25 amperes continuous per contact at 75°F

Keying See MIL-C-55302/31

Oversized pin exclusion (sockets only) 0465 diameter pin

Contact separation force The connector shall meet the requirements of MIL-C-55302/29

Wire size Number 26 AWG maximum with type II, solder eyelet contact for wire termination

Resistance to test probe damage The connector shall meet the requirements of MIL-C-55302/30

Mating and unmating The maximum mating force in pounds shall be the number of contacts multiplied by 25 and the withdrawal force in pounds shall be a minimum of 025 times the number of contacts and shall not exceed the measured insertion force

Contact resistance The average contact resistance of all contacts measured shall not exceed 015 ohm, and no individual contact pair shall have a resistance exceeding 020 ohm

Contact retention 3 pounds minimum

Dielectric withstanding voltage

Sea level 900 volts rms

High altitude. 200 volts rms

Replacement contacts See MIL-C-55302/32

Contact removal tool See MIL-I-81969/01

Part number M55302/25- (dash number from figure 1)

Patent number 3,404,367 The Government has a royalty free license under this patent for the benefit of manufacturers of the item either for the Government or for use in equipment to be delivered to the Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians
Army - CR
Navy - EC
Air Force - 17

Review activities
Army - AR, MI
Navy - AS, OS, SH
Air Force - 11, 99
DLA - ES

User activities
Army - AT, AV, ME
Navy - MC
Air Force - 19

Preparing activity
Army - CR

Agent
DLA - ES

(Project 5935-3858-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.