INCH-POUND
MIL-C-70683A (AR)
AMENDMENT 1
13 August 1996

MILITARY SPECIFICATION

CHARGE, DEMOLITION: 40LB, CRATERING
PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-C-70683A (AR), dated 22 August 1991, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, under SPECIFICATIONS, MILITARY: Add the following military specifications:

"MIL-P-48395 - Pellets, Explosive Compositions (For Use in Ammunition)

MIL-E-14970 - Explosive Composition A5".

PAGE 2

2.1.2, under PUBLICATION: Delete "FM 5-25" and substitute "FM 5-250".

PAGE 3

3.3: Delete in its entirety.

3.5: Delete in its entirety and substitute the following:

"3.5 Functioning. The loaded assembly, Part Number 9395714, shall completely function when initiated by blasting cap or detonating cord. The loaded assembly, Part Number 9395714-1, shall completely function when initiated by one (1) M112 Demolition Block."

AMSC N/A FSC 1375
DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

PAGE 5

4.3.1:

Delete "Clip" and substitute "*Clip".

Delete "Clip Assembly" and substitute "*Clip Assembly".

Delete "Pellets, Booster 9295839 5".

Add to end of paragraph: "* - required only for charge Part Number 9395714"

PAGE 6

TABLE I, sheet 1 of 3: Delete "Pellet, Booster" in its entirety.

PAGE 7

TABLE I, sheet 2 of 3:

Delete "CLIP" and substitute "CLIP 1/".

Delete "CLIP ASSEMBLY" and substitute "CLIP ASSEMBLY 1/".

Add new note as follows:

"1/ Required only for charge Part Number 9395714.

PAGE 8

TABLE I:

Charge, Demolition: 40lb., Cratering: Delete in its entirety and substitute the following:

"Charge, Demolition: 40 lb., Cratering
(Dwg. 9395714)

Examination for defects	20, 0-1	3.2	4.4.2.13
Waterproofness	20, 0-1	3.4	4.5.2
Functioning	20, 0-1	3.5	4.5.5"

PAGE 14

4.4.2.4: Delete in its entirety and substitute new 4.4.2.4 included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-C-70683A
AMENDMENT 1

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Pellet, Booster	1 OF 1	9395839
			NEXT HIGHER ASSEMBLY 9395842

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Compliance with MIL-P-48395 (Note 1)		3.2	Certificate of Test and Analysis
Minor 201	Poor workmanship	Level V	3.7	Visual

NOTES:
If using Alternate Moisture Content Requirement as per Note 5, Dwg. 9395839, a certificate of Test and Analysis shall also be provided to show compliance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

PAGE 17

4.4.2.7, TITLE: Delete "Clip" and substitute "Clip (required only for charge Part Number 9395714)".

PAGE 18

4.4.2.8, TITLE: Delete "Clip, Assembly" and substitute "Clip Assembly (required only for charge Part Number 9395714)".

PAGE 20

4.4.2.10, Major 102: Delete "True position of clip assembly (2 places)" and substitute "True position of clip assembly (2 places) (required only for charge Part Number 9395714)".

PAGE 23

4.4.2.13:

Major 102: Delete in its entirety and substitute "102 Functioning 5, 0-1 3.5 4.5.5 (Note 1/)".

Major 103: Delete in its entirety.

Major 104: Delete in its entirety.

Major 105: Delete in its entirety and substitute "105 Max. Height (Does not apply to 9395714-1) Level III 3.2 Gage".

Add new note as follows:

"1/ After three consecutive lot acceptance tests of 5 samples, the quantity shall be reduced to 3 samples. In event of a failure, the quantity of lot acceptance test samples shall revert back to 5 until 3 successive lots meet the requirement specified."

PAGE 26

4.5.1: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.

4.5.3: Delete in its entirety and substitute the following:

"4.5.3 Strength of handle. The cover top assembly shall be assembled to the applicable test equipment and a 100 lb. static load applied to the handle (see drawing 9395852, Note 4). Observation shall be made for failure of a weld or handle. Either defect shall class a unit defective."

4.5.5: Delete in its entirety and substitute the following:

"4.5.5 Functioning. All charges shall be tested above ground, observing all the safety requirements of FM 5-520. All charges are to be primed and initiated IAW applicable sections of TM 9-1375-213-12. Observation shall be made for complete detonation of the charge. Any charge failing to so function shall be classed defective.

4.5.5.1 Charge Part Number 9395714 (NSN 1375-01-250-6029-M039). Half the sample shall be tested IAW 4.5.5.1.1 and half IAW 4.5.5.1.2.

4.5.5.1.1 Functioning with blasting cap. Blasting caps shall comply with Type II of MIL-C-14003. A sand bag, maximum weight of 40 lbs., shall be placed on top of the charge to simulate stemming by soil.

4.5.5.1.2 Functioning with detonating cord. Detonating cord shall comply with Type I, Class E of MIL-C-17124. Pass the detonating cord through the shorter tunnel. A "uli" knot shall be made 24 inches from one end of the cord and drawn snugly against the tunnel, the knot positioned above the charge booster. A sand bag, maximum weight of 40 lbs., shall be placed on top of the charge to simulate stemming by soil. A blasting cap shall be attached to the other end of the cord and the cord shall be detonated.

4.5.5.2 Charge Part Number 9395714-1 (NSN 1375-01-378-9669-M039). Only one (1) M112 Demolition Block per charge shall be used."

PAGE 27

4.5.6: Delete in its entirety.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-0037)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:52Z
Check the source to verify that this is the current version before use.