W-L-00116/50
September 23, 1977

INTERIM FEDERAL SPECIFICATION SHEET

LAMP FLUORESCENT
TRADE NO. F40D, RAPID START, 35 WATT,
T-12 BULB, DAYLIGHT, MEDIUM BIPIN BASE
(DETAIL SPECIFICATION)

The complete requirements for Lamp, Fluorescent described herein shall consist of this document and the latest issue of W-L-00116/GEN.

This Interim Federal Specification Sheet was developed by General Services Administration, Federal Supply Service, Mechanical and Electrical Division, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification Sheet as a valid exception to W-L-116A, dated June 23, 1964.

Requirements.

TABLE I.

Lamp Size		Base	Color	Required Life (hours)	Minimum Lumens	
Nominal Watts	Bulb				at 100 hours	at 40% of Life
35	T-12	Medium Bipin	Day-light	20,000	2200	1850

Dimensions: A deviation in dimension from ANSI C78.700 shall be considered a defect.

Notes: 1. Lamp should not be used in ambient temperatures less than 65°F.

2. Lamp should only be used with rapid start ballast.

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:24Z
Check the source to verify that this is the current version before use.