W-L-00200c(GSA-FSS)
August 7, 1968
SUPERSEDING
Int. Fed. Spec. W-L-00200b(GSA-FSS)
May 5, 1967 and
INTERIM REVISION OF
Fed. Spec. W-L-200
November 18, 1955

# INTERIM FEDERAL SPECIFICATION

## LANTERN, ELECTRIC

This Interim Federal Specification was developed by General Services Administration, Federal Supply Service, Standardization Division, Washington, D.C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification W-L-200, dated November 18, 1955.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers electric hand lanterns, dry cell battery operated, of the floating and non-floating types. These lanterns are not for use in explosion-hazard areas or designed for underwater use.

1.2 Classification

1.2.1 Types. The electric lanterns shall be of four types as follows:

Type I - Single beam. (Concentrated light beam.)
Type II - Two beam. (One concentrated light beam and one diffused light beam.)
Type III - Floating, Warning flasher and Single beam (Concentrated light beam.)
Type IV - Warning Flasher and Single Beam (Concentrated Beam), Safety Lantern.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

W-B-101 - Battery, Dry.
MMM-A-250 - Adhesive, Water-Resistant (For Sealing Fiberboard Boxes).
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Set-up, Paperboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specification, Standards and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:
MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes,
MIL-STD-129 Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specified procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction sample. When so specified in the invitation for bids, a preproduction sample of the lantern shall be submitted to the contracting officer for test and approval (see 6.2).

3.2 Material. All materials shall be suitable for the use intended and shall be free from defects which might affect their serviceability or appearance. Dissimilar metals shall not be used in intimate contact with each other unless protected against electrolytic action.

3.3 Construction. The lanterns shall be of sturdy construction capable of meeting the test requirements of section 4.

3.4 Finish. All external metal parts of the lantern shall be corrosion-resisting or have a corrosion-resisting finish applied by plating or enameling.

3.5 Design, general. The lanterns shall be complete units including battery container, light source or sources, switch and handle. They shall utilize the current drawn from one 6-volt lantern battery (battery not included with lantern) designated 4F in Federal Specification W-B-101. The lantern shall be capable of being carried by the handle, or of standing on the base without other support. The concentrated light source shall be capable of projecting its beam horizontally without interference from the lantern either when standing or being carried. The switch shall provide a positive instantaneous means of energizing or de-energizing the light source. Where there is no specific reference herein as to type I, II, III, or IV the requirements shall apply fully to each type.

3.5.1 Type I. The type I lantern shall be capable of producing and projecting a concentrated light beam of nearly parallel rays having characteristics which conform to 3.8.1.

3.5.2 Type II. The type II lantern shall be capable of producing and projecting a concentrated light beam equal to that of type I lanterns (see 3.5.1) and also an independent diffused light beam having characteristics which conform to those required in 3.8.2. The switch shall provide a positive instantaneous choice of either light source.

3.5.3 Type III. The type III lantern shall be capable of producing and projecting a concentrated light beam equal to that of type I lanterns (see 3.5.1). The type III lanterns shall also be capable of floating and conform to the requirements in 3.9. In addition, a red flashing light (diffused beam) shall be required. The switch shall provide a positive instantaneous choice of either or both light sources.

3.5.4 Type IV. The type IV lantern shall be capable of producing and projecting a concentrated light beam equal to that of type I lanterns (see 3.5.1). In addition, a red flashing light (diffused beam) shall be required. The switch shall provide a positive instantaneous choice of either or both light sources.

3.6 Component Parts.

3.6.1 Battery container. The battery containers of type I and type II lanterns shall be of metal and of a size and shape to accommodate one 4F 6-volt lantern battery (see Federal Specification W-B-101) and other necessary wiring and contacts. The container lid shall be suitably fitted to retain the battery in proper position when subjected to the tests in section 4. No tools shall be required to remove or replace the battery.

3.6.1.1 Lantern case, type III. The type III lantern case shall be of high density translucent plastic and of a size and shape to accommodate one 4F 6-volt lantern battery, a single concentrated light beam assembly a warning flasher assembly, a four position switch, necessary wiring and contacts. A positive means of enclosing and holding the battery secure in the lantern case shall be provided. No special tools shall be required to remove or replace the lamp or battery.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

3.6.1.2 Lantern case, type IV. The type IV lantern case shall be of a size and shape to accommodate one 4F 6-volt lantern battery and be suitably fitted to retain the battery in proper position when subjected to the tests of section 4. The case shall be of corrosion-resisting metal or a metal having a corrosion-resisting finish applied by plating or enameling both internally and externally. No tools shall be required to remove or replace the lamps or battery.

3.6.1.3 Instructions. The type I and type II battery container shall have suitable instructions permanently affixed inside for proper installation of battery. The instructions shall be embossed, stenciled, or printed. Type III case shall have instructions for removing battery embossed on lantern case. The type IV case shall have instructions for lamp and battery installation on outside of case.

3.6.2 Handle. The type I and type II lantern shall have a suitable handle of metal for carrying the lantern in the hand. The handle shall distribute the weight of the lantern without excessive strain on any part and shall not interfere with the projected light beam or beams when the lantern is standing on its base. The type III handle shall be part of the formed plastic case.

3.6.3 Switch, general. There shall be a switch provided in the electrical circuit which shall be completely enclosed except for its actuating member. The actuating member shall be on the outside of the lantern and the type II lantern respective switch positions shall be suitably and permanently marked on the exterior of the lantern. If of metal, the exposed actuating member shall be suitably insulated from the electrical circuit to prevent accidental discharge of the battery through contact with any exterior metal part of the lantern. The switch shall be constructed to resist accidental movement from one position to another. If switch blades close the lantern circuit by making contact with internal metal parts, those metal parts shall be insulated from contact with any exterior metal part of the lantern.

3.6.3.1 Switch, type I. The switch provided in type I lanterns shall have an "on" and an "off" position. In addition, a flash or signaling switch position may be provided.

3.6.3.2 Switch, type II. The type II lantern switch shall have not less than three positions including "on", "off", and "on", to permit operation of either the concentrated or diffused light beam.

3.6.3.3 Switch, type III and IV. The type III and IV lantern switch shall have not less than four positions including "on single concentrated beam", "on flasher", "on both concentrated beam and flasher", "off all beams", to permit operation of either beam, individually, or simultaneous use of both light beams.

3.6.4 Reflector head assembly, general. The reflector head assembly shall consist of those parts of the lantern which accomplish conversion of the electrical energy of the battery into visible light and the projection of that light as a concentrated, or as a diffused beam of light or flasher. The essential parts of the assembly shall be a lamp, lampholder, reflector, lens, reflector and lens retaining ring, and assembly casing. All ferrous-metal parts of the reflector head assembly except current-carrying parts shall have a baked-enamel or electroplated finish to prevent corrosion.

3.6.4.1 Concentrated light, reflector head assembly, type I. Type I lanterns shall be equipped with prefocused light sources either of the sealed beam type with integral reflector, lens, filament and screw-type terminals, trade No. 4546, PAR-36, 4.7 volts, 0.50 ampere or trade No. 4506, PAR-36 4.7 volts, 0.47 ampere or approved equal; or have separate reflectors which are essentially parabolic in shape and have an aluminized or silver plated specular finish. Silverplated reflectors shall be protected by clear lacquer. The separate reflector shall be used with a single contact, miniature, flanged base lamp trade No. PR-15, 4.62 volts, 0.50 ampere or trade No. PR-13, 4.75 volts, 0.50 ampere, or approved equal, and a lampholder so located with respect to the reflector that when the lamp and reflector are in fully assembled position, the lamp filament is approximately at the focal point of the reflector. The lampholder shall hold the lamp in position by means of a suitable cap and the electrical contact with the lamp base shall be made by a helical coiled spring or other suitable means to prevent transmission of physical shock to the lamp base. The lens, when separate, shall be of clear glass; or plastic, if so specified (see 6.2) not less than 0.117 (2.97 millimeters) thick and be free of bubbles, striae, checks or cracks and the effective lens area for light transmission with the retaining ring in place shall be not less than 2-3/4 inches (69.85 millimeters) in diameter.

3.6.4.1.1 Reflector head assembly movement, type I. The reflector head assembly of type I lanterns shall be capable of being rotated through a vertical angle of not less than 90° when the lantern is resting on the base. The angle through which the reflector head assembly rotates shall be measured upward from 10° below the horizontal when the lantern is resting on its base on a horizontal plane. The reflector head assembly shall remain as positioned when the lantern is subjected to movements similar to those expected during normal use.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

3.6.4.2 Diffused light reflector head assembly, type II. The diffused light beam producing reflector head assembly shall be provided with a miniature screw-base lamp, trade No. 502, 5.1 volts, 0.15 amperes or approved equal. The lampholder shall be a miniature screw base shell which may be an integral part of the reflector. The reflector shape shall be at the option of the manufacturer and the reflector surface shall be silver plated or aluminized with a matte or semi-matte finish if the lens provided is of clear glass or plastic. The reflective surface of the reflector shall be specular if the lens provided is of the bulls-eye or honeycomb type. The lens shall be of glass; or plastic, if so specified (see 6.2), not less than 0.117 inch (2.97 millimeters) thick. The effective light transmitting area of the lens shall be not less than 2-3/4 inches (69.85 millimeters), nor more than 3-1/2 inches (88.90 millimeters) in diameter. A suitable metal guard shall be provided to protect the reflector head assembly. The guard shall not obstruct the light beam and be sturdy enough to withstand the rigidity test given in 4.4.6. The diffused light reflector head assembly shall be capable of projecting its beam of light in a vertical direction when the lantern is standing on its base.

3.6.4.3 Concentrated light reflector and flasher assemblies, type III. All essential parts of these assemblies shall be integral to the case. The concentrated light beam assembly shall be provided with a miniature flanged base lamp, trade No. PR-13, 4.75 volts, 0.50 amperes, or equal source, yielding the equivalent luminous intensity. The lampholder shall be so located with respect to the reflector that when the lamp and reflector are in fully assembled position, the lamp filament is approximately at the focal point of the reflector. Electrical contact with the lamp base shall be made by a helical coiled spring or other suitable means to prevent transmission of physical shock to the lamp base. The reflector shall be essentially parabolic in shape and have an aluminized specular finish. The lens shall be of a strong clear plastic, capable of meeting the test requirements of 4.4.7, 4.4.8 and 4.4.11 and be free of bubbles, striae or cracks and the effective lens area for light transmission with the retaining ring in place shall be not less than 2.750 inches (69.85 millimeters) in diameter. The diffused flasher light shall have a miniature screw base lampholder and a miniature screw base flasher lamp, trade No. 407, 4.90 volts, 0.30 amperes, or equal source, yielding the equivalent luminous intensity. The flasher assembly shall be mounted behind the concentrated light beam assembly and be visible through the translucent red plastic lantern case.

3.6.4.4 Concentrated light reflector and flasher assemblies, type IV. The concentrated light beam assembly shall be mounted on the lantern case. The lampholders shall be a miniature screw or flange type base provided with a miniature prefocused lamp to fit the lampholder. The lamps shall be either trade no. 27, 4.9 volts, 0.30 amperes, miniature screw-base or trade no. PR-13, 4.75 volts, 0.50 amperes, miniature flanged-base single contact or equal sources, yielding the equivalent luminous intensity. The concentrated light reflector shall be essentially parabolic in shape and have an aluminized specular finish. The lens shall be of a strong clear plastic, capable of meeting the test requirements of 4.4.8 and be free of bubbles, striae or cracks. The effective lens area for light transmission assembled with reflector shall not be less than 2.750 inches (69.85 millimeters) in diameter. The diffused flasher light shall have a miniature screw-base lampholder and a miniature screwbase flasher lamp, trade No. 407, 4.90 volts, 0.30 amperes, or equal source, yielding the equivalent luminous intensity. The flasher assembly shall be mounted on top of lantern case. The flasher assembly shall be covered with a translucent red plastic dome locking securely to the case. The flasher and dome assembly shall conform with requirements in 3.8.3 and be capable of meeting the test requirements as specified in 4.4.7 and 4.4.8.

3.6.4.5 Stand and carrying bail. The type IV lantern shall be provided with a stand fabricated from heavy gage wire or sheet metal. The carrying bail shall be formed from either heavy gage wire or a plastic material with a diameter not less than 0.375 inch (9.52 millimeters). The carrying bail shall be pivoted at or near the center of gravity of the lantern case, with battery installed, so as to permit the lantern to be rotated 360°. The carrying bail shall be connected to the case at the point of pivot by a friction means using either adjusting nuts or spring tension to permit the lantern to be adjusted firmly in place. The carrying bail and stand shall not crack, break or warp when tested as specified in 4.4.8.

3.6.5 Base. The lanterns shall have a suitable base which will provide a stable platform when subjected to test under the conditions stated in 4.4.6 and 4.4.7. The base is defined as that surface which is intended by the manufacturer to serve as the support or bottom of the lantern.

3.7 Wiring and connections.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

3.7.1 Current-carrying parts. Internal current-carrying springs and switch contacts shall be of commercial grade or better spring brass, phosphor bronze or beryllium copper. All other electrical current-carrying parts may be constructed of the above stated materials or suitable materials having the proper electrical conductivity characteristics and cross-sectional area for purpose intended. Bare, fixed conductors shall be securely held in position by rivets or other suitable means and be suitably insulated from contact with any metallic part of the outside of the outside of the lantern. Eyelets rivets or other fasteners shall not be used on current-carrying parts if the produce openings to the interior of the battery container or reflector head assembly.

3.7.2 Lamp lead wires. Lamp lead wires, if used, shall be flexible, rubber or plastic insulated not lighter than No. 22 AWG., and the terminal ends shall be permanently attached to the lampholder terminals; or in the case of sealed beam lamps be provided with permanently attached closed wire terminal lugs of suitable size for connection to the lamp terminals. Lamp lead wires shall be of ample length to permit replacement of parts and to permit normal movement of lantern parts without binding, chafing, or rubbing.

3.7.3 Circuits. The lantern electrical circuits shall be designed so that it shall be impossible to energize the lamp by making contact between any two points on the exposed exterior surface of the lantern when subjected to the test described in 4.4.9

3.7.4 Chafting protection. All openings in the battery container or reflector head assembly casing through which lead wires pass shall be smooth and well rounded or be provided with grommets or other suitable means to prevent chafting.

3.8 Performance.

3.8.1 Light characteristics, concentrated light, type I, type II and type III. The light beam produced by the concentrated light reflector head assembly shall consist of essentially parallel rays. When projected onto a screen whose plane is perpendicular to the optical axis of the light assembly being tested and 5 feet (1.524 meters) distant from the face of the lens the concentrated beam shall be not greater than 9 inches (228.60 millimeters) in diameter and be relatively free of shadows and filament images. Conformance of light characteristics shall be determined under the conditions stated in 4.4.2.

3.8.2 Light characteristics, diffused light, type II. The type II lantern diffused beam of light shall, when tested under the conditions of 3.8.1 and 4.4.3 produce and image on the screen not less than 60 inches (1.524 meters) nor more than 80 inches (2.032 meters) in diameter. The image shall be essentially circular with no shadows from the guard or handle.

3.8.3 Light characteristics, flasher light, type III and IV. The type III and IV lantern flasher light shall be visible a minimum of one-half mile (0.804 kilometers) and cycle at least 90 conditions stated in 4.4.4.

3.8.4 Switch. The switch shall be capable of completing 25,000 cycles of operation without breakage or apparent wear or becoming electrically inoperative. A cycle shall be from "off" through all "on" positions and back to "off".

3.8.5 Stability. The assembled lantern, including battery, shall be capable of standing without other support and shall not tip, fall or roll when placed on its base or stand on a plane surface inclined 15° from the horizontal in the positions stated in 4.4.6.

3.8.6 Rigidity. While standing on its base on a horizontal plane, the lantern shall be capable of withstanding a compressive load of 50 pounds (22.679 kilograms) in accordance with the requirements of 4.4.7.

3.9 Watertightness. The type III lantern only shall be watertight and show no leakage of water into its interior when tested as specified in 4.4.10 and 4.4.11.

3.10 Workmanship. The lantern workmanship shall be free from defects which will affect the appearance of the lanterns or impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure that suppliers and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

4.2 Sampling for acceptance inspection.

4.2.1 Sampling for group A inspection and tests. Sampling for group A inspection shall be in accordance with MIL-STD-105, inspection Level II (AQL) 2.5 and each sample lantern unit shall be subjected to the group A tests listed in Table I.

4.2.2 Sampling for group B tests. Sampling for group B tests shall be in accordance with MIL-STD-105, Inspection Level S2, (AQL), 4.0, and each sample lantern unit shall be subjected to the group B tests listed in Table I.

4.2.3 Sampling for group C tests. Group C tests will be required initially and thereafter only when the basic design of the equipment has been changed. One complete lantern unit (with battery installed), shall be subjected to the group C tests listed in Table I.

TABLE I

| Examination and Tests | Requirement Paragraph | Test Paragraph |
|---|---|---|
| Group A | | |
| General Examination | 3.2,3.4,3.5 2.5.1,3.5.2 3.5.3,3.5.4,3.6.1, 3.6.1.1,3.6.1.2, 3.6.2, 3.6.3.,3.6.4, 3.6.5,3.7,3.10 | 4.4.1 |
| Group B | | |
| Performance | | |
| Light characteristics, concentrated light, type I, type II, type III and IV | 3.8.1 | 4.4.2 |
| Light characteristics, diffused Light, Type II | 3.8.2 | 4.4.3 |
| Light characteristics, flashing light, type III and type IV | 3.8.3 | 4.4.4 |
| Group C | | |
| Switch | 3.8.4 | 4.4.5 |
| Stability | 3.8.5 | 4.4.6 |
| Rigidity | 3.8.6 | 4.4.7 |
| Drop test | — | 4.4.8 |
| Circuit test | 3.7.3 | 4.4.9 |
| Float test (type III only) | — | 4.4.10 |
| Watertightness (type III only) | 3.9 | 4.4.11 |

4.3. Acceptance inspection.

4.3.1 Acceptance group A and B examination and tests. The results of each examination and test shall be compared with the requirements of this specification. Failure to conform to the requirements of this specification for any tests shall be counted as a defect, and the lantern unit shall be rejected. If the number of such nonconforming lantern units in any sample exceeds the acceptance number of that sample, the lot represented by the sample shall be rejected.

4.3.2 Acceptance group C tests. The result of each test shall be compared with the requirements of this specification. In the event of failure to conform to the requirements of this specification for any group C tests, the lot represented by the sample shall be rejected.

4.4 Inspection and tests.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

4.4.1 General. Each type I, II, III or IV lantern unit in the sample shall be given a thorough mechanical and visual inspection to determine compliance with the requirements of this specification. Particular attention should be given to:

(a) Materials
(b) Finishes
(c) Completeness
(d) Instructions
(e) Handle
(f) Wiring and connections
(g) Accessibility of components and parts for servicing
(h) Access components (all threads and fastners shall bold tight and secure to prevent accidental opening).

4.4.2 Concentrated light beam test. The type I, II, III and IV lanterns shall be tested for compliance with the concentrated light performance requirements of 3.8.1. The test shall be conducted in a dark room and the lantern shall be equipped with fresh batteries.

4.4.3 Diffused light beam test, type II. Compliance with the diffused light performance requirements of 3.8.2 shall be determined for type II lanterns in a dark room with fresh batteries installed.

4.4.4 Flasher light test, type III and IV only. Compliance with the flasher light performance requirements of 3.8.3 shall be determined in a clear dark outdoor atmosphere with a fresh battery installed.

4.4.5 Switch test. The lanterns with batteries and lamps in place shall have each switch operated in a normal manner at a rate not to exceed 20 cycles per minute for a total of 1,00 cycles. A cycle shall be from "off" through all "on" positions and back to "off". Mechanical defects or faulty electrical operation of the switch shall constitute failure of the test. Lamps and batteries shall be replaced as required during the test. Failure of the lamps or batteries shall not be grounds for rejection.

4.4.6 Stability test. The lanterns with batteries in place shall be placed on a plane inclined as stated in 3.8.4 and shall be free standing when placed in any of seven different equally spaced positions about an axis perpendicular to the plane of the inclined surface. The surface of the plane shall be rough enough to prevent sliding.

4.4.7 Rigidity test. The assembled lanterns shall be subjected to an evenly distributed compressive load of 50 pounds (22.679 kilograms) applied vertically without shock to the top of the lantern. (Type II lanterns shall have the compressive load applied to the diffused light guard when the diffused reflector head assembly is pointing vertically). The load shall remain for five minutes. Examination shall disclose no permanent deformation or breakage of parts as a result of the test.

4.4.8 Drop test. The lantern with battery installed shall be dropped six times from a height of three feet (0.914 meter) into a box of loose, dry sand having a minimum depth of one foot (304.80 millimeters) and resting on a stable horizontal base. The lantern shall fall three times each on the base and top. No permanent deformation or breakage shall occur for type III. Type I and II breakage of the lens, or operating difficulty may occur as a result of this test. The lid of the battery case shall remain fastened during the test. The surface of the sand shall be leveled after each drop.

4.4.9 Circuit test. The assembled lantern with fresh battery installed and the switch in the "off" position shall be placed in all possible positions on a flat steel surface not less than 12 by 12 inches (304.80 by 304.80 millimeters) in area. The lamp shall not be energized as a result of this test.

4.4.10 Float test. The type III lantern only, completely assembled including battery, shall be allowed to float for 2 hours in sea water (or liquid of equal specific gravity). At the beginning and end of this period the lantern case shall not be less than one inch (25.40 millimeters) above the surface of the water.

4.4.11 Watertightiness. The type III lantern only, complete with battery, shall be submerged in salt water (3 percent aqueous solution of NaCl) at a head of three feet (0.914 meter) for a period of 30 minutes. At the end of this period the lantern shall be removed and the outside dried by wiping. The lantern shall then be disassembled and examined to verify compliance with 3.9.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

4.5 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing and marking requirements as required by section 5 of this specification are complied with. Defects shall be scored in accordance with table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping container fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

TABLE II. Classification of Preparation for delivery defects

| Examine | Defect |
|---|---|
| Markings (exterior and interior containers) | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application. |
| Materials | Any component missing or damaged. |
| Workmanship | Inadequate application of components such as: Incomplete closure of container, loose strapping. Bulging or distortion of containers. |
| Packaging and packing | Packages improperly sealed. Case liner omitted. Case liner not sealed. |

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each lantern shall be packaged in accordance with method IC-2 of MIL-P-116.

5.1.2 Level B. Each lantern shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, PPP-B-676 or PPP-B-636, class domestic.

5.1.3 Level C. The lanterns shall be packaged to afford protection against deterioration and damage during shipment from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Lanterns of one type in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-601, overseas type or PPP-B-621, class 2. The boxes shall be closed and strapped in accordance with the appendix to the applicable box specification. When the gross weight exceeds 250 pounds, skids shall be provided in accordance with the applicable box specification.

5.2.2 Level B. Twelve unit packages of lanterns of one type shall be packed in a closefitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with method I of the appendix to the box specification.

5.2.3 Level C. The lanterns shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3. Standard packaging (civil agencies). The standard packaging and packing for civil agencies shall be as specified in 5.1.2 and 5.2.2, respectively.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

5.4.Marking

5.4.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 Military agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.

6.1.1 Type I lanterns are intended for use in the illumination of objects at a distance as in general outdoor use.

6.1.2 Type II lanterns can be used for distant illumination or for illumination over a relatively wide area of objects closer to the observer.

6.1.3 Type III floating lanterns can be used for distant illumination or for a flashing warning light in general outdoor use.

6.1.4 Type IV safety lanterns can be used for distant illumination or for a flashing warning light in general outdoor use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type (see 1.2.1).
(c) Preproduction sample if required (see 3.1).
(d) Plastic lens, if required (see 3.6.4.1 and 3.6.4.2).
(e) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
(f) Quantity of unit packages of lanterns required in shipping container (see 5.2.1).

6.3 It is belived that this specification adequately describes the characteristics necessary to secure the desired material, and that normally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

6.4 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of the specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured for Federal Government requirements.

6.6 Standard pack for civil agencies. The standard pack requirements in 5.3 are intended for use in procurements of stores stock replenishments. Procuring officers should use the standard pack requirements when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot or intermediate storage point for temporary storage, subsequent issue or shipment to eventual user.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.