FEDERAL SPECIFICATION SHEET

REELS, PLASTIC AND FIBERGLASS, WITH 5/16-INCH CENTER HOLE

This amendment, which forms a part of W-R-175/1D, dated 22 December 1986, is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 7

Under Qualification: Delete and substitute:

"1. The qualification sample for 0.250-inch tape width "KA" through "NA" reels shall consist of 20 completely assembled type ER-250-NA reels. Qualification of the sample reels ER-250-NA shall constitute qualification for all 0.250-inch tape width "KA" through "NA" reels constructed of the same material as the reels tested.

2. The qualification sample for 0.250-inch tape width "PA" reels shall consist of 20 completely assembled type ER-250-PA reels. Qualification of the sample reels ER-250-PA shall constitute qualification for only those "PA" reels constructed of the same material as the reels tested.

3. The qualification sample for 0.500-inch tape width reels without friction rings shall consist of 20 completely assembled type ER-500-NA reels without friction rings. The qualification sample for 0.500-inch tape width reels with friction rings shall consist of 10 completely assembled type ER-500-NA reels with friction rings and 10 completely assembled type ER-500-NA reels without friction rings. Qualification of the sample reels ER-500-NA without friction rings shall constitute qualification for all W-R-175/1 0.500-inch tape width reels without friction rings which are constructed of the same material as the reels tested. Qualification of the sample reels ER-500-NA with friction rings shall constitute qualification of all W-R-175/1 0.500-inch tape width reels with and without friction rings which are constructed of the same material as the reels tested.

AMSC N/A FSC 5835
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

4. The mounting surface parallelism and outside hub surface cylindricity measurements shall be made on completely assembled reels."

MILITARY INTERESTS:

Custodians

Army - CR
Navy - SH
Air Force - 99

Review activities

Navy - NV, OM
Air Force - 80
DLA - ES

User activity:

Navy - AS

CIVIL COORDINATING ACTIVITY:
NASA - NPPO

Preparing activity:
Navy - SH
(Project 5835-0090-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.