W-R-175/2D
AMENDMENT-1
March 23, 1988

FEDERAL SPECIFICATION SHEET

REEL, HUBS, FIBERGLASS AND METALLIC,
WITH 3-INCH CENTER HOLE

This amendment, which forms a part of W-R-175/2D, dated 22 December 1986, is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

Table I, under hub dimensions for "angle between successive keyslots and flange mounting holes for hubs only": Delete and substitute:

"

Characteristic[3]	Tape width indicator	Dimensions			
		"RB" hubs		"RC" hubs	
		maximum	minimum	maximum	minimum
Angle between[4] (R) successive keyslots and flange mounting holes for hubs		60.5 (1.056rad)	59.5 (1.038rad)	60.25 (1.052rad)	59.75 (1.043rad)

"

PAGE 4

Table I, under hub dimensions for "inside hub surface cylindricity (FF)": Delete and substitute:

"

Characteristic[3]	Dimensions			
	"RB" hubs		"RC" hubs	
	maximum	minimum	maximum	minimum
Inside hub surface cylindricity (FF)	.003 (0.076)		.002 (0.051)	

"

AMSC N/A FSC 5835
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

PAGE 5

Under Qualification, paragraph 1: Delete and substitute:

"1. The qualification sample for "RB" hubs shall consist of 10 EH-250-RB hubs. The qualification sample for "RC" hubs shall consist of 10 EH-250-RC hubs."

MILITARY INTERESTS:

Custodians

Army - CR
Navy - SH
Air Force - 99

Review activities

Navy - NV, OM
Air Force - 80
DLA - ES

User activity

Navy - AS

CIVIL COORDINATING ACTIVITY:
NASA - NPPO

Preparing activity:
Navy - SH
(Project 5835-0090-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.