FEDERAL SPECIFICATION SHEET

# REELS, PLASTIC, FIBERGLASS, METALLIC, AND METALLIC FLANGE PHENOLIC HUB, WITH 3-INCH CENTER HOLE

This amendment, which forms a part of W-R-175/3D, dated 22 December 1986, is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 7

Table I, under "Inside hub surface cylindricity (FF)", only: Delete and substitute:

"

| Characteristic[3] | Reel and hub indicator | Dimensions | | Flange deflection limit |
|---|---|---|---|---|
| | | maximum | minimum | |
| Inside hub surface cylindricity (FF) | | .004 (0.102) in/in of width | | |

"

PAGE 8

Footnote 5(f): Delete and substitute:

"(f) The ring shall be flat on the hub and shall exhibit no visible buckling or puckering of the ring surface, cracking or slitting when mounted on the reel."

PAGE 11

Table II, column 1: After "Roughness of outside hub surface": add "(X)".

PAGE 12

Footnote 5(f): Delete and substitute:

"(f) The ring shall be flat on the hub and shall exhibit no visible buckling or puckering of the ring surface, cracking or slitting when mounted on the reel."

AMSC N/A FSC 5835

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

PAGE 13

Table III, under "Inside diameter of flange" only: Delete and substitute:

"

| Characteristic[3] | Reel and hub indicator | Dimensions | | Flange deflection limit |
|---|---|---|---|---|
| | | maximum | minimum | |
| Inside diameter of flange[5] (K) | | 3.700 (93.980)[6] | 3.600 (91.440)[6] | |

"

PAGE 14

"

| Characteristic[3] | Tape width indicator | Dimensions | | Flange deflection limit |
|---|---|---|---|---|
| | | maximum | minimum | |
| Inside hub surface cylindricity (FF) | | .002 (0.051) in/in of width | | |

"

PAGE 16

Footnote 4(f): Delete and substitute:

"(f) The ring shall be flat on the hub and shall exhibit no visible buckling or puckering of the ring surface, cracking or slitting when mounted on the reel."

PAGE 17

Under QUALIFICATION: Delete and substitute:

"1. The qualification sample for "EB", "JB", and "PB" reels without friction rings shall consist of 20 completely assembled type ER-1000-JB reels without friction rings. The qualification sample for "EB", "JB", and "PB" reels with friction rings shall consist of 10 completely assembled type ER-1000-JB reels with friction rings and 10 completely assembled type ER-1000-JB reels without friction rings. Qualification of the sample reels ER-1000-JB without friction rings shall constitute qualification for all "EB", "JB", and "PB" reels without friction rings regardless of reel width. Qualification of the sample reels ER-1000-JB with friction rings shall constitute qualification for all "EB", "JB", and "PB" reels with and without friction rings regardless of reel width.

2. The qualification sample for "EC", "PC", and "SC" reels without friction rings shall consist of 10 completely assembled type ER-500-PC reels without friction rings; five separate hubs (for the type ER-500-PC reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-500-PC reels) prior to assembly. The qualification sample for "EC", "PC", and "SC" reels with



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

friction rings shall consist of five completely assembled type ER-500-PC reels with friction rings; five completely assembled type ER-500-PC reels without friction rings; five separate hubs (for the type ER-500-PC reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-500-PC reels) prior to assembly. Qualification of the sample reels ER-500-PC without friction rings shall constitute qualification for all "EC", "PC", and "SC" reels without friction rings regardless of reel width. Qualification of the sample reels ER-500-PC with friction rings shall constitute qualification for all "EC", "PC", and "SC" reels with and without friction rings regardless of reel width.

3. The qualification sample for "ED", "JD", and "PD" reels without friction rings shall consist of 10 completely assembled type ER-1000-JD reels without friction rings; five separate hubs (for the type ER-1000-JD reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-1000-JD reels) prior to assembly. The qualification sample for "ED", "JD", and "PD" reels with friction rings shall consist of five completely assembled type ER-1000-JD reels with friction rings; five completely assembled type ER-1000-JD reels without friction rings; five separate hubs (for the type ER-1000-JD reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-1000-JD reels) prior to assembly. Qualification of the sample reels ER-1000-JD without friction rings shall constitute qualification for all "ED", "JD", and "PD" reels without friction rings regardless of reel width. Qualification of the sample reels ER-1000-JD with friction rings shall constitute qualification for all "ED", "JD", and "PD" reels with and without friction rings regardless of reel width.

4. The qualification sample for "QD", and "SD" reels without friction rings shall consist of 10 completely assembled type ER-2000-QD reels without friction rings; five separate hubs (for the type ER-2000-QD reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-2000-QD reels) prior to assembly. The qualification sample for "QD", and "SD" reels with friction rings shall consist of five completely assembled type ER-2000-QD reels with friction rings; five completely assembled type ER-2000-QD reels without friction rings; five separate hubs (for the type ER-2000-QD reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-2000-QD reels) prior to assembly. Qualification of the sample reels ER-2000-QD without friction rings shall constitute qualification for all "QD", and "SD" reels without friction rings regardless of reel width. Qualification of the sample reels ER-2000-QD with friction rings shall constitute qualification for all "QD", and "SD" reels with and without friction rings regardless of reel width.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

5. Completely assembled "EB", "EC", "JB", "PB", "PC", and "SC" reels shall be measured for mounting surface parallelism and outside hub surface cylindricity as specified in W-R-175."

MILITARY INTERESTS:

Custodians

Army - CR
Navy - SH
Air Force - 99

Review activities

Navy - NV, OM
Air Force - 80
DLA - ES

User activity

Navy - AS

CIVIL COORDINATING ACTIVITY:
NASA - NPPO

Preparing activity:
Navy - SH
(Project 5835-0090-03)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.