FEDERAL SPECIFICATION SHEET

REELS, PRECISION, ALUMINUM, WITH 3-INCH CENTER HOLE

This amendment, which forms a part of W-R-175/4D, dated 22 December 1986, is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 6

Table I, under dimensions for "flange wobble (PP)", only: Delete and substitute:

Characteristic[3]	Dimensions		Flange deflection limit
	maximum	minimum	
Flange wobble (PP)	ECP 0.015 (0.381) JCP 0.015 (0.381) PCP 0.018 (0.457) QCP 0.020 (0.508) SCP 0.020 (0.508) TCP 0.025 (0.635) UCP 0.028 (0.711)		

PAGE 7

Footnote 4 (f): Delete and substitute:

"(f) The ring shall be flat on the hub and shall exhibit no visible buckling or puckering of the ring surface, cracking or slitting when mounted on the reel."

Footnote 7, line 6: Delete "HCP" and substitute "JCP".

AMSC N/A FSC 5835
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

PAGE 8

Under Qualification: Paragraph 1: Delete and substitute:

"1. The qualification sample for reels without friction rings shall consist of 10 completely assembled type ER-1000-SCP reels without friction rings; five separate hubs (for the type ER-1000-SCP reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-1000-SCP reels) prior to assembly. The qualification sample for reels with friction rings shall consist of five completely assembled type ER-1000-SCP reels with friction rings; five completely assembled type ER-1000-SCP reels without friction rings; five separate hubs (for the type ER-1000-SCP reels) without friction rings and prior to assembly; and five separate flanges (for the type ER-1000-SCP reels) prior to assembly. Qualification of the sample reels ER-1000-SCP without friction rings shall constitute qualification for all W-R-175/4 reels without friction rings regardless of reel width and flange diameter. Qualification of the sample reels ER-1000-SCP with friction rings shall constitute qualification for all W-R-175/4 reels with and without friction rings regardless of reel width and flange diameter."

MILITARY INTERESTS:

Custodians

Army - CR
Navy - SH
Air Force - 99

Review activities

Navy - NV, OM
Air Force - 80
DLA - ES

User activity

Navy - AS

CIVIL COORDINATING ACTIVITY:
NASA - NPPO

Preparing activity:
Navy - SH
(Project 5835-0090-4)

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:25Z
Check the source to verify that this is the current version before use.