FEDERAL SPECIFICATION SHEET

REELS, PRECISION, GLASS FLANGE WITH ALUMINUM HUB,
3-INCH CENTER HOLE

This amendment, which forms a part of W-R-175/6A, dated 22 December 1986, is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 4

Table I, under "flange thickness (J)," only: Delete and substitute:

"

Characteristic[3]	Reel and hub indicator	Dimensions		Flange deflection limit
		maximum	minimum	
Flange thickness (J)		0.095 (2.413)	0.082 (2.083)	

"

PAGE 5

Table I, under "Distance between flanges at hub", only: Delete and substitute:

"

Characteristic[3]	Tape width indicator	Dimensions		Flange deflection limit
		maximum	minimum	
Distance between flanges at hub	250	0.272 (6.909)	0.268 (6.807)	
	500	.522 (13.259)	.518 (13.157)	
	750	.772 (19.609)	.768 (19.507)	
	1000	1.023 (25.984)	1.018 (25.857)	
	1500	1.522 (38.659)	1.518 (38.557)	
(N)	2000	2.022 (51.359)	2.018 (51.257)	

"

AMSC N/A FSC 5835

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

PAGE 7

Footnote 4: Delete and substitute:

"4 This dimension is exclusive of any coating used on the reel hub. The coating shall meet the following requirements:

(a) The thickness of the coating shall be 0.030 (0.762) maximum.
(b) The outside diameter of the coated hub shall be concentric to 0.010 (0.254) TIR.
(c) The outside coating surface cylindricity shall be a maximum of 0.010 (0.254).
(d) The roughness of the outside coating surface shall be no greater than 50 microinches.
(e) The coating shall meet the temperature and humidity requirements of W-R-175."

PAGE 8

Under "QUALIFICATION", paragraph 1: Delete and substitute:

"1. The qualification sample shall consist of 10 completely assembled type ER-1000-SGP reels; five separate hubs (for the type ER-1000-SGP reels) prior to coating and assembly; and five separate flanges (for the type ER-1000-SGP reels) coated but prior to assembly. Qualification of the sample reels ER-1000-SGP shall constitute qualification for all W-R-175/6 reels regardless of reel width and flange diameter."

MILITARY INTERESTS:

Custodians

Army - CR
Navy - SH
Air Force - 99

Review activities

Navy - NV, OM
Air Force - 80
DLA - ES

User activity

Navy - AS

CIVIL COORDINATING ACTIVITY:
NASA - NPPO

Preparing activity:
Navy - SH
(Project 5835-0090-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.