A-A-50055
June 23 1983

COMMERCIAL ITEM DESCRIPTION

GRINDERS AND MIXER-GRINDERS, MEAT, ELECTRIC

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification 00-G-667 for procurement of the items listed below.

Intended use. The meat grinders are intended for use in kitchens, galleys and commissaries. The mixer-grinders are intended for use in meat cutting plants and the larger commissaries.

Salient characteristics.

This commercial item description covers the following items:

Item 1 - Grinder
Size 4 - Counter top
Size 8 - Counter top
Size 20 - Counter top

Size 20 - Floor mounted
Size 30 - Floor mounted
Size 50 - Floor mounted

Item 2 - Mixer-Grinder - Floor mounted
Size 100 (100 lbs/ min. minimum production capacity)

Item 3 - Mixer-Grinder Integrated System, twin hoppers floor mounted in tandem
Size 100 (100 lbs/min. minimum production capacity)

Item 4 - Operator platform

Size indicates the minimum capacity, in pounds per minute of medium grade raw beef, which can be processed on the second grind through a 1/8 inch hole plate. Capacity for 50 Hz items shall be a minimum of 80 percent of the values specified above.

General.

Safety and sanitation. Grinders and mixer-grinders shall comply with the applicable requirements of Underwriters Laboratories Standard No. 73 and National Sanitation Foundation Standards No. C-2 and 8. The operator shall be protected against accidental contact with the feed screw by permanently secured safety guards or by the size of the feed opening.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the currentversion before use.

Knives. Knives shall be fabricated from steel, shall be removable, and shall be ground flat on the side which contacts the end plate. Knives shall have a Rockwell "C" hardness between 45 to 60.

End plates. End plates shall be fabricated from steel and shall have a Rockwell "C" hardness between 45 to 66. End plates shall mate with, and lock into, the housing and shall not rotate during operation. They shall be secured by a locking ring which can be easily tightened and removed.

Feed worm. The feed worm shall be removable from the machine body.

Motors. Motors shall have an ambient temperature rating of 40°C, be totally enclosed or drip proof, and rated for continuous duty, with over-current protection.

Operator platform. When specified, item 2 or 3 shall be furnished with a platform to facilitate operator access to the hopper. The platform shall be fabricated of aluminum, stainless steel or galvanized steel. The platform shall be 18 to 20 inches from the floor and shall be approximately 20 by 37 inches. An intermediate step and a 35 inch high guard rail on one side and one end shall be provided. The platform and step shall have a safety tread. The structure shall be stable with an operator standing on it.

Detailed requirements.

Item 1 grinders shall conform to the requirements of table I. Size 8 grinders shall be designed for counter top use and sizes 20, 30, and 50 shall be designed for floor mounting. Size 8 grinders shall have four legs or be designed for sealing to a bench or table top. Size 20, 30 and 50 grinders shall be mounted on four legs so that the centerline of the end plate is 28 $\pm$ 1 inches above the floor. A meat stomper and a stainless steel meat pan shall be furnished with each grinder. The pan for size 30 machines shall have a minimum capacity of 75 lbs of meat. The pan for size 50 machines shall have a high back and a minimum capacity of 125 lbs of meat. The stomper shall be constructed so that it cannot contact the feed worm. Motors for size 8, 20 and 30 grinders shall have motor circuit switches while the motor for size 50 grinders shall have a magnetic, across-the-line contactor breaking all incoming lines with start-and-stop control and overload protection. Size 8 grinders shall be provided with 3 wire, 6 foot cords and NEMA 5-15P attachment plugs. All other sizes shall have provisions for permanent connection to the power supply.

Item 2 grinder-mixers shall conform to the requirements of table I. The agitator shaft shall be removable for cleaning. The mixing hopper shall have a minimum capacity of 200 lbs and shall be provided with a hinged lid and a means for holding the lid in fully open position. A safety interlock shall cut power to the unit when the lid is raised 1/8 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

from the closed position. A foot switch for intermittent operation shall be furnished. The mixer-grinder shall be mounted on four swivel or two swivel and two rigid casters, two of which shall be equipped with brakes. The distance from the floor to the centerline of the end plate shall be a minimum of 23 inches. The mixer-grinder shall have a magnetic across-the-line contactor breaking all in-coming lines with a start-and-stop control and overload or solid state protection. The mixer-grinder shall have a means to allow for mixing and grinding simultaneously or for mixing only. Unless otherwise specified, controls shall be located on the right side of the unit when viewed from the grinding end. Mixer-grinders shall be supplied with 8 foot, 4 conductor, power supply cords and NEMA L15-30P attachment plugs.

Item 3 mixer-grinders shall consist of two item 2 mixer-grinders connected together to form an integrated system for continuous ground meat production. The mixer-grinders shall conform to the requirements for item 2 units and shall be identical except for leg height and connections necessary for system integration.

The final grind mixer-grinder shall be equipped with a foot operated switch. The primary grind mixer-grinder may be equipped with a mounted heavy duty switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements

Items Sizes	Item 1 Size 4	Item 1 Size 8	Item 1 Size 20 (Counter)	Item 1 Size 20 (Floor)	Item 1 Size 30	Item 1 Size 50	Item 2 Size 100	Item 2 Size 100
Capacity lbs/min (min)	4	8	20	20	30	50	100	100
Knives per item	3	3	3	3	3	3	3	3
Plates per item								
1/8 inch	1	1	1	1	1	1	1	1
3/16 inch	1	1	1	1	1	1	1	1
3/8 inch	1	1	1	1	1	1	1	1
Hopper capacity lbs (min)	-		-	-	-	-	200	200
Min. plate dia. (in.)	2-3/4	2-3/4	3-13/16	3-13/16	3-7/8	5	5	5
Min. HP	1/4	1/2	2	2	3	7-1/2	10	10 (ea)
Electrical power, domestic	115V 60 Hz 1 Ph	120V 60 Hz 1 Ph	220V 60 Hz 3 Ph	208V 60 Hz 3 Ph	208V 60 Hz 3 Ph	208V 60 Hz 3 Ph	208V 60 Hz 3 Ph	208V 60 Hz 3 Ph
Electrical power, European requirements	220V 50 Hz 1 Ph	220V 50 Hz 1 Ph	220 or 380V 50 Hz 3 Ph	220 or 380V 50 Hz 3 Ph	380V 50 Hz 3 Ph	220 or 380V 50 Hz 3 Ph	380V 50 Hz 3 Ph	380V 50 Hz 3 Ph

Source: https://assist.dla.mil -- Downloaded: 20260-26T08:38Z
Check the source to verify that this is the current version before use.

Identification plate. In addition to the marking and identification required by UL 73, the identification plate shall include the contract number and national stock number.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

Packaging.

A. Commercial packaging. Each machine shall be packaged in accordance with commercial practice.

B. Commercial packing. Each machine shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

C. Export packaging. The legs of the machine shall be disassembled and placed in a weather-resistant fiberboard box constructed and closed in accordance with PPP-B-636. Technical literature shall be placed in a paper envelope or plastic bag and then taped to the machine. When applicable, other unattached components shall be packaged in a weather-resistant fiberboard box constructed and closed in accordance with PPP-B-636. The machine, legs and components shall be cleaned, preserved, cushioned and immobilized to afford protection against corrosion, deterioration and physical damage during shipment and storage.

D. Export packing. Each machine shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type style A or J, grade B, type 3 load of PPP-B-601, or nailed wood box conforming to class 1, style 2 or 4, grade B, type 3 load of PPP-B-621. Boxed legs and components shall be stowed in an unused portion within the shipping container or be shipped together with the parent machine as a set. The contents of each box shall be cushioned, blocked and braced to prevent movement while the box is in transit. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

E. Marking of interior boxes and shipping container (commercial and export). Commercial marking for interior boxes and shipping containers is acceptable provided the following information is included:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

National stock number
Item description
Quantity, unit of issue
Date of packaging (month/year)
Contract number
Name, address and zip code of contractor 1/

1/ Interior boxes do not require this information.

When a machine is shipped in two or more containers, set markings shall be applicable. The set markings shall be placed in the surfaces containing identification markings and located in the lower right hand corner. A 2-inch black disc shall be placed above these numbers on each container. For example:

SET 1	SET 2
PK 1 of 3	PK 1 of 3
PK 2 of 3	PK 2 of 3
PK 3 of 3	PK 3 of 3

Sources of information for nongovernmental documents.

Underwriters Laboratories, Inc.
333 Pfingston Road
Northbrook, IL 60062

National Electrical Manufacturers Association
155 East 44th Street
New York, NY 10017

National Sanitation Foundation
P.O. Box 1468
Ann Arbor, MI 48106

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 84

Review Activities

Army - MD, TS
Navy - SA, SH, MC

User Activity

Army - CE

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0735

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.