
FED. SUP CLASS
4730



(a) MARK EACH WRENCH PAD WITH AN EQUILATERAL TRIANGLE TO DENOTE PRECISION TYPE. MARKING SHALL BE DEPRESSED .025 ±.010.

MATERIAL: STEEL; ALUMINUM ALLOY; CORROSION RESISTANT STEEL (CRES); TITANIUM ALLOY (SEE PROCUREMENT SPECIFICATION).

FINISH: SEE PROCUREMENT SPECIFICATION.

IN ADDITION TO THE SAMPLING REQUIREMENTS OF THE PROCUREMENT SPECIFICATION, THE SURFACE OF THE CONE ENDS ON 100% OF THE CROSSES OF A LOT SHALL BE INSPECTED.

NO CODE LETTER IN PART NUMBER FOR STEEL.

ADD D IN PLACE OF DASH FOR ALUMINUM ALLOY (EXCEPT 7075-T73).

ADD J IN PLACE OF DASH FOR CRES, TYPE 304.

ADD K IN PLACE OF DASH FOR CRES, TYPE 316.

ADD S IN PLACE OF DASH FOR CRES, TYPE 347.

ADD T IN PLACE OF DASH FOR TITANIUM ALLOY.

ADD W IN PLACE OF DASH FOR 7075-T73 ALUMINUM ALLOY.

TITANIUM IS NOT RECOMMENDED FOR USE IN OXYGEN SYSTEMS.

EXAMPLE OF PART NUMBERS:

MS24403-8 - CROSS, .500 TUBING, STEEL.
MS24403D8 - CROSS, .500 TUBING, ALUMINUM ALLOY (EXCEPT 7075-T73).
MS24403J8 - CROSS, .500 TUBING, CRES, TYPE 304.
MS24403K8 - CROSS, .500 TUBING, CRES, TYPE 316.
MS24403S8 - CROSS, .500 TUBING, CRES, TYPE 347.
MS24403T8 - CROSS, .500 TUBING, TITANIUM ALLOY:
MS24403W8 - CROSS, .500 TUBING, 7075-T73 ALUMINUM ALLOY.

BREAK ALL SHARP EDGES AND REMOVE ALL HANGING BURRS AND SLIVERS.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ± .015

FOR DESIGN PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

(E) DENOTES CHANGES

APPROVED 6 MAR 58 REVISED (A) 10 FEB 67 (B) 16 JUN 78 (C) 22 MAR 79 (D) 16 APR 82 (E) 4 Apr 85

User activities:

Review activities: ARMY - ME, AV
DLA - CS

This Military Standard is approved for use by HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016, Department of the Air Force, and is available for use by all Departments and agencies of the Department of Defense.

P.A. AIR FORCE - 82 (E) Other Cust AIR FORCE - 99 NAVY - AS	TITLE CROSS, TUBE, PRECISION TYPE	MILITARY STANDARD MS 24403
PROCUREMENT SPECIFICATION MIL - F - 5509	SUPERSEDES: ~~AN 807~~	SHEET 1 OF 2

DD FORM 672-1 Limited Coordination

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

(Reverse 4730-F722)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:54Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
4730

DASH NO.	TUBING OD	THREAD T (REF)	Q +.047 - .000	U RAD	V	W APPROX
2	.125	.312 -24UNJF-3A	.734		.312	.312
3	.187	.375 -24UNJF-3A	.797		.375	.375
4	.250	.437 -20UNJF-3A	.859	.062	.437	
5	.312	.500 -20UNJF-3A	.922		.500	.469
6	.375	.562 -18UNJF-3A	1.031	.094	.562	.500
8	.500	.750 -16UNJF-3A	1.219		.750	.687
10	.625	.875 -14UNJF-3A	1.422		.875	.781
12	.750	1.062 -12UNJ -3A	1.625		1.062	.906
16	1.000	1.312 -12UNJ -3A	1.781	.125	1.312	1.094
20	1.250	1.625 -12UNJ -3A	2.031		1.625	1.312
24	1.500	1.875 -12UNJ -3A	2.297		1.875	1.500
28	1.750	2.250 -12UNJ -3A	2.781	.187	2.250	1.781
32	2.000	2.500 -12UNJ-3A	3.031	.250	2.562	2.031

(E)

APPROVED 6 MAR 90 REVISED (E) FOR CHANGE. SEE PAGES 1 - 2.

This Military Standard is approved for use by HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016, Department of the Air Force, and is available for use by all Departments and agencies of the Department of Defense.

Review activities: ARMY - ME, AV

User activities:

DLA - CS

P.A. AIR FORCE - 82 (E)
Other Cust
AIR FORCE - 99
NAVY - AS

PROCUREMENT SPECIFICATION
MIL - F - 5509

TITLE
CROSS, TUBE, PRECISION TYPE

SUPERSEDES:
~~AN827~~

MILITARY STANDARD
MS24403

SHEET 2 OF 2

DD FORM 1 SEP 87 672-1 Limited Coordination

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:54Z
Check the source to verify that this is the current version before use.