DISTRIBUTION STATEMENT A. Approved for public release ; distribution is unlimited.
NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

DO FORM 672-1
1 OCT 52

P.A.
AF - 82
OTHER CUST
AF - 99
NAVY - YD
DSA - GS

OTHER INT.
A -
N -
AF -

PROCUREMENT SPECIFICATION
NONE


SUPERSEDES:

# MILITARY STANDARD

AIR INLET, AXIAL, GENERATOR

# MS25159 (ASG)

SHEET 1 OF 1




6 HOLES $\frac{.202}{.192}$ DIA PLUS .006 MAX TAPER SPACED AS SHOWN. HOLES MUST BE WITHIN .005 NOMINAL ℄ LOCATION IN CIRCUMFERENTIAL DIRECTION. HOLE CIRCLE MUST BE CONCENTRIC WITH $\frac{5.140}{5.130}$ REF DIA WITHIN .010 MAX TOTAL INDICATOR READING.

MATERIAL: ALUMINUM, DIE-CAST, SPECIFICATION QQ-A-591,COMP 11 (NO. 380).

FINISH: ANODIZE, SPECIFICATION MIL-A-8625, TYPE II (B)

WEIGHT: 3/4 POUND.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: ANGLES ±1/2°, DECIMALS ±.016.

| MS PART NO. | FIIN |
|---|---|
| MS25159-1 | |
| | |

FED. SUP CLASS. 4730

APPROVED 12 Aug 55 REVISED (A) 20 Aug 57 (B) PROPOSED 1 Sep 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:04Z
Check the source to verify that this is the current version before use.