FED. SUP CLASS 4720

(B)

SIZE	EQUIVALENT TUBING OD	END FITTING NUMBER	MAX WT PER FITTING	HOSE ASSEMBLY NUMBER	MAX WT 3 FT ASSY	MAX WT 1 FT OF HOSE	END FITTINGS PART NUMBER	MAX WT. PER FITTING	MAX SYSTEM OPERATING PRESSURE (PSI) FUEL	OIL	HYDRAULIC OR PNEUMATIC	INSTRUMENT AIR
MIL-H-8795 HOSE ASSEMBLIES												
		MS24587		MS28741			MS24587					
(b) -3	3/16	-3	.04	-3	.44	.13	MS24587 -3					
(c) -4	1/4	-4	.06	-4	.57	.16	-4				3000	
(c) -5	5/16	-5	.07	-5	.71	.20	-5					
-6	3/8	-6	.09	-6	.89	.24	-6		1000		2000	
-8	1/2	-8	.09	-8	.99	.27	-8					
-10	5/8	-10	.14	-10	1.43	.38	-10			50	1750	
-12	3/4	-12	.20	-12	1.79	.46	-12				1500	
-16	1	-16	.23	-16	1.80		-16		750		800	
-20	1-1/4	-20	.43	-20	2.45	.56	-20		500		600	
-24	1-1/2	-24	.52	-24	3.10	.69	-24		250		500	
-32	2	-32	.88	-32	4.43	.97	MS24587 -32				350	
MIL-H-8790 HOSE ASSEMBLIES												
-4	1/4		.10	MS28759-E	1.03	.29	MS28760-4				3000	
				MS28762-4			MS28761-4					
		MS28780-4		MS28920-E			MS28760-4 AND MS28780-4	.11				
		MS28781-4		MS28921-E	1.04		MS28760-4 AND MS28781-4	.12				
			.11	MS28922-E			MS28780-4					
		MS28781-4		MS28923-E	1.06		MS28780-4 AND MS28781-4	.12				
				MS28924-E			MS28781-4					
-5	5/16		.12	MS28759-F	1.08	.30	MS28760-5					
			.11	MS28762-5	1.05		MS28761-5					
		MS28780-5	.12	MS28920-F	1.11		MS28760-5 AND MS28780-5	.14				
		MS28781-5		MS28921-F			MS28760-5 AND MS28781-5	.15				
			.14	MS28922-F	1.12		MS28780-5					
		MS28781-5		MS28923-F	1.14		MS28780-5 AND MS28781-5	.15				
			.15	MS28924-F	1.15		MS28781-5					
-6	3/8		.16	MS28759-G	1.36	.39	MS28760-6					
				MS28762-6	1.34		MS28761-6					
		MS28780-6		MS28920-G	1.41		MS28760-6 AND MS28780-6	.17				
		MS28781-6		MS28921-G			MS28760-6 AND MS28781-6	.18				
			.18	MS28922-G			MS28780-6					
		MS28781-6		MS28923-G			MS28780-6 AND MS28781-6	.18				
				MS28924-G	1.42		MS28781-6					
-8	1/2		.24	MS28759-H	2.09	.57	MS28760-8					
			.25	MS28762-8	2.08		MS28761-8					
		MS28780-8	.24	MS28920-H			MS28760-8 AND MS28780-8	.25				
		MS28781-8		MS28921-H	2.09		MS28760-8 AND MS28781-8					
				MS28922-H	2.07		MS28780-8					
		MS28781-8	.25	MS28923-H	2.12		MS28780-8 AND MS28781-8	.25				
				MS28924-H	2.09		MS28781-8					
-10	5/8		.34	MS28759-J	2.53	.66	MS28760-10					
			.38	MS28762-10	2.52		MS28761-10					
		MS28780-10		MS28920-J	2.51		MS28760-10 AND MS28780-10	.35				
		MS28781-10	.36	MS28921-J	2.54		MS28760-10 AND MS28781-10	.40				
				MS28922-J	2.49		MS28780-10					
		MS28781-10	.35	MS28923-J	2.53		MS28780-10 AND MS28781-10	.40				
			.40	MS28924-J	2.56		MS28781-10					

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE in EFFECT ON DATE OF INVITATIONS FOR BID.

THIS IS A DESIGN STANDARD . NOT TO BE USED AS A PART NUMBER.

(B) FOR CHANGES SEE SHEET 2

APPROVED 11 Nov 59 REVISED (4) 17 July 62 (B) 4 Mar 64

USED: NINE

REVIEWER: navy - Weps USAF - 11

P.A. USAF - (11)
Other Cust
Navy - Weps

TITLE
CHART, HOSE SELECTION

MILITARY STANDARD
MS33620 (ASG)

PROCUREMENT SPECIFICATION
None

SUPERSEDES: AND10340

SHEET 1 OF 2

DD FORM 672-1 (Limited coordination)

This standard has been approved by the Weps (Department of the Navy) and the Department of the USAF and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23117:062
Check the source to verify that this is the current version before use.

FED. SUP CLASS 4720

(B)

SIZE	EQUIVALENT TUBING OD	END FITTING NUMBER	MAX WT PER FITTING	HOSE ASSEMBLY NUMBER	MAX WT 3 FT ASSY	MAX WT 1 FT OF HOSE	END FITTINGS PART NUMBER	MAX WT PER FITTING	MAX SYSTEM OPERATING PRESSURE (PSI) FUEL	OIL	HYDRAULIC OR PNEUMATIC	INSTRUMENT AIR
MIL-H-8790 HOSE ASSEMBLIES												
-12	3/4		.55	MS28759-K	3.36	.85	MS28760-12				3000	
			.58	MS28762-12	3.34		MS28761-12					
		MS28780-12	.55	MS28920-K			MS28760-12 AND MS28780-12	.58				
		MS28781-12		MS28921-K	3.37		MS28760-12 AND MS28781-12	.63				
			.58	MS28922-K	3.34		MS28780-12					
		MS28781-12		MS28923-K	3.35		MS28780-12 AND MS28781-12	.63				
			.63	MS28924-K	3.38		MS28781-12					
-16	1		.85	MS28759-M	5.09	1.34	MS28760-16				3000	
			.94	MS28762-16	5.44		MS28761-16					
		MS28780-16	.85	MS28920-M	5.27		MS28760-16 AND MS28780-16	.87				
		MS28781-16		MS28921-M	5.28		MS28760-16 AND MS28781-16	.91				
			.87	MS28922-M	5.20		MS28780-16					
		MS28781-16		MS28923-M	5.21		MS28780-16 AND MS28781-16	.91				
			.91	MS28924-M	5.22		MS28781-16					
(a) MIL-H-5593 HOSE ASSEMBLIES												
-2	1/8		.01	AN6270-2	.20	.06	AN773-2					300
-3	3/16			AN6270-3	.21	.07	AN773-3					250
-4	1/4		.02	AN6270-4	.26	.08	AN773-4				20	200
-6	3/8		.03	AN6270-6	.37	.10	AN773-6					150
-8	1/2		.06	AN6270-8	.64	.18	AN773-8					125
-10	5/8		.07	AN6270-10	.75	.21	AN773-10					
MIL-H-25579-3 HOSE ASSEMBLIES												
				MIL-H-25579 DASH NO.			MIL-H-25579 DASH NO.					
(b)-3			.05	-3	.24	.06	-3		1500	1500	1500	
-4			.08	-4	.40	.09	-4					
-5			.09	-5	.45	.11	-5					
-6			.11	-6	.56	.13	-6					
-8			.20	-8	.81	.16	-8					
-10			.29	-10	1.14	.21	-10					
-12			.42	-12	1.69	.26	-12		1000	1000	1000	
-16			.66	-16	2.80	.63	-16		1250	1250	1250	
-20			1.10	-20	3.83	.73	-20		1000	1000	1000	

SPECIFICATION NUMBER			ANA BULLETIN OR QPL NUMBER		
HOSE ASSEMBLIES	HOSE	FITTING	HOSE ASSEMBLIES	HOSE	FITTING
MIL-H-8790	MIL-H-8788	MIL-F-8789	-	QPL-8788	QPL-8789
MIL-H-8795	MIL-H-8794	MIL-A-5070	-	QPL-8794	QPL-5070
AN6270	MIL-H-5593	AN773	-	QPL-5593	ANA268
MIL-H-25579	-	-	QPL-25579	-	-

(a) AN6270 HOSE ASSEMBLIES MAY BE USED IN HYDRAULIC AND PNEUMATIC SYSTEMS ONLY FOR DRAIN LINES OR WHERE PRESSURE DOES NOT PULSATE OR EXCEED 20 PSI (NO SUCTION).
(b) NOT TO BE USED IN HYDRAULIC SYSTEMS.
(c) THIS HOSE MAY BE USED WHERE DYNAMIC IMPULSE DOES NOT EXCEED 3750 PSI, IF DYNAMIC IMPULSES OF 4500 PSI ARE REQUIRED MIL-H-8790 HOSE ASSEMBLIES SHALL BE USED.

(B)

APPROVED 10 Nov 59 REVISED (B) FOR CHANGES SEE SHEET 1

REVIEWED: Navy - Weps USAF - 11

This standard has been approved by the Weps (Department of the Navy) and the USAF and is mandatory for use by Department of the USAF. All other military activities are required to employ this standard where suitable.

THIS IS A DESIGN STANDARD, NOT TO BE USED AS A PART NUMBER

P.A. USAF - (11)	TITLE	MILITARY STANDARD
Other Cust Navy - Weps	CHART, HOSE SELECTION	MS33620(ASG)
PROCUREMENT SPECIFICATION None	SUPERSEDES AND 10340	SHEET 2 OF

Downloaded from https://assist.dla.mil -- Downloaded: 2026-10-23T17:06Z
Check the date above to verify that this is the current version before use.

DD FORM 672-1 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.