[INCH-POUND]
A-A-59590/17
26 June 2002

COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

# HOLDERS, ELECTRICAL CARD, WEDGE RETAINERS, 3 PIECE, SCREW ACTUATED DRIVE, .260 X .260 INCH BODY SIZE

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

The complete requirements for procuring electrical card holders described herein shall consist of this document and the latest issue in effect of A-A-59590.

SCOPE. This CID specification sheet covers 3 piece card holders that use screw actuated wedges to hold circuit card assemblies into their installed positions in heat sinking devices (cold plates, heat exchanger) or other applications. Card holders covered by this CID are intended to provide 60g/6ms resistance to shock, withstand 25 G-rms of vibration and provide 2 to 4 degrees C/W/inch thermal resistance between the circuit card assemblies and the heat sink surfaces. Items covered by this CID specification sheet are intended for commercial/industrial applications.

CLASSIFICATION. This CID specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes).

| AA59590/ | 17 | C, B ,H | N, J, T, V | * * | W, D, E |
|---|---|---|---|---|---|
| CID number | Applicable CID sheet | Finish | Mounting | Length | Options |

SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card firmly in place providing high resistance to shock and vibration while providing maximum thermal transfer.

Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein and the general CID.


Expanded and relaxed dimensions. Expanded and relaxed dimensions shall be as specified in figure 1.

Mounting options. The mounting options shall be as specified in A-A-59590.

Mounting holes (when required). Two mounting holes are required on card holders less than 6.00 inches (152.4 mm) in length. See table I and figure 1 for mounting hole spacing requirements.

AMSC N/A FSC 5998
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.




| Inches | mm | Inches | mm | Inches | mm | Inches | mm |
|---|---|---|---|---|---|---|---|
| .07 | 1.8 | .20 | 5.1 | .260 | 6.6 | .325 | 8.26 |
| .13 | 3.3 | .25 | 6.4 | .270 | 6.86 | .70 | 17.8 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ± .02 (0.5 mm), for 2 places and ± .010 (0.25 mm), for 3 places.

FIGURE 1. Relaxed and expanded dimensions.

TABLE I. Assembly dimensions.

| PIN length designator | Dimension "LENGTH" ± .02 (± 0.5) | Dimension "B" ± .03 (± 0.8) | Dimension "M" ± .005 (± 0.13) |
|---|---|---|---|
| 28 | 2.8 (71) | 2.30 (58.4) | .90 (22.9) |
| 38 | 3.8 (96) | 3.30 (83.8) | 1.90 (48.3) |
| 48 | 4.8 (122) | 4.30 (109.2) | 2.90 (73.7) |
| 58 | 5.8 (147) | 5.30 (134.6) | 3.90 (99.1) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Options. Card holders can have the following options. Card holders not requiring one of the following options shall leave the options position in the PIN blank.

Lockwasher and flat washer (see figure 2). A lockwasher and flat washer located under the screw head will provide for additional resistance to loosening from shock and vibration. Card holders requiring a lockwasher and flat washer option shall include a suffix “W” in the PIN (see classification and notes).





FIGURE 2. Lockwasher and flat washer details.

Screw self-locking element (see figure 3). The use of a screw self-locking element will provide prevailing torque for resistance to loosening from shock vibration. Card holders requiring a screw self-locking element shall include a suffix “E” in the PIN (see classification and notes).




FIGURE 3. Screw self-locking element details.

Lockwasher, flat washer, and screw self-locking element. Card holders requiring a lockwasher, flat washer, and screw self-locking element option shall include a suffix “D” in the PIN (see classification and notes).

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

| Manufacturer CAGE | Manufacturer name and address | Manufacturer contact information |
|---|---|---|
| 52094 | Calmark Corporation<br>4915 Walnut Grove Avenue<br>San Gabriel, CA 91776–2099 | Tel: (626) 287–0451<br>Fax: (626) 287–7350<br>E-mail: sales@calmark.com<br>URL: www.calmark.com |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Part number supersession data. This CID specification sheet part numbers supersedes the following manufacturer's part numbers as shown. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE II. Commercial P/N supersession data. 1/

| PIN designator AA59590/17 | Vendor similar designator or type part number 2/ CAGE 52094 | PIN designator AA59590/17 | Vendor similar designator or type part number 2/ CAGE 52094 |
|---|---|---|---|
| CJ28 | 245-2.80H | CJ28W | W245-2.80H |
| CN28 | 245-2.80 | CN28W | W245-2.80 |
| CT28 | 245-2.80T0 | CT28W | W245-2.80T0 |
| CV28 | 245-2.80T2 | CV28W | W245-2.80T2 |
| CJ28E | 245-2.80HL | CJ28D | W245-2.80HL |
| CN28E | 245-2.80L | CN28D | W245-2.80L |
| CT28E | 245-2.80T0L | CT28D | W245-2.80T0L |
| CV28E | 245-2.80T2L | CV28D | W245-2.80T2L |
| BJ28 | A245-2.80H | BJ28W | WA245-2.80H |
| BN28 | A245-2.80 | BN28W | WA245-2.80 |
| BT28 | A245-2.80T0 | BT28W | WA245-2.80T0 |
| BV28 | A245-2.80T2 | BV28W | WA245-2.80T2 |
| BJ28E | A245-2.80HL | BJ28D | WA245-2.80HL |
| BN28E | A245-2.80L | BN28D | WA245-2.80L |
| BT28E | A245-2.80T0L | BT28D | WA245-2.80T0L |
| BV28E | A245-2.80T2L | BV28D | WA245-2.80T2L |
| HJ28 | HA245-2.80H | HJ28W | WHA245-2.80H |
| HN28 | HA245-2.80 | HN28W | WHA245-2.80 |
| HT28 | HA245-2.80T0 | HT28W | WHA245-2.80T0 |
| HV28 | HA245-2.80T2 | HV28W | WHA245-2.80T2 |
| HJ28E | HA245-2.80HL | HJ28D | WHA245-2.80HL |
| HN28E | HA245-2.80L | HN28D | WHA245-2.80L |
| HT28E | HA245-2.80T0L | HT28D | WHA245-2.80T0L |
| HV28E | HA245-2.80T2L | HV28D | WHA245-2.80T2L |

1/ CID PINs listed only with length designator "28".
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph of the basic CID.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Example of PIN with available length designators.

| PIN designator<br>AA59590/17 | Vendor similar designator or type part number 1/<br>CAGE 52094 |
|---|---|
| CN28 | 245-2.80 |
| CN38 | 245-3.80 |
| CN48 | 245-4.80 |
| CN58 | 245-5.80 |

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph of the basic CID.

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – 7FXE

Preparing Activity:

DLA – CC

Project 5998–0117



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.