INCH-POUND

A–A–59590/19A
7 July 2007
SUPERSEDING
A–A–59590/19
16 August 2002


COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

HOLDER, ELECTRICAL CARD, WEDGE RETAINERS, 3 PIECE, SCREW ACTUATED DRIVE, .260 X .260 INCH BODY SIZE, WITH SCREW RETENTION

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring electrical card holders described herein shall consist of this document and the latest issue in effect of A–A–59590.

CLASSIFICATION/PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes).



Example: AA59590/19EV28D is the PIN for a nickel plated, 2.8 inches (71 mm) long card holder with a flat washer, lockwasher, and screw self-locking element. The card holder also features two tapped mounting holes for use with 2-56 UNC 2A fasteners.

SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card assembly firmly in its installed position and provide high resistance to loosening due to shock and vibration. Card holders shall also provide maximum thermal transfer from the circuit card assembly to the cold plate or heat sink surfaces. The screw retention feature is intended to prevent unintentional disassembly of the card holder.


Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein (see figures 1, 2, 3, 4, and table I) and meet the general requirements of CID A–A–59590.

Material. Unless otherwise specified herein, the card holder materials shall be as specified in A–A–59590.

Cold plate dimensions. Recommend cold plate slot width to accommodate the circuit card assembly with attached card holder is .300 inch (7.62 mm) plus the thickness of the printed board of the circuit card assembly (see A–A–59590).

Nominal installation torque. When card holders are used in cold plate applications, the nominal installation torque of each card holder shall be as follows: 10 inch-pounds (1.1 N-m) for assemblies using no options or option “W” and 12 inch-pounds (1.4 N-m) for assemblies using options “D” or “E”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.07	1.8	.20	5.1	.25	6.4	.270	6.86	.70	17.8
.13	3.3	.23	5.8	.260	6.6	.325	8.26		

NOTES:

1. Dimensions are in inches. Millimeters are given for information only.
2. Unless otherwise specified, tolerances are for ±.02 inch (0.51 mm) for two place decimals and ±.010 inch (0.25 mm) for three place decimals.
3. The tolerance for the mounting hole spacing is ±.005 inches (0.13 mm).
4. The across flats dimension for hex drive socket shall be .109 inch (2.78 mm) for mounting options “J”, “N”, “T”, and “V”. The across flats dimension for hex drive socket shall be a metric dimension of 2.5 mm (.098 inch) across flats for mounting option “G”.

FIGURE 1. Relaxed and expanded dimensions, basic configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Screw retention locknut (see figure 2). Card holders shall have a screw retention locknut intended to prevent unintentional disassembly of the card holder. The locknut shall be fabricated of a corrosion resistant material.




FIGURE 2. Screw retaining self-locking nut details.

Finish. The finish designator shall be as specified in A–A–59590. The finishes available for this CID specification sheet are as follows: “B” (black anodize), “C” (chemical film), “E” (electroless nickel), or “H” (hard black anodize).

Mounting. The mounting designators shall be as specified in A–A–59590. Except when using mounting option “N”, two mounting holes are required on the card holders. The mounting options available for this CID specification sheet are as follows: “J” (rivet mounting holes), “N” (no mounting holes), “T” (tapped 0-80 UNF 2B holes), “V” (tapped 2-56 UNC 2B holes), or “G” (tapped M2.5 x.45 metric holes). See figure 1 and table I for mounting hole spacing requirements. Card holders using mounting option “J” may be shipped unassembled.

Counterbore holes (for rivet mounting). The holes used for rivet mounting shall be .068/.073 inch (1.73/1.85 mm) diameter, countersunk 100 degrees by .140 inch (3.56 mm) diameter through holes with an access/clearance counterbore of .156 inch (3.96 mm) diameter by .200 inch (5.08 mm) deep.

Length, expanded, and relaxed dimensions. The length designator shall be as specified in A–A–59590 and the lengths available for this CID specification sheet are listed in table I. The length, expanded, and relaxed dimensions shall be as specified on figure 1.

TABLE I. Assembly dimensions (see figure 1).

PIN length designator	Dimension “LENGTH” ±.02 (0.5 mm)	Dimension “B” ±.03 (0.8 mm)	Dimension “M” ±.005 (0.13 mm)
28	2.8 (71 mm)	2.30 (58.4 mm)	.90 (22.9 mm)
33	3.3 (84 mm)	2.80 (71.1 mm)	1.40 (35.6 mm)
38	3.8 (97 mm)	3.30 (83.8 mm)	1.90 (48.3 mm)
43	4.3 (109 mm)	3.80 (96.5 mm)	2.40 (61.0 mm)
48	4.8 (122 mm)	4.30 (109.2 mm)	2.90 (73.7 mm)
53	5.3 (135 mm)	4.80 (121.9 mm)	3.40 (86.4 mm)
58	5.8 (147 mm)	5.30 (134.6 mm)	3.90 (99.1 mm)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Options. Card holders can have the options described in table II. The correct PIN configuration identifier for each option is listed in table II. Card holders not requiring these options shall leave the options position in the PIN blank.

TABLE II. Options.

Configuration	Applicable figures	Hardware added to basic configuration
	1 and 2	No changes from basic configuration
W	1, 2, and 3	Lockwasher and flat washer
E	1, 2, and 4	Screw self-locking element
D	1, 2, 3, and 4	Lockwasher, flat washer, and screw self-locking element

Lockwasher and flat washer (see figure 3). A lockwasher and flat washer located under the screw head will provide for additional resistance to loosening from shock and vibration. Card holders requiring a lockwasher and flat washer option shall include a suffix “W” in the PIN (see classification and notes).




FIGURE 3. Lockwasher and flat washer details.

Screw self-locking element (see figure 4). The use of a screw self-locking element will provide prevailing torque for resistance to loosening from shock and vibration. Card holders requiring a screw self-locking element shall include a suffix “E” in the PIN (see classification and notes).




FIGURE 4. Screw self-locking element details.

Lockwasher, flat washer, and screw self-locking element. Card holders requiring a lockwasher, flat washer, and screw self-locking element option shall include a suffix “D” in the PIN (see classification and notes).

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Source of documents.

Commercial Item Description.

A–A–59590 – Holder, Electrical Card, Wedge Retainers, 3 Piece, Screw Actuated Drive, General Requirements For.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111–5094.)

Other Publications.

AEROSPACE INDUSTRIES ASSOCIATION (AIA)

AIA/NAS 1283 – Fasteners, Male Threaded, Self–locking.

(Application for copies should be addressed to the Aerospace Industries Association, 1250 Eye Street, NW, Suite 1200, Washington, DC 20005–3924 or at URL: http://www.aia-aerospace.org.)

Ordering data. Ordering data is as specified in A–A–59590.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Manufacturer CAGE	Manufacturer name and address	Manufacturer contact information
52094	Calmark Corporation 4915 Walnut Grove Avenue San Gabriel, CA 91776–2099	Telephone: (626) 287–0451 Facsimile: (626) 287–7350 Electronic mail: sales@calmark.com URL: www.calmark.com

Part number supersession data. These CID specification sheet PINs supersedes the following manufacturer's part numbers as shown in table III. The CID PINs listed in table III are only for length designator "28". See table IV for CID PIN construction using other available lengths for this specification sheet. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE III. Commercial part number supersession data.

PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094	PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094
BJ28	A245CR2.80HR	BJ28W	WA245CR2.80HR
BN28	A245CR2.80R	BN28W	WA245CR2.80R
BT28	A245CR2.80T0R	BT28W	WA245CR2.80T0R
BV28	A245CR2.80T2R	BV28W	WA245CR2.80T2R
BG28	MA245CR2.80TM2.5R	BG28W	MWA245CR2.80TM2.5R

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data – Continued.

PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094	PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094
BJ28E	A245CR2.80HLR	BJ28D	WA245CR2.80HLR
BN28E	A245CR2.80LR	BN28D	WA245CR2.80LR
BT28E	A245CR2.80T0LR	BT28D	WA245CR2.80T0LR
BV28E	A245CR2.80T2LR	BV28D	WA245CR2.80T2LR
BG28E	MA245CR2.80TM2.5LR	BG28D	MWA245CR2.80TM2.5LR
TCJ28	245CR2.80HR	CJ28W	W245CR2.80HR
CN28	245CR2.80R	CN28W	W245CR2.80R
CT28	245CR2.80T0R	CT28W	W245CR2.80T0R
CV28	245CR2.80T2R	CV28W	W245CR2.80T2R
CG28	M245CR2.80TM2.5R	CG28W	MW245CR2.80TM2.5R
CJ28E	245CR2.80HLR	CJ28D	W245CR2.80HLR
CN28E	245CR2.80LR	CN28D	W245CR2.80LR
CT28E	245CR2.80T0LR	CT28D	W245CR2.80T0LR
CV28E	245CR2.80T2LR	CV28D	W245CR2.80T2LR
CG28E	M245CR2.80TM2.5LR	CG28D	MW245CR2.80TM2.5LR
EJ28	EN245CR2.80HR	EJ28W	WEN245CR2.80HR
EN28	EN245CR2.80R	EN28W	WEN245CR2.80R
ET28	EN245CR2.80T0R	ET28W	WEN245CR2.80T0R
EV28	EN245CR2.80T2R	EV28W	WEN245CR2.80T2R
EG28	MEN245CR2.80TM2.5LR	EG28W	MWEN245CR2.80TM2.5R
EJ28E	EN245CR2.80HLR	EJ28D	WEN245CR2.80HLR
EN28E	EN245CR2.80LR	EN28D	WEN245CR2.80LR
ET28E	EN245CR2.80T0LR	ET28D	WEN245CR2.80T0LR
EV28E	EN245CR2.80T2LR	EV28D	WEN245CR2.80T2LR
EG28E	MEN245CR2.80TM2.5LR	EG28D	MWEN245CR2.80TM2.5LR
HJ28	HA245CR2.80HR	HJ28W	WHA245CR2.80HR
HN28	HA245CR2.80R	HN28W	WHA245CR2.80R
HT28	HA245CR2.80T0R	HT28W	WHA245CR2.80T0R
HV28	HA245CR2.80T2R	HV28W	WHA245CR2.80T2R
HG28	MHA245CR2.80TM2.5LR	HG28W	MWHA245CR2.80TM2.5LR

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data – Continued.

PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094	PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094
HJ28E	HA245CR2.80HLR	HJ28D	WHA245CR2.80HLR
HN28E	HA245CR2.80LR	HN28D	WHA245CR2.80LR
HT28E	HA245CR2.80T0LR	HT28D	WHA245CR2.80T0LR
HV28E	HA245CR2.80T2LR	HV28D	WHA245CR2.80T2LR
HG28E	MHA245CR2.80TM2.5LR	HG28D	MWHA245CR2.80TM2.5LR

1/ The CID PINs listed are only for length designator “28”.
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59590.

TABLE IV. Example of PIN with available length designators.

PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094	PIN designator AA59590/19	Vendor similar designator or type part number 1/ 2/ CAGE 52094
EV28D	WEN245CR2.80T2LR	EV48D	WEN245CR4.80T2LR
EV33D	WEN245CR3.30T2LR	EV53D	WEN245CR5.30T2LR
EV38D	WEN245CR3.80T2LR	EV58D	WEN245CR5.80T2LR
EV43D	WEN245CR4.30T2LR		

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59590.
2/ Other lengths are available on request.

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

Review activity:
Air Force – 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – FSS

Preparing Activity:
DLA – CC

Project 5998–2007–019

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.