INCH-POUND

A–A–59590/22A
11 September 2007
SUPERSEDING
A–A–59590/22
23 August 2002


COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

HOLDER, ELECTRICAL CARD, WEDGE RETAINERS, 3 PIECE, SCREW ACTUATED DRIVE .500 X .450 INCH BODY SIZE, WITH VISUAL LOCK INDICATION

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring electrical card holders described herein shall consist of this document and the latest issue in effect of A–A–59590.

CLASSIFICATION/PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes).



Example: AA59590/22ET48E is the PIN for a nickel plated, 4.8 inches (122 mm) long card holder with a visual lock indication and a screw self-locking element. The card holder also features two tapped 0-80 UNF mounting holes for use with fasteners.

SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card assembly firmly in its installed position and provide high resistance to loosening due to shock and vibration. Card holders shall also provide maximum thermal transfer from the circuit card assembly to the cold plate or heat sink surfaces. Card holders shall have a visual indicator to show when the assembly is in its relaxed (unlocked) state.


Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein (see figures 1, 2, 3, 4, and table I) and meet the general requirements of CID A–A–59590.

Material. Unless otherwise specified herein, the card holder materials shall be as specified in A–A–59590.

Cold plate dimensions. Recommend cold plate slot width to accommodate the circuit card assembly with attached card holder is .525 inch (13.3 mm) plus the thickness of the printed board of the circuit card assembly (see A–A–59590).

Nominal installation torque. When card holders are used in cold plate applications, the nominal installation torque of each card holder shall be as follows: 31 inch-pounds (3.5 N-m) for assemblies using no options or option “W” and 34 to 36 inch-pounds (3.8 to 4.1 N-m) for assemblies using options “D” or “E”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.156	3.96	.25	6.4	.40	10.2	.500	12.7	.600	15.24
.20	5.1	.37	9.4	.460	11.68	.57	14.5	.70	17.8

NOTES:

1. Dimensions are in inches. Millimeters are given for information only.
2. Unless otherwise specified, tolerances are for ±.02 inch (0.51 mm) for two place decimals and ±.010 inch (0.25 mm) for three place decimals.
3. The tolerance for the mounting hole spacing is ±.005 inches (0.13 mm).
4. The across flats dimension for hex drive socket shall be .156 inch (3.96 mm) for mounting options “J”, “N”, “T”, and “V”. The across flats dimension for hex drive socket shall be a metric dimension of 2.5 mm (.098 inch) across flats for mounting option “G”.

FIGURE 1. Relaxed and expanded dimensions, basic configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Visual lock indicator (see figure 2). Card holders shall have a visual indicator to show when the card holder assembly is in its relaxed (unlocked) state. When the card holder assembly is in the relaxed state, the end of the actuating screw shall display a red band on the side of the screw. When the actuating screw on the card holder has been tightened so that the assembly is in the expanded (locked) position, this red band shall be concealed.




FIGURE 2. Visual lock indicator details.

Finish. The finish designator shall be as specified in A–A–59590. The finishes available for this CID specification sheet are as follows: “B” (black anodize), “C” (chemical film), “E” (electroless nickel), or “H” (hard black anodize).

Mounting. The mounting designators shall be as specified in A–A–59590. Except when using mounting option “N”, two mounting holes are required on the card holders. The mounting options available for this CID specification sheet are as follows: “J” (rivet mounting holes), “N” (no mounting holes), “T” (tapped 0-80 UNF 2B holes), “V” (tapped 2-56 UNC 2B holes), or “G” (tapped M2.5 x.45 metric holes). See figure 1 and table I for mounting hole spacing requirements. Card holders using mounting option “J” may be shipped unassembled.

Counterbore holes (for rivet mounting). The holes used for rivet mounting shall be .136 inch (3.45 mm) diameter, countersunk 100 degrees by .190/.200 inch (4.83/5.08 mm) diameter through holes with an access/clearance counterbore of .190/.200 inch (4.83/5.08 mm) diameter by .390 inch (9.91 mm) deep.

Length, expanded, and relaxed dimensions. The length designator shall be as specified in A–A–59590 and the lengths available for this CID specification sheet are listed in table I. The length, expanded, and relaxed dimensions shall be as specified on figure 1.

TABLE I. Assembly dimensions (see figure 1).

PIN length designator	Dimension “LENGTH” ±.02 (0.5 mm)	Dimension “B” ±.03 (0.8 mm)	Dimension “M” ±.005 (0.13 mm)
28	2.8 (71 mm)	2.30 (58.4 mm)	.90 (22.9 mm)
33	3.3 (84 mm)	2.80 (71.1 mm)	1.40 (35.6 mm)
38	3.8 (97 mm)	3.30 (83.8 mm)	1.90 (48.3 mm)
43	4.3 (109 mm)	3.80 (96.5 mm)	2.40 (61.0 mm)
48	4.8 (122 mm)	4.30 (109.2 mm)	2.90 (73.7 mm)
53	5.3 (135 mm)	4.80 (121.9 mm)	3.40 (86.4 mm)
58	5.8 (147 mm)	5.30 (134.6 mm)	3.90 (99.1 mm)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Options. Card holders can have the following options described in table II. See table II for the correct PIN configuration identifier. Card holders not requiring these options shall leave the options position in the PIN blank.

TABLE II. Options.

Configuration	Applicable figures	Hardware added to basic configuration
	1 and 2	No changes from basic configuration
W	1, 2, and 3	Lockwasher and flat washer
E	1, 2, and 4	Screw self-locking element
D	1, 2, 3, and 4	Lockwasher, flat washer, and screw self-locking element

Lockwasher and flat washer (see figure 3). A lockwasher and flat washer located under the screw head will provide for additional resistance to loosening from shock and vibration. Card holders requiring a lockwasher and flat washer option shall include a suffix “W” in the PIN (see classification and notes).




FIGURE 3. Lockwasher and flat washer details.

Screw self-locking element (see figure 4). The use of a screw self-locking element will provide prevailing torque for resistance to loosening from shock and vibration. Card holders requiring a screw self-locking element shall include a suffix “E” in the PIN (see classification and notes).




FIGURE 4. Screw self-locking element details.

Lockwasher, flat washer, and screw self-locking element. Card holders requiring a lockwasher, flat washer, and screw self-locking element option shall include a suffix “D” in the PIN (see classification and notes).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Source of documents.

Commercial Item Description.

A–A–59590 – Holder, Electrical Card, Wedge Retainers, 3 Piece, Screw Actuated Drive, General Requirements For.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111–5094.)

Other Publications.

AEROSPACE INDUSTRIES ASSOCIATION (AIA)

AIA/NAS 1283 – Fasteners, Male Threaded, Self–locking.

(Application for copies should be addressed to the Aerospace Industries Association, 1250 Eye Street, NW, Suite 1200, Washington, DC 20005–3924 or at URL: http://www.aia-aerospace.org.)

Ordering data. Ordering data is as specified in A–A–59590.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Manufacturer CAGE	Manufacturer name and address	Manufacturer contact information
52094	Calmark Corporation 4915 Walnut Grove Avenue San Gabriel, CA 91776–2099	Telephone: (626) 287–0451 Facsimile: (626) 287–7350 Electronic mail: sales@calmark.com URL: www.calmark.com

Part number supersession data. These CID specification sheet PINs supersedes the following manufacturer's part numbers as shown in table III. The CID PINs listed in table III are only for length designator "28". See table IV for CID PIN construction using other available lengths for this specification sheet. This information is being provided to assist in reducing proliferation in the Government inventory system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data.

PIN designator AA59590/22	Vendor similar designator or type part number 1/ 2/ CAGE 52094	PIN designator AA59590/22	Vendor similar designator or type part number 1/ 2/ CAGE 52094
BJ28	VA255–2.80H	BJ28W	WVA255–2.80H
BN28	VA255–2.80	BN28W	WVA255–2.80
BT28	VA255–2.80T0	BT28W	WVA255–2.80T0
BV28	VA255–2.80T2	BV28W	WVA255–2.80T2
BG28	MVA255–2.80TM2.5	BG28W	MWVA255–2.80TM2.5
BJ28E	VA255–2.80HL	BJ28D	WVA255–2.80HL
BN28E	VA255–2.80L	BN28D	WVA255–2.80L
BT28E	VA255–2.80T0L	BT28D	WVA255–2.80T0L
BV28E	VA255–2.80T2L	BV28D	WVA255–2.80T2L
BG28E	MVA255–2.80TM2.5L	BG28D	MWVA255–2.80TM2.5L
CJ28	V255–2.80H	CJ28W	WV255–2.80H
CN28	V255–2.80	CN28W	WV255–2.80
CT28	V255–2.80T0	CT28W	WV255–2.80T0
CV28	V255–2.80T2	CV28W	WV255–2.80T2
CG28	MV255–2.80TM2.5	CG28W	MWV255–2.80TM2.5
CJ28E	V255–2.80HL	CJ28D	WV255–2.80HL
CN28E	V255–2.80L	CN28D	WV255–2.80L
CT28E	V255–2.80T0L	CT28D	WV255–2.80T0L
CV28E	V255–2.80T2L	CV28D	WV255–2.80T2L
CG28E	MV255–2.80TM2.5L	CG28D	MWV255–2.80TM2.5L
EJ28	VEN255–2.80H	EJ28W	WVEN255–2.80H
EN28	VEN255–2.80	EN28W	WVEN255–2.80
ET28	VEN255–2.80T0	ET28W	WVEN255–2.80T0
EV28	VEN255–2.80T2	EV28W	WVEN255–2.80T2
EG28	MVEN255–2.80TM2.5	EG28W	MWVEN255–2.80TM2.5
EJ28E	VEN255–2.80HL	EJ28D	WVEN255–2.80HL
EN28E	VEN255–2.80L	EN28D	WVEN255–2.80L
ET28E	VEN255–2.80T0L	ET28D	WVEN255–2.80T0L
EV28E	VEN255–2.80T2L	EV28D	WVEN255–2.80T2L
EG28E	MVEN255–2.80TM2.5L	EG28D	MWVEN255–2.80TM2.5L

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data – Continued.

PIN designator AA59590/22	Vendor similar designator or type part number 1/ 2/ CAGE 52094	PIN designator AA59590/22	Vendor similar designator or type part number 1/ 2/ CAGE 52094
HJ28	VHA255–2.80H	HJ28W	WVHA255–2.80H
HN28	VHA255–2.80	HN28W	WVHA255–2.80
HT28	VHA255–2.80T0	HT28W	WVHA255–2.80T0
HV28	VHA255–2.80T2	HV28W	WVHA255–2.80T2
HG28	MVHA255–2.80TM2.5	HG28W	MWVHA255–2.80TM2.5
HJ28E	VHA255–2.80HL	HJ28D	WVHA255–2.80HL
HN28E	VHA255–2.80L	HN28D	WVHA255–2.80L
HT28E	VHA255–2.80T0L	HT28D	WVHA255–2.80T0L
HV28E	VHA255–2.80T2L	HV28D	WVHA255–2.80T2L
HG28E	MVHA255–2.80TM2.5L	HG28D	MWVHA255–2.80TM2.5L

1/ The CID PINs listed are only for length designator “28”.
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59590.

TABLE IV. Example of PIN with available length designators.

PIN designator AA59590/22	Vendor similar designator or type part number 1/ 2/ CAGE 52094
ET28E	VEN255–2.80T0L
ET38E	VEN255–3.80T0L
ET48E	VEN255–4.80T0L
ET58E	VEN255–5.80T0L

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59590.
2/ Other lengths are available on request.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

Review activity:
Air Force – 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – FSS

Preparing Activity:
DLA – CC

Project 5998–2007–022

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.