[INCH–POUND]

A–A–59590/23C
23 March 2018
SUPERSEDING
A–A–59590/23B
23 March 2013


COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

# HOLDER, ELECTRICAL CARD, WEDGE RETAINERS, 3 PIECE, SCREW ACTUATED DRIVE, .500 X .450 INCH BODY SIZE, WEDGE MOUNTING BODY, WITH SCREW RETENTION,

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

The complete requirements for procuring electrical card holders described herein shall consist of this document and the latest issue in effect of A–A–59590.

CLASSIFICATION/PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes).




Example: AA59590/23EV58D is the PIN for a nickel plated, 5.8 inches (147 mm) long card holder with a flat washer, lockwasher, and screw self-locking element. The card holder also features two tapped mounting holes for use with 2-56 UNC 2A fasteners.

SALIENT CHARACTERISTICS.

Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein (see figures 1, 2, 3, 4, and table I) and meet the general requirements of CID A–A–59590.

Material. Unless otherwise specified herein, the card holder materials shall be as specified in A–A–59590.

Performance. Card holders shall hold the circuit card assembly it is attached to firmly in its installed position and prevent loosening or movement as a result of shock and vibration. The card holder shall also provide a thermal transfer path from the circuit card assembly to the cold plate or heat sink surfaces.


Screw retention (see figure 2). The screw retention feature is intended to prevent the unintentional disassembly of the card holder. The self-locking nut used for the screw retention feature shall be fabricated of a corrosion resistant material.

Actuating screw hex drive socket. The dimension for hex drive socket shall be as specified on figure 1.

Cold plate dimensions. The recommend cold plate slot width to accommodate the circuit card assembly with attached card holder is .525 inch (13.3 mm) plus the thickness of the printed board of the circuit card assembly (see A–A–59590).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.




| Inches | mm | Inches | mm | Inches | mm | Inches | mm | Inches | mm |
|---|---|---|---|---|---|---|---|---|---|
| .156 | 3.96 | .20 | 5.1 | .30 | 7.62 | .460 | 11.68 | .600 | 15.24 |
| .19 | 4.8 | .25 | 6.4 | .31 | 7.9 | .500 | 12.70 | .70 | 17.8 |

NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
2. Unless otherwise specified, tolerances are ±.02 inch (0.51 mm) for two place decimals and ±.010 inch (0.25 mm) for three place decimals.
3. The tolerance for the mounting hole spacing is ±.005 inches (0.13 mm).
4. The across flats dimension for hex drive socket shall be .156 inch (3.96 mm) for mounting options "J", "N", "T", and "V". The across flats dimension for hex drive socket shall be a metric dimension of 3.0 mm (.118 inch) across flats for mounting option "G".

FIGURE 1. Relaxed and expanded dimensions, basic configuration.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Nominal installation torque. When card holders are used in cold plate applications, the nominal installation torque of each card holder shall be as follows: 31 inch-pounds (3.5 N-m) for assemblies using no options or option "W" and from 34 to 36 inch-pounds (3.8 to 4.1 N-m) for assemblies using options "D" or "E".

Screw retention (locknut). The screw retention feature is intended to prevent unintentional disassembly of the card holder shall be as specified in figure 2. The locknut shall be fabricated of a corrosion resistant material.





FIGURE 2. Screw retaining self-locking nut details.

Finish. The finish materials shall be as specified in A–A–59590. The wedge body finishes available for this CID specification sheet are as follows: "B" (black anodize), "C" (gold chemical film), "E" (electroless nickel), "H" (hard black anodize), or "R" (clear chemical film).

Mounting. The mounting designators shall be as specified in A–A–59590. Except when using mounting option "N", two mounting holes are required on the card holders. The mounting options available for this CID specification sheet are as follows: "J" (rivet mounting holes), "N" (no mounting holes), "T" (tapped 0-80 UNF 2B holes), "V" (tapped 2-56 UNC 2B holes), or "G" (tapped M2.5 x.45 metric holes). See figure 1 and table I for mounting hole spacing requirements. Card holders using mounting option "J" may be shipped unassembled.

Rivet mounting holes. The holes used for rivet mounting shall be .136 inch (3.45 mm) diameter, countersunk 100 degrees by .190/.200 inch (4.83/5.08 mm) diameter through holes with an access/clearance counterbore of .190/.200 inch (4.83/5.08 mm) diameter by .390 inch (9.91 mm) deep.

Rivets. This card holder uses rivet style B as specified in A–A–59590 when rivet mounting is used.

Length, expanded, and relaxed dimensions. The length designator shall be as specified in A–A–59590 and the lengths available for this CID specification sheet are listed in table I. The length, expanded, and relaxed dimensions shall be as specified on figure 1.

TABLE I. Assembly dimensions (see figure 1).

| PIN length designator | Dimension "LENGTH" ±.02 (0.5 mm) | Dimension "B" ±.03 (0.8 mm) | Dimension "M" ±.005 (0.13 mm) |
|---|---|---|---|
| 28 | 2.8 (71 mm) | 2.30 (58.4 mm) | .90 (22.9 mm) |
| 38 | 3.8 (97 mm) | 3.30 (83.8 mm) | 1.90 (48.3 mm) |
| 48 | 4.8 (122 mm) | 4.30 (109.2 mm) | 2.90 (73.7 mm) |
| 58 | 5.8 (147 mm) | 5.30 (134.6 mm) | 3.90 (99.1 mm) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Configuration. The configuration of a card holder shall be as specified in table II. The details of a particular configuration consist of those on figures 1 and 2, and may include those on figures 3 and 4. The correct PIN configuration identifier for each option is listed in table II. Card holders not requiring the options described by table II shall leave the configuration position in the PIN blank.

TABLE II. Configuration.

| Configuration designator | Applicable figures | Hardware added to basic configuration |
|---|---|---|
| | 1 and 2 | No changes from basic configuration |
| W | 1, 2 and 3 | Lockwasher and flat washer |
| E | 1, 2 and 4 | Screw self-locking element |
| D | 1, 2, 3 and 4 | Lockwasher, flat washer, and screw self-locking element |

No added hardware. The base configuration of the card holder is as depicted by figure 1. Card holders requiring no added hardware options do not include a configuration identifier in the PIN (see classification, table II and notes herein).

Lockwasher and flat washer (see figure 3). The use of a lockwasher and flat washer located under the screw head will provide for additional resistance to loosening of the card holder assembly from shock and vibration. Card holders requiring a lockwasher and flat washer option shall include a suffix "W" in the PIN (see classification, table II and notes herein).





FIGURE 3. Lockwasher and flat washer details.

Screw self-locking element (see figure 4). The use of a self-locking element on the screw will provide a prevailing-torque for increased resistance to loosening of the card holder assembly from shock and vibration. The screw self-locking element shall be as specified in A–A–59590. Card holders requiring a screw self-locking element shall include configuration identifier "E" in the PIN (see classification, table II and notes herein).





FIGURE 4. Screw self-locking element details.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Lockwasher, flat washer, and screw self-locking element. Card holders requiring a lockwasher, flat washer, and screw self-locking element option shall include a suffix "D" in the PIN (see classification, table II and notes herein).

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Source of documents.

Commercial Item Description.

A–A–59590 – Holder, Electrical Card, Wedge Retainers, 3 Piece, Screw Actuated Drive, General Requirements For.

(Copies of these documents are available online at http://quicksearch.dla.mil.)

Ordering data. Ordering data shall be as specified in A–A–59590.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

| Manufacturer CAGE | Manufacturer name and address | Manufacturer contact information |
|---|---|---|
| 5BG68 | American Circuit Card Retainers, Inc.<br>(formerly Card Locks Unlimited, Inc.)<br>2310 E. Orangethorpe Avenue<br>Anaheim, CA 92806–1231 | Telephone: (714) 738–6194<br>Facsimile: (714) 446–0119<br>E-mail: sales@accrmfg.com<br>URL: www.accrmfg.com |
| 61081 | Pentair Technical Products<br>(formerly Calmark Corporation)<br>7328 Trade Street<br>San Diego, CA 92121–3410 | Telephone: (858) 740–2400<br>Facsimile: (858) 740–2430<br>E-mail: schroff.us@pentair.com<br>URL: http://www.pentairprotect.com |

Part number supersession data. These CID specification sheet PINs supersedes the following manufacturer's part numbers as shown in table III. The CID PINs listed in table III are only for length designator "28". See table IV for CID PIN construction using other available lengths for this specification sheet. This information is being provided to assist in reducing proliferation in the Government inventory system.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data.

| PIN designator AA59590/23 | Vendor similar designator or type part number 1/ 2/ | |
|---|---|---|
| | CAGE 61081 | CAGE 5BG68 |
| BJ28 | A255CR2.80HR | 3500BA–2.80HR |
| BN28 | A255CR2.80R | 3500BA–2.80R |
| BT28 | A255CR2.80T0R | 3500BA–2.80T0R |
| BV28 | A255CR2.80T2R | 3500BA–2.80T2R |
| BG28 | MA255CR2.80TM2.5R | 3500MBA–2.80TM2.5R |
| BJ28W | WA255CR2.80HR | 3500WBA–2.80HR |
| BN28W | WA255CR2.80R | 3500WBA–2.80R |
| BT28W | WA255CR2.80T0R | 3500WBA–2.80T0R |
| BV28W | WA255CR2.80T2R | 3500WBA–2.80T2R |
| BG28W | MWA255CR2.80TM2.5R | 3500MWBA–2.80TM2.5R |
| BJ28E | A255CR2.80HLR | 3500BA–2.80HLR |
| BN28E | A255CR2.80LR | 3500BA–2.80LR |
| BT28E | A255CR2.80T0LR | 3500BA–2.80T0LR |
| BV28E | A255CR2.80T2LR | 3500BA–2.80T2LR |
| BG28E | MA255CR2.80TM2.5LR | 3500MBA–2.80TM2.5LR |
| BJ28D | WA255CR2.80HLR | 3500WBA–2.80HLR |
| BN28D | WA255CR2.80LR | 3500WBA–2.80LR |
| BT28D | WA255CR2.80T0LR | 3500WBA–2.80T0LR |
| BV28D | WA255CR2.80T2LR | 3500WBA–2.80T2LR |
| BG28D | MWA255CR2.80TM2.5LR | 3500MWBA–2.80TM2.5LR |
| CJ28 | 255CR2.80HR | 3500CG–2.80HR |
| CN28 | 255CR2.80R | 3500CG–2.80R |
| CT28 | 255CR2.80T0R | 3500CG–2.80T0R |
| CV28 | 255CR2.80T2R | 3500CG–2.80T2R |
| CG28 | M255CR2.80TM2.5R | 3500MCG–2.80TM2.5R |
| CJ28W | W255CR2.80HR | 3500WCG–2.80HR |
| CN28W | W255CR2.80R | 3500WCG–2.80R |
| CT28W | W255CR2.80T0R | 3500WCG–2.80T0R |
| CV28W | W255CR2.80T2R | 3500WCG–2.80T2R |
| CG28W | MW255CR2.80TM2.5R | 3500MWCG–2.80TM2.5R |

See footnotes at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data.

| PIN designator AA59590/23 | Vendor similar designator or type part number 1/ 2/ | |
|---|---|---|
| | CAGE 61081 | CAGE 5BG68 |
| CJ28E | 255CR2.80HLR | 3500CG–2.80HLR |
| CN28E | 255CR2.80LR | 3500CG–2.80LR |
| CT28E | 255CR2.80T0LR | 3500CG–2.80T0LR |
| CV28E | 255CR2.80T2LR | 3500CG–2.80T2LR |
| CG28E | M255CR2.80TM2.5LR | 3500MCG–2.80TM2.5LR |
| CJ28D | W255CR2.80HLR | 3500WCG–2.80HLR |
| CN28D | W255CR2.80LR | 3500WCG–2.80LR |
| CT28D | W255CR2.80T0LR | 3500WCG–2.80T0LR |
| CV28D | W255CR2.80T2LR | 3500WCG–2.80T2LR |
| CG28D | MW255CR2.80TM2.5LR | 3500MWCG–2.80TM2.5LR |
| EJ28 | EN255CR2.80HR | 3500EN–2.80HR |
| EN28 | EN255CR2.80R | 3500EN–2.80R |
| ET28 | EN255CR2.80T0R | 3500EN–2.80T0R |
| EV28 | EN255CR2.80T2R | 3500EN–2.80T2R |
| EG28 | MEN255CR2.80TM2.5LR | 3500MEN–2.80TM2.5R |
| EJ28W | WEN255CR2.80HR | 3500WEN–2.80HR |
| EN28W | WEN255CR2.80R | 3500WEN–2.80R |
| ET28W | WEN255CR2.80T0R | 3500WEN–2.80T0R |
| EV28W | WEN255CR2.80T2R | 3500WEN–2.80T2R |
| EG28W | MWEN255CR2.80TM2.5R | 3500MWEN–2.80TM2.5R |
| EJ28E | EN255CR2.80HLR | 3500EN–2.80HLR |
| EN28E | EN255CR2.80LR | 3500EN–2.80LR |
| ET28E | EN255CR2.80T0LR | 3500EN–2.80T0LR |
| EV28E | EN255CR2.80T2LR | 3500EN–2.80T2LR |
| EG28E | MEN255CR2.80TM2.5LR | 3500MEN–2.80TM2.5LR |
| EJ28D | WEN255CR2.80HLR | 3500WEN–2.80HLR |
| EN28D | WEN255CR2.80LR | 3500WEN–2.80LR |
| ET28D | WEN255CR2.80T0LR | 3500WEN–2.80T0LR |
| EV28D | WEN255CR2.80T2LR | 3500WEN–2.80T2LR |
| EG28D | MWEN255CR2.80TM2.5LR | 3500MWEN–2.80TM2.5LR |

See footnotes at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data.

| PIN designator AA59590/23 | Vendor similar designator or type part number 1/ 2/ | |
|---|---|---|
| | CAGE 61081 | CAGE 5BG68 |
| HJ28 | HA255CR2.80HR | 3500BH–2.80HR |
| HN28 | HA255CR2.80R | 3500BH–2.80R |
| HT28 | HA255CR2.80T0R | 3500BH–2.80T0R |
| HV28 | HA255CR2.80T2R | 3500BH–2.80T2R |
| HG28 | MHA255CR2.80TM2.5LR | 3500MBH–2.80TM2.5R |
| HJ28W | WHA255CR2.80HR | 3500WBH–2.80HR |
| HN28W | WHA255CR2.80R | 3500WBH–2.80R |
| HT28W | WHA255CR2.80T0R | 3500WBH–2.80T0R |
| HV28W | WHA255CR2.80T2R | 3500WBH–2.80T2R |
| HG28W | MWHA255CR2.80TM2.5LR | 3500MWBH–2.80TM2.5R |
| HJ28E | HA255CR2.80HLR | 3500BH–2.80HLR |
| HN28E | HA255CR2.80LR | 3500BH–2.80LR |
| HT28E | HA255CR2.80T0LR | 3500BH–2.80T0LR |
| HV28E | HA255CR2.80T2LR | 3500BH–2.80T2LR |
| HG28E | MHA255CR2.80TM2.5LR | 3500MBH–2.80TM2.5LR |
| HJ28D | WHA255CR2.80HLR | 3500WBH–2.80HLR |
| HN28D | WHA255CR2.80LR | 3500WBH–2.80LR |
| HT28D | WHA255CR2.80T0LR | 3500WBH–2.80T0LR |
| HV28D | WHA255CR2.80T2LR | 3500WBH–2.80T2LR |
| HG28D | MWHA255CR2.80TM2.5LR | 3500MWBH–2.80TM2.5LR |
| RJ28 | R255CR2.80HR | 3500CC–2.80HR |
| RN28 | R255CR2.80R | 3500CC–2.80R |
| RT28 | R255CR2.80T0R | 3500CC–2.80T0R |
| RV28 | R255CR2.80T2R | 3500CC–2.80T2R |
| RG28 | MR255CR2.80TM2.5R | 3500MCC–2.80TM2.5R |
| RJ28W | WR255CR2.80HR | 3500WCC–2.80HR |
| RN28W | WR255CR2.80R | 3500WCC–2.80R |
| RT28W | WR255CR2.80T0R | 3500WCC–2.80T0R |
| RV28W | WR255CR2.80T2R | 3500WCC–2.80T2R |
| RG28W | MWR255CR2.80TM2.5R | 3500MWCC–2.80TM2.5R |

See footnotes at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data.

| PIN designator AA59590/23 | Vendor similar designator or type part number 1/ 2/ | |
|---|---|---|
| | CAGE 61081 | CAGE 5BG68 |
| RJ28E | WR255CR2.80HR | 3500WCC–2.80HR |
| RN28E | WR255CR2.80R | 3500WCC–2.80R |
| RT28E | WR255CR2.80T0R | 3500WCC–2.80T0R |
| RV28E | WR255CR2.80T2R | 3500WCC–2.80T2R |
| RG28E | MWR255CR2.80TM2.5R | 3500MWCC–2.80TM2.5R |
| RJ28D | WR255CR2.80HLR | 3500WCC–2.80HLR |
| RN28D | WR255CR2.80LR | 3500WCC–2.80LR |
| RT28D | WR255CR2.80T0LR | 3500WCC–2.80T0LR |
| RV28D | WR255CR2.80T2LR | 3500WCC–2.80T2LR |
| RG28D | MWR255CR2.80TM2.5LR | 3500MWCC–2.80TM2.5LR |

1/ The CID PINs listed are only for length designator "28".
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59590.

PIN length examples. The CID PINs listed in table IV are for all available standard card holder lengths for this specification sheet. However, only one specific finish, mounting and configuration are listed (see PIN example for a break-down of the codes).

TABLE IV. Example of PIN with available length designators.

| PIN designator AA59590/23 | Vendor similar designator or type part number 1/ 2/ | |
|---|---|---|
| | CAGE 61081 | CAGE 5BG68 |
| EV28D | WEN255CR2.80T2LR | 3500WEN–2.80T2LR |
| EV38D | WEN255CR3.80T2LR | 3500WEN–3.80T0LR |
| EV48D | WEN255CR4.80T2LR | 3500WEN–5.80T0LR |
| EV58D | WEN255CR5.80T2LR | 3500WEN–5.80T0LR |

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59590.
2/ Other lengths are available on request.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Guidance on use of alternative parts with less hazardous or non–hazardous materials. This CID specification sheet provides for a number of alternative surface finish materials via the PIN. Users should select the PIN with the least hazardous material that meets the form, fit, and function requirements of their application.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Review activity:
Air Force – 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – FAS

Preparing activity:
DLA – CC

Project 5998–2018–003

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.