[INCH-POUND]
A-A-59590/24
6 September 2002

COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET


HOLDERS, ELECTRICAL CARD, WEDGE RETAINERS, 3 PIECE, SCREW ACTUATED DRIVE, .500 X .450 INCH BODY SIZE, WITH VISUAL LOCK INDICATION AND SCREW RETENTION

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

The complete requirements for procuring electrical card holders described herein shall consist of this document and the latest issue in effect of A-A-59590.

SCOPE. This CID specification sheet covers 3 piece card holders with a visual locking indicator feature that use screw actuated wedges to hold circuit card assemblies into their installed positions in heat sinking devices (cold plates, heat exchanger) or other applications. Card holders covered by this CID are intended to provide 60g/6ms resistance to shock, withstand 25 G-rms of vibration and provide 1 to 2 degrees C/W/inch thermal resistance between the circuit card assemblies and the heat sink surfaces. The screw retention feature is intended to prevent unintentional disassembly of the card holder. Items covered by this CID specification sheet are intended for commercial/industrial applications.

CLASSIFICATION/PART OR IDENTIFICATION NUMBER (PIN). This CID specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes).



SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card firmly in place providing high resistance to shock and vibration while providing maximum thermal transfer. The recommended installation torque for the assembly is 31 inch-pounds (3.5 N-m) for the standard screw and 35 inch-pounds (4.0 N-m) for screws with self-locking element.

Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein and the general CID. Card holders shall have a visual indicator to show when the assembly is in its relaxed (unlocked) state and a retention feature to prevent unintentional disassembly of the card holder.


Finish options. The finish options C, B or H shall be as specified in A–A–59590.

Mounting options. The mounting options N, J, T or V shall be as specified in A–A–59590. When specified, two mounting holes are required on card holders less than 6.00 inches (152.4 mm) in length. See table I and figure 1 for mounting hole spacing requirements.

Length, expanded and relaxed dimensions. The length, expanded and relaxed dimensions shall be as specified in figure 1. The length designator shall be as specified in A–A–59590 and the available lengths are listed in table I.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.156	3.97	.27	6.9	.40	10.2	.500	12.7	.600	15.24
.25	6.4	.30	7.6	.460	11.68	.57	14.5	.70	17.8

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Unless otherwise specified, tolerances are ±.02 (0.5 mm), for 2 places and ±.010 (0.25 mm), for 3 places.

FIGURE 1. Assembly configuration and dimensions.

TABLE I. Additional assembly dimensions (see figure 1).

PIN length designator	Dimension “LENGTH” ± .02 (0.5 mm)	Dimension “B” ± .03 (0.8 mm)	Dimension “M” ± .005 (0.13 mm)
28	2.8 (71)	2.30 (58.4)	.90 (22.9)
38	3.8 (97)	3.30 (76.2)	1.90 (48.3)
48	4.8 (122)	4.30 (101.7)	2.90 (73.7)
58	5.8 (147)	5.30 (127.0)	3.90 (99.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Visual lock indicator (see figure 2). When the card holder is in the unlocked (relaxed) state, the end of the actuating screw shall display a red band on the side of the screw. When the actuating screw on the card holder has been tightened (assembly expanded) so that the assembly is in the locked position, this red band shall be concealed.




FIGURE 2 Visual lock indicator.

Screw retention (locknut). The screw retention feature intended to prevent unintentional disassembly of the card holder shall be as specified in figure 3. The locknut shall be fabricated of a corrosion resistant material.




FIGURE 3. Screw retaining self-locking nut (corrosion resistant) details.

Options. Card holders can have the following options. Card holders not requiring one of the following options shall leave the options position in the PIN blank.

Lockwasher and flat washer (see figure 4). A lockwasher and flat washer located under the screw head will provide for additional resistance to loosening from shock and vibration. Card holders requiring a lockwasher and flat washer option shall include a suffix “W” in the PIN (see classification and notes).




FIGURE 4. Lockwasher and flat washer details.

Screw self-locking element (see figure 5). The use of a screw self-locking element will provide prevailing torque for resistance to loosening from shock vibration. Card holders requiring a screw self-locking element shall include a suffix “E” in the PIN (see classification and notes).




FIGURE 5. Screw self-locking element details.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

Lockwasher, flat washer, and screw self-locking element. Card holders requiring a lockwasher, flat washer, and screw self-locking element option shall include a suffix “D” in the PIN (see classification and notes).

NOTES.

PIN. The PIN should be used for government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Manufacturer CAGE	Manufacturer name and address	Manufacturer contact information
52094	Calmark Corporation 4915 Walnut Grove Avenue San Gabriel, CA 91776–2099	Tel: (626) 287–0451 Fax: (626) 287–7350 E-mail: sales@calmark.com URL: www.calmark.com

Part number supersession data. This CID specification sheet part numbers supersedes the following manufacturer’s part numbers as shown. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE II. Commercial part number supersession data. 1/

PIN designator AA59590/24	Vendor similar designator or type part number 2/ CAGE 52094	PIN designator AA59590/24	Vendor similar designator or type part number 2/ CAGE 52094
CJ28	V255CR2.80HR	CJ28W	WV255CR2.80HR
CN28	V255CR2.80R	CN28W	WV255CR2.80R
CT28	V255CR2.80T0R	CT28W	WV255CR2.80T0R
CV28	V255CR2.80T2R	CV28W	WV255CR2.80T2R
CJ28E	V255CR2.80HLR	CJ28D	WV255CR2.80HLR
CN28E	V255CR2.80LR	CN28D	WV255CR2.80LR
CT28E	V255CR2.80T0LR	CT28D	WV255CR2.80T0LR
CV28E	V255CR2.80T2LR	CV28D	WV255CR2.80T2LR
BJ28	VA255CR2.80HR	BJ28W	WVA255CR2.80HR
BN28	VA255CR2.80R	BN28W	WVA255CR2.80R
BT28	VA255CR2.80T0R	BT28W	WVA255CR2.80T0R
BV28	VA255CR2.80T2R	BV28W	WVA255CR2.80T2R
BJ28E	VA255CR2.80HLR	BJ28D	WVA255CR2.80HLR
BN28E	VA255CR2.80LR	BN28D	WVA255CR2.80LR
BT28E	VA255CR2.80T0LR	BT28D	WVA255CR2.80T0LR
BV28E	VA255CR2.80T2LR	BV28D	WVA255CR2.80T2LR

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.

TABLE II. Commercial part number supersession data. 1/ – Continued.

PIN designator AA59590/24	Vendor similar designator or type part number 2/ CAGE 52094	PIN designator AA59590/24	Vendor similar designator or type part number 2/ CAGE 52094
HJ28	VHA255CR2.80HR	HJ28W	WVHA255CR2.80HR
HN28	VHA255CR2.80R	HN28W	WVHA255CR2.80R
HT28	VHA255CR2.80T0R	HT28W	WVHA255CR2.80T0R
HV28	VHA255CR2.80T2R	HV28W	WVHA255CR2.80T2R
HJ28E	VHA255CR2.80HLR	HJ28D	WVHA255CR2.80HLR
HN28E	VHA255CR2.80LR	HN28D	WVHA255CR2.80LR
HT28E	VHA255CR2.80T0LR	HT28D	WVHA255CR2.80T0LR
HV28E	VHA255CR2.80T2LR	HV28D	WVHA255CR2.80T2LR

1/ CID PINs listed only with length designator “28”.
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph of the basic CID.

TABLE III. Example of PIN with available length designators.

PIN designator AA59590/24	Vendor similar designator or type part number 1/ CAGE 52094
CJ28	V255CR2.80HR
CJ38	V255CR3.80HR
CJ48	V255CR4.80HR
CJ58	V255CR5.80HR

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph of the basic CID.

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – 7FXE

Preparing Activity
DLA – CC

Project 5998–0124

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:20Z
Check the source to verify that this is the current version before use.