MILITARY SPECIFICATION

TEST SET, ELECTRONIC CIRCUIT PLUG-IN UNIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers electronic test sets for testing plug-in units of NTDS and MTDS equipments AN/SSQ-29, AN/USQ-36, AN/SRC-16, AN/SRC-23, AN/SCA-1, AN/TYA-17, AN/TYA-19, AN/TYA-24, and test sets AN/SSM-4 and AN/SSM-4A.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-945	- Test Equipment for Use With Electronic Equipment. General Specification
MIL-E-15090	- Equipment, Light Gray (Formula No. 111)
MIL-E-16400	- Electronic, Interior Communications and Navigation Equipment, Naval Ship and Shore: General Specification for
MIL-E-17555	- Electronic and Electrical Equipment, Accessories, and Repair Parts, Packing and Packaging of

STANDARDS

MILITARY

MIL-STD-108	- Definitions of and Basic Requirements for Enclosures for Electric and Electronics Equipment
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-415	- Test Points and Test Facilities for Electronic Systems and Associated Equipment - Design Standard for
MIL-STD-781	- Reliability Tests: Exponential Distribution

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:12Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General requirements. The equipment shall be in accordance with the provisions of MIL-E-16400, except as otherwise specified herein.

3.2 Function The test set shall determine acceptable module or circuit card functioning. The test set, when used in conjunction with external general purpose test equipment, shall provide the means for testing, dynamically or by other appropriate methods, the module or circuit card under observation. The test set shall be capable of testing the individual plug-in modules and circuits used in the equipments shown in Tables I and II.

Table I. Digital modules.

Item	Federal stock no.	Description	Equipment
1.	N5895-972-9110	Counter Flip Flop	SSQ-29( ), SCA-1( )
2.	N5895-972-9094	Nand	SSQ-29( ), SCA-1( )
3.	N5895-972-9113	Inverter	SSQ-29( ), SCA-1( )
4.	N5895-972-9111	Eight Count	SSQ-29( ), SCA-1( )
5.	N5895-972-9098	Lamp Amplifier	SSQ-29( )
6.	N5895-972-9099	BCD to Decimal Converter	SSQ-29( ), SCA-1( )
7.	N5895-972-9100	Phase Selector Gate	SSQ-29( ), SCA-1( )
8.	N5895-972-9101	Detector Sampler	SSQ-29( ), SCA-1( )
9.	N5895-972-9102	Generator Pulse Former	SSQ-29( ), SCA-1( )
10.	N5895-972-9104	Universal Flip Flop	SSQ-29( ), SCA-1( )
11.	N5895-972-9103	Gate Advance	SSQ-29( ), SCA-1( )
12.	N5895-972-9105	Toggle Trigger	SSQ-29( )
13.	N5895-972-910c	Phase Detector	SSQ-29( ), SCA-1( )
14.	N5895-981-5546	Address Output Amp.	SSQ-29( )
15.	N5895-972-9107	Power Pulse Former	SSQ-29( ), SCA-1( )
16.	N5895-972-9106	Locked Oscillator	SSQ-29( ), SCA-1( )
17.	N5895-972-9109	Exclusive Or	SSQ-29( ), SCA-1( )
18.	2N5895-981-5561	Digital Tone Heterodyne	SSQ-29( ), SCA-1( )
19.	N5895-970-9048	Signal Strength Detector	SCA-1( )
20	N5895-972-9112	Input Buffer	SSQ-29( )
21.	N5895-972-9114	Power Amplifier	SSQ-29( ), SCA-1( )
22.	N5895-972-9115	Frequency Tripler	SSQ-29( ), SCA-1( )
23.	N5895-972-9116	Output Buffer Amplifier	SSQ-29( ), SCA-1( )
24.	N5895-972-911[illegible]	Distributing Amplifier	
25.	2N5895-970-9049	Receive Heterodyne A	SCA-1( )
26.	2N5895-970-9050	Receive Heterodyne B1	SCA-1( )
27.	2N5895-970-9051	Receive Heterodyne B2	SCA-1( )
28.	N5905-970-9052	Cryptor Amplifier	SCA-1( )
29.	N5895-972-9121	Keyed Filter Ckt. Board	SSQ-29( ), SCA-1( )
30.	N5895-972-9118	Nor Gate	SSQ-29( ), SCA-1( )
31.	N5895-972-9122	Multiple Input Flip Flop	SSQ-29( ), SCA-1( )
32.	N5895-972-9123	Pedestal Gate	SSQ-29( ), SCA-1( )
33.	N5895-972-9126	Grouping Amplifier	SSQ-29( ), SCA-1( )

Source: https://assist.dla.mil -- Downloaded: 20261O-20T19:12Z
Check the source to verify that this is the current version before use.

Table I. Digital modules (continued).

Item	Federal stock no.	Description	Equipment
34.	N5895-972-9127	Low Pass Filter	SSQ-29( ), SCA-1( )
35.	2N5895-987-3479	Transmit Heterodyne	SCA-1( )
36.	N5895-970-6467	HCC Level Control	SCA-1( )
37.	N5895-086-9873	Tone Presence Detector	SCA-1( )
38.	Not Assigned	NTDS Level Control	SSQ-29( )
39.	N5820-981-5509	Carrier Squaring Amp.	SCA-1( )
40.	N5895-972-9130	NTDS Net Busy Detector	SSQ-29( )
41.	N5895-972-9120	One Shot	SSQ-29( ), SCA-1( )
42.	Not Assigned	Audio Amplifier Card	SSQ-29( )
43.	N5895-970-6476	Diode And	SCA-1( )
44.	N5895-970-6478	Diode Or	SCA-1( )
45.	N5895-970-6479	RPC Pulse Generator	SCA-1( )
46.	N5895-970-6480	Printer Control	SCA-1( )
47.	N5895-970-9041	Tone Keyer	SCA-1( )
48.	N5895-970-6481	Matrix Power Regulator	SCA-1( )
49.	N5895-086-9880	TTY Multivibrator	SCA-1( )
50.	N5895-970-9042	TTY Send Detector	SCA-1( )
51.	N5895-971-1911	One Shot	SCA-1( )
52.	N5895-970-9040	Three Input Nor	SCA-1( )
53.	N5895-086-9878	Three Input Nand	SCA-1( )
54.	N5895-970-6472	Universal Flip Flop	SCA-1( )
55.	N5895-970-6474	Highest Power Inverter	SCA-1( )
56.	N5895-970-9043	Scanning Multivibrator	SCA-1( )
57.	N5895-086-9876	Nand	SCA-1( )
58.	N5895-086-9877	Eight Count	SCA-1( )
59.	N5895-970-9039	Counter Flip Flop	SCA-1( )
60.	N5895-970-6473	Inverter	SCA-1( )
61.	N5895-970-9038	Pedestal Gate	SCA-1( )
62.	N5895-970-9037	Nor	SCA-1( )
63.	N5895-970-9044	PNP Lamp Amplifier	SCA-1( )
64.	N5895-970-9045	NPN Lamp Amplifier	SCA-1( )
65.	N5895-970-9047	Matrix Bias Regulator	SCA-1( )
66.	N5820-979-3886	Relay Driver	SCA-1( )
67.	N5895-979-3885	Matrix Power Oscillator	SCA-1( )
68.	N5820-978-4543	Ringing Generator	SRC-16( )
69	N5820-981-3369	Conference Bridge	SRC-16( )
70.	N5820-978-4547	Operate Receive Amplifier	SRC-16( )
71.	N5820-682-3986	Wave Shaper	AN/SSM-4( )
72.	N5820-682-3987	Multivibrator	AN/SSM-4( )
73.	N5820-682-3991	Phase Shifter	AN/SSM-4( )
74.	N5895-682-3992	Audio Oscillator	AN/SSM-4( )
75.	N5999-682-3990	Special Function Generator	AN/SSM-4( )
76.	N6625-740-5273	Pulse Driver	AN/SSM-4( )
77.	N5999-682-3985	Voltage Control	AN/SSM-4( )
78.	N5820-978-9704	Network Squelch	SRC-16( )
79.	N5845-981-3364	Conference Transmit Amp.	SRC-16( )
80.	N5820-981-5477	Conference Receive Amp.	SRC-16( )

Source: https://assist.dla.mil -- Downloaded: 202640-20T19:12Z
Check the source to verify that this is the current version before use.

Table I. Digital modules (continued).

Item	Federal stock no.	Description	Equipment
81.	N5820-981-5476	Component Mounting Board	SRC-16( )
82.	N5895-981-1465	Off-Hook Relay	SRC-16( )
83.	N5945-981-3374	Aural Disable	SRC-16( )
84.	N5820-981-8960	Relay Unit, AM Enable	SRC-16( )
85.	N5820-978-2585	Selector, Multicoupler	SRC-16( )
86.	N5820-981-3372	Selector, Whip Coupler	SRC-16( )
87.	N5820-981-3363	Relay Unit, Receiver Crosspoint	SRC-16( )
88.	N5820-981-3370	Relay Unit, Crosspoint #1	SRC-16( )
89.	N5820-978-4540	Relay Unit, Matrix Jump	SRC-16( )
90	N5820-981-3371	Terminal Load	SRC-16( )
91.	N5820-981-3362	SSB/Conference	SRC-16( )
92.	N5895-981-1471	Simplex	SRC-16( )
93.	N5825-981-1470	Duplex	SRC-16( )
94.	N5825-981-1468	Tone	SRC-16( )
95.	N5895-981-1469	Voice	SRC-16( )
96.	N5820-978-9703	Selector, Channel XMTR	SRC-16( )
97	N5820-978-2574	Selector, Channel RCVR	SRC-16( )
98	N5945-978-4537	Ring Counter Stage	SRC-16( )
99.	N5820-978-2575	Clock Pulse	SRC-16( )
100.	N5945-978-4538	Antenna Transfer	SRC-16( )
101.	N5945-978-2576	Interlock	SRC-16( )
102.	N5945-978-2577	Hold Transfer	SRC-16( )
103.	N5945-978-4539	Band Transfer	SRC-16( )
104.		JJ5 Multi Purpose FF	USQ-36
105		JJ8 Phase Mod	USQ-36
106.		JK2 Strobe Driver	USQ-36
107.		JK3 RC Correlator	USQ-36
108.		JK4 Drive Logic	USQ-36
109.		JK5 Sig. Pres. 1	USQ-36
110.		JK7 Sig. Pres. 2	USQ-36
111.		JK8 Pulse Prod. Det.	USQ-36
112.		JK9 Sig. Pres. 3	USQ-36
113.		JL2 Sig. Pres. 4	USQ-36
114.		JL3 Logic A .p	USQ-36
115.		JM2 330.000 and 300.000 KC OSC	USQ-36
116.		JM3 176.000 and 250.000 KC OSC	USQ-36
117.		JM4 172.480 and 177.760 KC OSC	USQ-36
118.		JM5 179 520 and 181.280 KC OSC	USQ-36
119.		JM7 188.040 and 184.800 KC OSC	USQ-36
120.		JM8 186.560 and 191.840 KC OSC	USQ-36
121.		JM9 167.640 and 168.520 KC OSC	USQ-36
122.		JL5 Decoupler	USQ-36, SSM-4A
123.		JJ7 Trans. Mix	USQ-36
124.		JP7 Level Control	USQ-36
125.		JJ9 Audio Input/Output Transformer	USQ-36
126.		JN8 OSC Self Check	USQ-36

Source: https://assist.dla.mil -- Downloaded: 20260-20T19:12Z
Check the source to verify that this is the current version before use.

Table I. Digital modules (continued).

Item	Federal stock no.	Description	Equipment
127.		JN2 Rev Mix	USQ-36
128.		JL9 Doppler VCO	USQ-36
129.		JP3 Filter Driver	USQ-36
130.		JP4 Digital Filter	USQ-36
131.		JP5 Phase Detector	USQ-36
132.		JN4 Doppler Mixer 1	USQ-36
133.		JN3 Operational Amp.	USQ-36
134.		JL7 Frame Trans. Det. 1	USQ-36
135.		JL8 Frame Trans. Det. 2	USQ-36
136.		-- Doppler Tone Translator	USQ-36
137.		JN7 Doppler Freq. Synthesizer	USQ-36
138.		-- Address Selector	USQ-36
139.		JX3 Keyer/Alarm	TYA-17
140.		JX4 Selector Amplifier	TYA-19
141.		JX5 Discriminator/Output	TYA-19
142.		JX2 OSC/AMPL	TYA-17
143.		JX7 Data Hub	TYA-19
144.		KD7 MTDS Relay Control	TYA-17, 19, 24
145.		KD8 Alarm Summary	TYA-19
146.		KD9 Microphone Amp.	TYA-19
147.		KJ4 Positive/Negative Pulse Driver	SSM-4A
148.		KT7 PPD Test Generator	SSM-4A
149.		KT5 Test Pattern Generator	SSM-4A
150.		KT8 Squaring Amplifier	SSM-4A
151.		GT4 Multivibrator	SSM-4A
152.		JP8 Address Output Amplifier	USQ-36
153.		KH4 Detector Alarm	TYA-19
154.		JP9 Phase Shifter	USQ-36
155.		JN9 Oscillator Self-check 2	USQ-36
156.		JP2 Oscillator Self-check 3	USQ-36
157.		LK2 Relay/Driver	TYA-17
158.		-- Thermal Alarm Control	SRC-23
159.		-6V A3 Circuit Board	USQ-36(V)
160.		-15V A4 Circuit Board	USQ-36(V)
161.		+15V A1 Circuit Board	USQ-36(V)
162		+ 6V A2 Circuit Board	USQ-36(V)
163.		Gate Electronic Transmitter	SRC-23(V), SRA-34(V)
164.		Counter, Electronic Digital	SRC-23(V), SRA-34(V)
165.		Gate, Electronic Counter	SRA-34(V)
166.		Timer, Sequence	SRA-34(V)
167.		Circuit Card Assembly	SRA-34(V)
168.		Circuit Card Assembly	SRA-34(V)

Source: https://assist.dla.mil -- Downloaded: 20260-20T19:12Z
Check the source to verify that this is the current version before use.

Table II. Analog modules.

Item	Federal stock no.	Description	Equipment
1.	N5820-086-8768	LSB Amplifier-Mixer	SRC-16( )
2.	N5820-086-8769	USB Amplifier-Mixer	SRC-16( )
3.	2N5820-983-4103	Transmitter Gain Control	SRC-16( )
4.	2N5820-986-0568	Balanced Modulator	SRC-16( )
5.	2N5821-983-4105	Frequency Multiplier Comparator	SRC-16( )
6	N5820-086-8973	RF Isolation Amplifier	SRC-16( )
7.	N5820-086-8718	Coupler, Control Servo	SRC-16( )
8.	N5820-084-3383	Coupler, Control Servo	SRC-16( )
9.	2N5895-983-4109	MC Frequency Stabilizer	SRC-16( )
10.	N5820-973-2583	Frequency Multiplier	SRC-16( )
11.	2N5820-979-5929	IF/AM Amplifier	SRC-16( )
12.	N5820-981-3373	Electronic Control Amp.	SRC-16( )
13.	N5820-978-2584	Receiver Gain Control	SRC-16( )
14.	2N5985-979-5930	Variable RF Attenuator	SRC-16( )
15.	N5820-084-3446	1 MC Frequency Divider	SRC-16( )
16.	N5820-084-3447	100 KC Frequency Divider	SRC-16( )
17.	N5895-981-3367	Compression Amplifier	SRC-16( )
18.	N5820-086-8771	Audio Frequency Amplifier	SRC-16( )
19.	N6130-086-8976	Power Supply	SRC-16( )
20.	2N5845-983-4104	Antenna Coupler Control	SRC-16( )
21.	N6110-086-8990	Electric Control Amp.	SRC-16( )
22.	N5820-931-3366	Amplifier Mixer	SRC-16( )
23.	N5820-981-5476	Audio Frequency Amplifier	SRC-16( )
24.	N6130-981-3368	Power Supply	SRC-16( )
25.	N5820-978-9707	Audio Frequency Osc.-CW	SRC-16( )
26.	N6130-981-5473	Power Supply	SRC-16( )
27.	N6110-977-6080	Electronic Control Amp.	SRC-16( )
28	N6130-981-5469	Power Supply	SRC-16( )
29.	2N6130-979-5923	Power Supply, AC	SRC-16( )
30.	N5820-981-5476	Relay Unit	SRC-16( )
31.	N5820-981-5478	Rotary Switch Control	SRC-16( )
32.	N5820-978-2582	Speaker Amplifier	SRC-16( )
33.	2N5820-686-8140	FSK Oscillator	SRC-16( )
34.		R.F. Tuner	SRC-23
35.		Frequency Divider-Stab.	SRC-23
36.		Oscillator, R.F. - B.F.O.	SRC-23
37.		TR Relay	SRC-23
38.		Protector, Rcvr. Overload	SRC-23
39.		Relay Ass'y, Rec.	SRC-23
40.		Relay Ass'y, Trans.	SRC-23
41.		Power Supply	SRC-23
42.		Adapter, Radio Set	SRC-23
43.		Sweep Generator	SRC-23

Source: https://assist.dla.mil -- Downloaded: 202610-20T19:12Z
Check the source to verify that this is the current version before use.

3.3 Reliability. The equipment shall conform to the reliability requirements of 4.5.

3.4 Design requirements.

3.4.1 Minimum limitations. The test set shall consist of the minimum number of units that will test the modules specified herein and shall conform to the requirements for size, weight, and reliability specified herein.

3.4.1.1 Construction (modular). The requirements of MIL-E-16400 for modular construction shall apply.

3.4.2 Operating conditions. The equipment shall be capable of operation under the following conditions as specified in MIL-E-16400:

(a) Temperature, Range 4.
(b) Humidity.

3.4.3 Input power. The primary power required by the AN/SSQ( ) (V) (U) units of the test set shall be 115 volt, single phase, 50 to 400 Hertz (Hz). The primary power required by the AN/SRC-23(V) units of the test set shall insure operation at both 115 volt, delta-connected, three phase, 400 Hz or 115 volt line-to-neutral Y-connected. The limit of operation shall be ±10 percent in voltage and ±5 percent in frequency over the nominal value specified.

3.4.4 Mechanical. Mechanical design shall conform to the following:

3.4.4.1 Shock and vibration. Shock and vibration requirements shall be in accordance with MIL-T-945.

3.4.4.2 Enclosure. The degree of enclosure shall be dripproof in accordance with MIL-STD-108.

3.4.5 Controls, indicators, and panel layout.

3.4.5.1 Identification. Tactile identification of controls is not required.

3.4.5.2 Control classification. Controls are classified as continually required.

3.4.5.3 Locking devices. Locking devices on controls are not required.

3.4.5.4 Elapsed time meters. Elapsed time meters shall be provided.

3.4.6 Size. The test set shall be designed to conform to shipboard maintenance conditions of the NTDS program, and shall be as compact and maintainable as practical. The test set may be configured in separate units. These units shall be portable and each unit shall be contained in a combination case as specified in MIL-T-945. In no event shall any unit of the test set for AN/SRC-23 exceed an overall dimension of 27-1/2 inches (69.85 cm) wide, 21 inches (53.34 cm) deep, and 14 inches (35.56 cm) high, nor shall any unit of the test set

Source: https://assist.dla.mil -- Downloaded: 20260-20T19:12Z
Check the source to verify that this is the current version before use.

pertaining to AN/USQ-36( ) circuit cards exceed an overall dimension of 24 inches (60.96 cm) wide, 24 inches (60.96 cm) deep, and 14 inches (35.56 cm) high.

3.4.7 Weight. The weight of any unit shall not exceed 100 pounds. The weight of any unit for testing AN/USQ-36( ) circuit cards shall not exceed 85 pounds.

3.4.8 Equipment design. Special attention shall be given to the design of the test set to assure the greatest possible convenience to the operator. It shall be possible to conduct marginal tests on a module or circuit card where applicable.

3.4.8.1 Trouble isolation. The test set shall be so designed that an electronic technician 3rd class can readily determine the existence of trouble within a module or circuit card and, where practical and desirable, isolate the trouble to a particular circuit on the module or circuit card.

3.4.9 Card test holder. The test set shall also include module or circuit card test holders that will accept, at the option of the user, any one of the prime equipment plug-in modules or circuit cards specified in 3.2. The module or circuit card holders shall be designed as part of the main cabinet or be supplied as attachment items included with the main cabinet. If practicable, one module or circuit card test holder shall be designed for each group of system modules or circuit cards excluding those modules and circuit cards not within the testing capability of the test set.

3.5 Performance. When performing module or circuit card tests, the test set shall operate in conjunction with a minimum of external standard general purpose test equipment. The test set shall provide power source voltages for energizing each module or circuit card under test If practical, the signal sources shall be provided by the test set; however, they may be provided by external standard test equipment. Monitoring of outputs shall be accomplished in conjunction with the external standard test equipment.

3.6 Test point facilities. The module test set shall provide test point facilities for connecting the monitoring scopes or meters that may be required for testing and measuring the modules or circuit cards under test as well as the module test set Test point facilities for the module test shall be in accordance with MIL-STD-415, however, the need to employ monitoring scopes and meters shall be kept to a minimum. Standard monitoring equipment that will be required for checking a module or circuit card under test shall not be supplied as part of the module test set. A listing of this equipment shall be submitted to the Naval Electronic Systems Command early in the contract period. A list of the test equipment that will normally be aboard ship will be furnished the contractor as a guide for the selection of items that may be used as standard monitoring equipment. If the equipment selected for monitoring purposes has to be modified, the modified equipment shall be supplied as part of the test set.

3.7 Patch leads. Patch leads or cables, as necessary, shall be supplied by the contractor.

Source: https://assist.dla.mil -- Downloaded: 202640-20T19:12Z
Check the source to verify that this is the currentversion before use.

3.8 Painting. The equipment shall be finished with gray enamel, type II, class 1, in accordance with MIL-E-15090.

3.9 Instruction plates. Instruction plates are not required.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Government verification. All quality assurance operations performed by the contractor will be subject to Government verification at any time. Verification will include (a) surveillance of the operations to determine that practices, methods, and procedures are being properly applied, (b) Government product inspection to measure quality of product to be offered for acceptance, and (c) Government product inspection of delivered products to assure compliance with all inspection requirements of this specification. Failure of the contractor to promptly correct deficiencies discovered by him or of which he is notified shall be cause for suspension of acceptance until corrective action has been made or until conformance of product to prescribed criteria has been demonstrated.

4.1.2 Quality assurance terms and definitions. Quality assurance terms used in this specification shall be as defined in MIL-STD-109.

4.2 Classification of inspection. The method of examination and testing shall be classified as follows:

(a) First article inspection (4.3)
(b) Quality conformance inspection (4.4)

(1) Production inspection (4.4.1)
(2) Environmental inspection (4.4.2)

(c) Reliability testing (4.5)
(d) Inspection of preparation for delivery (4.4.3)

4.3 First article inspection. First article inspection shall consist of all examinations and tests necessary to determine conformance with the requirements of this specification. First article inspection shall include the examination and testing specified in production inspection and environmental inspection.

Source: https://assist.dla.mil -- Downloaded: 202610-20T19:12Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Production inspection. Production inspection shall be made on every equipment offered for delivery. The inspection shall comprise such examination and testing as will prove the workmanship and reveal the omissions and errors of the production process such as functional and performance tests at a limited number of points, tests which detect deviations from design, tests of adjustment, and tests which detect hidden defects of material. Production inspection shall include the requirements of 3.2.

4.4.2 Environmental inspection. Environmental inspection shall be as listed below and shall be performed on units which have been subjected to and passed production inspection.

Environmental inspection.

Inspection	Reference paragraph
Low temperature	3.4.2
High temperature	3.4.2
Steady-state voltage and frequency	3.4.3
Transient voltage	3.4.3
Transient frequency	3.4.3
Power interruption	3.4.3

4.4.2.1 Sampling for environmental inspection. One equipment shall be selected from each successive 50 equipments produced or fraction thereof. The first sample equipment shall be selected from the first months production.

4.4.3 Inspection of preparation for delivery. Inspections shall be conducted to insure conformance with the requirements of Section 5 of this specification.

4.5 Reliability test. The equipment shall be subjected to a 700 hour reliability test in accordance with test plan XXVIII of MIL-STD-781. The test shall be in accordance with test level C of MIL-STD-781 except that the off cycle shall be one hour per day. Input voltage cycling shall be required.

4.5.1 Test sample. The total operating test time shall be 700 hours to be accumulated on one unit or divided between two or more units. The test shall be completed prior to the delivery of production equipment.

4.5.2 Failure. Failures are malfunctions or parameter deviations which prevent the equipment from performing within the operational requirements specified herein.

4.5.3 Evaluation of test. No specific accept/reject criteria is established. The contractor shall evaluate each observed failure to determine the cause. Where equipment manufacturer design or part manufacturer design

Source: https://assist.dla.mil -- Downloaded: 202610-20T19:12Z
Check the source to verify that this is the current version before use.

deficiencies are identified or when pattern failures (as defined by MIL-STD-781) exist, the contractor shall propose and implement corrective action to prevent or reduce the probability of recurrence. The test shall be considered successfully completed when all corrective actions have been approved by the procuring activity.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging, packing, and marking. The equipment, accessories, and technical publications shall be preserved and packaged by level A or C; packed by level A, B, or C; and marked as specified in the order in accordance with MIL-E-17555.

6 NOTES

6.1 Intended use. This equipment is intended for shipboard use.

6.2 Environmental inspection. Approval to ship may be withheld at the discretion of the Government, pending the decision from the contracting officer on the adequacy of corrective action.

6.2.1 Initial shipments. Initial shipment of end items will be contingent upon successful completion of the environmental inspection.

Preparing activity:
Navy - EC

(Project 6625-N660)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay or will otherwise enhance use of the document DoD contractors government activities or manufacturers vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes" in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:12Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Naval Electronic Systems Command
ATTN ELEX 5043
Department of the Navy
Washington, DC 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-20T19:12Z
Check the source to verify that this is the current version before use.