MILITARY SPECIFICATION

VOLTAGE REGULATOR SUBASSEMBLY: 10525765

This amendment forms a part of Military Specification MIL-V-60219(MU), dated 3 March 1965.

* Paragraph 4.5.2.1.1.3: Add to sentence "except that the trip current resistors shall be values that give the next higher bias ratio (R7 to R3 for -6V) and (R27 to R28 for +35V) than the potentiometer settings".

Paragraph 4.5.2.3.2: Delete last line and substitute "shall be greater than 72.0 milliamperes but less than 168 milliamperes".

* Paragraph 4.5.2.5.1.3.1: Delete "1.3 amperes ± 0.15 amperes" and substitute "1.3 amperes $^{+\ 0.26\ \text{amperes}}_{-\ 0.0}$".

* Paragraph 4.5.2.5.1.3.2: Delete "10.0 amperes ± 0.9 amperes" and substitute "10.0 amperes $^{+\ 1.0\ \text{amperes}}_{-\ 0.0}$".

Paragraph 4.5.2.6.1.4: Delete last line and substitute "rms AC current shall be greater than 50 milliamperes but less than 168 milliamperes".

Paragraph 4.5.2.6.2.5: Delete last line and substitute "rms AC current shall be greater than 72 milliamperes but less than 218 milliamperes".

Table VI (a): Add the following part and part number under appropriate columns:

"C12"	"10525820"

Figure No. 2: Add new capacitor "C12" shunted across the "minus 6V load".

* The outside margin has been marked to indicate where additions to the previous amendment has been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A252Y

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:20Z
Check the source to verify that this is the current version before use.