INCH-POUND

MIL-DTL-83503/21D
21 July 2004
SUPERSEDING
MIL-C-83503/21C
17 June 1998

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, FLAT CABLE, NONENVIRONMENTAL, HEADER, STRAIGHT THRU (.100 INCH SPACING) WITH POLARIZING FEATURE SOLDERLESS WRAPPOST OR PWB TERMINATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83503.






FIGURE 1. Dimensions and configuration.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.








FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.003	0.08	.025	0.64	.05	1.3	.240	6.10
.005	0.13	.030	0.76	.060	1.52	.250	6.35
.006	0.15	.032	0.81	.08	2.0	.290	7.37
.010	0.25	.034	0.86	.100	2.54	.31	7.9
.01	0.3	.035	0.89	.105	2.67	.32	8.13
.012	0.30	.042	1.07	.116	2.95	.352	8.94
.015	0.38	.045	1.14	.125	3.18	.573	14.55
.020	0.51	.050	1.27	.142	3.60	.610	15.49
				.16	4.1	1.3	33.0

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ± .005 inch (0.13 mm) for three place decimals and ± .01 inch (0.3 mm) for two place decimals.
4. For 10 and 14 position connectors the polarizing feature on this end is non-existent.
5. Two thread cutting screws, No. 4-24 (1/4 inch long) type BG are provided.
6. Pin length for printed wiring board (PWB) thickness of is as follows:

PWB thickness inch (mm)	Pin length Min inch (mm)	Pin length Max inch (mm)
.062 (1.57)	.089 (2.26)	.116 (2.95)
.125 (3.18)	.152 (3.86)	.178 (4.52)

7. Solderless wrappost, pin length shall be .610 ±.015 inch (15.49 ±0.38 mm).

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and characteristics.

Dash Number	Number of pins	Dimensions						
		A inch (mm)	B inch (mm)	C inch (mm)	D 1/ inch (mm)	E spaces	F inch (mm)	Termination, right angle contact type
-01 -02 -03	10 10 10	1.26 (32.0)	1.10 (27.9)	.86 (21.84)	.690 (17.53)	4	.400 (10.16)	.062 PWB .125 PWB Wrappost
-04 -05 -06	14 14 14	1.46 (37.1)	1.30 (33.0)	1.06 (26.92)	.890 (21.34)	6	.600 (15.24)	.062 PWB .125 PWB Wrappost
-07 -08 -09	16 16 16	1.56 (39.6)	1.40 (35.6)	1.16 (29.46)	.990 (25.15)	7	.700 (17.78)	.062 PWB .125 PWB Wrappost
-10 -11 -12	20 20 20	1.76 (44.7)	1.60 (40.6)	1.36 (34.54)	1.190 (30.23)	9	.900 (22.86)	.062 PWB .125 PWB Wrappost
-13 -14 -15	26 26 26	2.06 (52.3)	1.90 (48.3)	1.66 (42.16)	1.490 (37.85)	12	1.200 (30.48	.062 PWB .125 PWB Wrappost
-16 -17 -18	34 34 34	2.46 (62.5)	2.30 (58.4)	2.06 (52.32)	2.06 (52.32)	16	1.600 (40.64)	.062 PWB .125 PWB Wrappost
-19 -20 -21	40 40 40	2.76 (70.1)	2.60 (66.0)	2.36 (59.94)	2.36 (59.94)	19	1.900 (48.26)	.062 PWB .125 PWB Wrappost
-22 -23 -24	50 50 50	3.26 (82.8)	3.10 (78.7)	2.86 (72.64)	2.86 (72.64)	24	2.400 (60.96)	.062 PWB .125 PWB Wrappost
-25 -26 -27	60 60 60	3.76 (95.5)	3.60 (91.4)	3.36 (85.34)	3.36 (85.34)	29	2.900 (73.66)	.062 PWB .125 PWB Wrappost
-28 -29 -30	64 64 64	3.96 (100.6)	3.80 (96.5)	3.56 (90.42)	3.390 (86.11)	31	3.100 (78.74)	.062 PWB .125 PWB Wrappost

1/ Tolerance for “D” dimension is +.030 -.000 inch (+0.76 -0.00 mm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configurations: See figure 1 and table I.

Temperature range: -55° to +120°C.

Voltage rating: 300 V rms.

Current rating: 1 ampere.

Materials:

Contacts: The contacts shall be phosphor bronze or brass. Phosphor bronze shall be in accordance with ASTM B139, copper alloy UNS No. C51000. Brass shall be in accordance with copper alloy CDA 260, spring temper; or copper alloy UNS No. C72500 spring temper in accordance with ASTM B122.

Contact plating:

Contact area: Gold in accordance with MIL-DTL-83503.

Solder tail termination area: Gold or tin-lead in accordance with MIL-DTL-83503.

Housing: Glass filled polyester in accordance with MIL-M-24519, type GPT-15F, GPT-20F, GPT-30F.

Accessories: Parts may be constructed of polyester in accordance with MIL-M-24519 or other materials specified in MIL-DTL-83503, provided these parts do not come in contact with current carrying components.

Polarization key: Shall be permanently attached to header (added feature key shall be bonded to header).

Mating connector: See MIL-DTL-83503/7.

Solderless wrappost contacts:


Wrappost geometry: .045 inch (1.14 mm) square wrappost in accordance with figures 2 and 3.

Parallelism: See figure 3 and table.

Tip configuration: The tip configuration of the wrappost shall terminate in a radius or bevel to facilitate insertion of the wrapping tool. See figure 3.

Solderless wrappost contact wire accommodation: 26 or 28 AWG solid.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.




Number of wrapped corrections	"E" Length	
	Wire gage 28 inch (mm)	Wire gage 26 inch (mm)
1	.219 (5.56)	.226 (5.74)
2	.388 (9.85)	.402 (10.21)
3	.557 (14.15)	.578 (14.68)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 2. Wrappable length (typical connection).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.



Inches	mm
.0012	0.030
.0015	0.038
.003	0.076

A inch (mm)	B inch (mm)	C inch (mm)	Parallelism inch (mm)	Straightness Inch/inch
.045 (1.14) nominal .042 (1.07) min	.045 (1.14) nominal .042 (1.07) min	.066 (1.68) max .059 (1.50) min	.005 (0.13)	.005

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. If the tip of the wrappost terminates in a bevel, the apex of the bevel shall be flat, with no side of the flat exceeding .020 inch.

FIGURE 3. Wrappost geometry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.

Withstanding voltage:

Sea level: 500 V rms, minimum.

Altitude: 200 V rms, minimum.

Cable retention: Not applicable.

Connector-cable flexing: Not applicable.


Contact resistance: 50 milliohms, maximum.

Latch retention: The latch shall retain the mating connector when the cable retention force is applied to the mating connector cable. The latch shall also function as an ejector to eject mating connector.

Marking:

Part or identifying number (PIN): The PIN shall consist of the letter “M”, followed by the basic specification number, “/”, the specification sheet number, “-” and dash number from table I.

Example:



Contact identification: Molded triangle “ Δ ” or notch to show number 1 contact, or raised numbers to show position number “1”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.

Referenced documents: In addition to MIL-DTL-83503, this document references the following:

MIL-M-24519
MIL-DTL-83503/7
ASTM B122
ASTM B139
CDA 260

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4601-002)

Review activities:
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://www.dodssp.daps.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:20Z
Check the source to verify that this is the current version before use.