INCH-POUND

MIL-DTL-83513/8F
22 March 2007
SUPERSEDING
MIL-DTL-83513/8E
25 June 2002

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, PLUG, MICROMINIATURE, POLARIZED SHELL, PIN CONTACTS, CLASS P, CRIMP TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83513.




FIGURE 1. Connector, plug, .050 spacing.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connector, plug, .050 spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.


Number of cavities	A ±.010	B BSC	C +.010 -.018	D BSC
9	.778 (19.76)	.2918 (7.412)	.398 (10.11)	.565 (14.35)
15	.928 (23.57)	4418 (11.222)	.548 (13.92)	.715 (18.16)
21	1.078 (27.38)	.5918 (15.032)	.698 (17.73)	.865 (21.97)
25	1.178 (29.92)	.6918 (17.572)	.798 (20.27)	.965 (24.51)
31	1.328 (33.73)	.8418 (21.382)	.948 (24.08)	1.115 (28.32)
37	1.478 (37.54)	.9918 (25.192)	1.098 (27.89)	1.265 (32.13)
51	1.428 (36.27)	.9418 (23.922)	1.048 (26.62)	1.215 (30.86)

Inches	mm
.0019	0.048
.002	0.05
.0038	0.097
.004	0.10
.005	0.13
.006	0.15
.010	0.25
.014	0.36
.025	0.64
.027	0.69
.032	0.81
.036	0.91
.045	1.14
.0459	1.166
.050	1.27
.0664	1.687
.088	2.24
.093	2.36
.094	2.39
.095	2.41
.130	3.30
.1138	2.89
.173	4.39
.199	5.05
.208	5.28

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm).
4. Metric equivalents are in parentheses or columns.
5. Plane from which the lead length is measured.

FIGURE 1. Connector, plug, .050 spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.



NOTES:
1. Engaging face of pin insert shown.
2. Cavity identification numbers are for reference only and do not appear on part.

FIGURE 2. Insert arrangement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1. This specification sheet describes the pin side of a rectangular plastic shell connector. This connector uses reverse gender contact, i.e., the live pin recessed in the insulator with the static socket protruding from a shrouded interface.

Material and finish:

Shell: The requirements for shell materials shall be in accordance with MIL-DTL-83513.

Contact identification: See figure 2 for contact layout identification.

Contact connection: The pin contact (being recessed in the insulator) is normally connected to the live side of the circuit.

Current rating, maximum: 3 amperes per contact.

Mounting and mating hardware: Hardware is to be ordered separately, (see MIL-DTL-83513/5, configuration A and B).

Mounting hardware torque: 2.0 to 2.5 inch-pounds

Mating receptacle: Mating receptacle in accordance with MIL-DTL-83513/7 or MIL-DTL-83513/9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.

Example of Part or Identifying Number (PIN):

M83513/08 - A 01 1/

- M83513/08 -: Specification sheet number
- A: Insert arrangement (see figure 2)
  - A = 9
  - B = 15
  - C = 21
  - D = 25
  - E = 31
  - F = 37
  - G = 51
- 01 1/: Wire type
  - 01 = M22759/11-26-9, 18 inches long 2/
  - 02 = M22759/11-26-9, 36 inches long 2/
  - 03 = M22759/11-26-( ), 18 inches long 2/ 3/
  - 04 = M22759/11-26-( ), 36 inches long 2/ 3/
  - 05 = A-A-59551, type S, 25 AWG, except shall be gold plated 10 microinches; 0.5 inch long 4/ 5/
  - 06 = A-A-59551, type S, 25 AWG, except shall be gold plated 10 microinches; 1.0 inch long 4/ 5/
  - 07 = A-A-59551, type S, 25 AWG, tin plated 100 microinches; 0.5 inch long 4/ 5/ 6/
  - 08 = A-A-59551, type S, 25 AWG, tin plated 100 microinches; 1.0 inch long 4/ 5/ 6/
  - 09 = M22759/33-26-9, 18 inches long 2/
  - 10 = M22759/33-26-9, 36 inches long 2/
  - 11 = M22759/33-26-( ), 18 inches long 2/ 3/
  - 12 = M22759/33-26-( ), 36 inches long 2/ 3/
  - 13 = M22759/11-26-9, 72 inches long 2/
  - 14 = M22759/11-26-( ), 72 inches long 2/
  - 15 = M22759/33-26-9, 72 inches long 2/
  - 16 = M22759/33-26-( ), 72 inches long 2/
  - 17 = 04035-26A-9, 18 inches long 2/
  - 18 = 04035-26A-9, 36 inches long 2/
  - 19 = 04035-26A-9, 72 inches long 2/
  - 20 = 04035-26A-( ), 18 inches long 2/ 3/
  - 21 = 04035-26A-( ), 36 inches long 2/ 3/
  - 22 = 04035-26A-( ), 72 inches long 2/ 3/

1/ These connectors have leads attached of which wire type, wire size, wire color, and lead length are specified in PIN.

2/ Lead length tolerance +1.0, -0.0 inch.

3/ Color coding in accordance with MIL-STD-681, system I, except the appropriate color code shall be the individual contact cavity number minus 1 for contact positions 1 through 10, repeat this color sequence for contact positions 11 through 20, etc. For example:

Pin number	Identification
4	3
9	8
21	0
31	0
47	6

4/ Lead length tolerance +0.2, -0.0 inch.

5/ Contact and wire may be welded or a single piece design.

6/ Pure tin. The use of pure tin is prohibited. Tin content used in connector materials shall not exceed 97 percent, and an alloy material shall be chosen to inhibit the growth of tin whiskers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-DTL-83513, this document references the following:

A-A-59551
MIL-DTL-83513/5
MIL-DTL-83513/7
MIL-DTL-83513/9
MIL-STD-681

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4660-000)

Review activities:
Army - AT, MI
Navy - AS, CG, MC, SH
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:28Z
Check the source to verify that this is the current version before use.