INCH-POUND

MIL-DTL-83528/6G
05 September 2023
SUPERSEDING
MIL-DTL-83528/6F
27 July 2018


DETAIL SPECIFICATION SHEET

GASKETING MATERIAL, CONDUCTIVE, SHIELDING GASKET, ELECTRONIC, ELASTOMER, EMI/RFI, RECTANGULAR, D-CROSS SECTION

Inactive for new design after 05 September 2023. No superseding specification.

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall
consist of this specification sheet and the latest issue of MIL-DTL-83528.



NOTE:
1. Dimensions are in inches; metric equivalents are given in parenthesis and are for general information only.
2. Tolerance on flash shall be ± .008 (0.20 mm) on the extension and ± .005 (0.13 mm) on the thickness.

FIGURE 1. EMI/RFI gasket, elastomer, rectangular with “D” cross section.

AMSC N/A

FSC 5999

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:39Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and interface: See figure 1 and table I.

Material: Type A, B, C, D, E, F, H, J, K, L, or M.

Part or Identifying Number (PIN): See table I.

Supersession information: See table II.

TABLE I. Dimensions.

PIN 1/ M83528/006X	W 2/		L 2/		Cross Section Area (cm^2) 3/
	Min	Max	Min	Max	
001	.285 (7.24)	.295 (7.49)	.983 (24.97)	.993 (25.22)	.057
002	.485 (12.32)	.495 (12.57)	.983 (24.97)	.993 (25.22)	.057
003	.619 (15.72)	.629 (15.98)	1.243 (31.57)	1.253 (31.83)	.057
004	.815 (20.70)	.845 (21.46)	2.985 (75.82)	3.015 (76.58)	.057
005	1.325 (33.66)	1.355 (34.42)	5.265 (133.73)	5.295 (134.49)	.057

1/ "X" in the PIN shall be replaced by the applicable material type. Complete PIN example: M38528/006A001.
2/ Dimensions are in inches; metric equivalents are given in parenthesis and are for general information only.
3/ For calculation of volume resistivity (for reference only).

TABLE II. Supersession information.

PIN 1/ M83528/006X	Superseded DESC Drawing PIN 85100X 1/
001	001
002	002
003	003

1/ "X" in the PIN indicates the applicable material type.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. This document references MIL-DTL-83528.

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

(Project 5999-2023-008)

Review activities:
Air Force – 19
NSA – NS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:39Z
Check the source to verify that this is the current version before use.