INCH-POUND


MIL-DTL-83528/8G
28 November 2023
SUPERSEDING
MIL-DTL-83528/8F
24 January 2019

DETAIL SPECIFICATION SHEET

GASKETING MATERIAL, CONDUCTIVE, SHIELDING GASKET, ELECTRONIC, ELASTOMER, EMI/RFI, HOLLOW P-STRIP

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the gasketing material described herein shall consist of this specification sheet and the latest issue of MIL-DTL-83528.



NOTE: Length shall be as specified on the purchase order.

FIGURE 1. EMI/RFI gasket, elastomer, and hollow P-strip.

AMSC N/A
FSC 5999

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:40Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and interface: See figure 1 and table I.

Material: Type A, B, C, D, E, F, H, J, K, L, or M.

Part or Identifying Number (PIN): See table I.

Supersession information: See table II.

TABLE I. Dimensions.

PIN 1/ M83528/008X	Nominal dimensions 2/, 3/				Cross section area (cm^2) 4/
	A	B	C	D	
001	.200 (5.08)	.080 (2.03)	.650 (1.65)	.062 (1.57)	.430
002	.250 (6.35)	.125 (3.18)	.250 (6.35)	.062 (1.57)	.359
003	.250 (6.35)	.125 (3.18)	.375 (9.53)	.062 (1.57)	.409
004	.250 (6.35)	.150 (3.96)	.375 (9.53)	.062 (1.57)	.374
005	.312 (7.92)	.187 (4.75)	.563 (14.30)	.062 (1.57)	.585
006	.360 (9.14)	.255 (6.48)	.420 (10.67)	.070 (1.79)	.562
007	.200 (5.08)	.080 (2.03)	.275 (6.99)	.062 (1.57)	.294
008	.250 (6.35)	.125 (3.18)	.625 (15.88)	.062 (1.57)	.509

1/ "X" in the PIN shall be replaced by the applicable material type. Complete PIN example: M38528/008A001.
2/ Dimensions are in inches; metric equivalents are given in parenthesis and are for general information only.
3/ Tolerance shall be as follows:

Dimensions		Tolerance
Under	.101 (2.57)	± .005 (0.13)
	.101 to .200 (2.57 to 5.08)	± .008 (0.20)
	.201 to .300 (5.10 to 7.62)	± .010 (0.25)
	.301 to .500 (7.62 to 12.70)	± .015 (0.38)
Over	.500 (12.70)	± .020 (0.51)

4/ For calculation of volume resistivity (for reference only).

Table II. Supersession information.

PIN 1/ M83528/008X	Superseded DESC Drawing PIN 85107X 1/
001	001
002	002
003	003
004	004
005	005
006	006
007	N/A
008	N/A

1/ "X' in the PIN indicates the applicable material type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:40Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced document. This document references MIL-DTL-83528.

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

(Project 5999-2023-017)

Review activities:
Air Force – 19
NSA – NS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:40Z
Check the source to verify that this is the current version before use.