INCH POUND

MIL-R-83536/27
AMENDMENT 1
15 December 1995

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 6PDT,
LOW LEVEL TO 10 AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY
SEALED, ALL WELDED, AC COIL

This amendment forms a part of MIL-R-83536/27, dated 27 March 1992, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1, side view Delete "SERIAL NUMBER SHALL BE MARKED ON TOP OF RELAYS"

PAGE 5

Contact voltage drop or resistance, delete in its entirety and substitute

"Contact voltage drop and resistance

Initial contact voltage drop 0 100 volt maximum Rated resistive current at 6 V dc or peak ac Relays shall not make or break this load

Initial contact resistance 0 010 ohm maximum 50 mA maximum at 6 V dc or peak ac

High level life (contact voltage drop)

During life 10 percent open circuit voltage maximum

After life 0 125 volt maximum

Intermediate current (contact resistance)

During intermediate current 3 ohms maximum

After intermediate current 0 150 ohm maximum

Low level (contact resistance)

During low level 100 ohms maximum

After low level 0 150 ohm maximum at 100 mA and 28 V dc "

PAGE 8

Vibration (random), line 2 Delete "15 minutes each plane"

Weight Delete "(117 94 g's)" and substitute "(117 94 grams)"

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Air Force - 99
DLA - FS

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5945 0964 19

AMSC N/A
DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.