
INCH-POUND
MIL-PRF-22710/24C
20 November 2018
SUPERSEDING
MIL-PRF-22710/24B
20 April 2001

PERFORMANCE SPECIFICATION SHEET

SWITCHES, ROTARY (PRINTED CIRCUIT), (TOGGLE, BIDIRECTIONAL, SEALED, ILLUMINATED OR NONILLUMINATED), STYLE SRPC24

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-PRF-22710.




INCHES	MM	INCHES	MM	INCHES	MM
0.015	0.38	0.180	4.57	0.350	8.89
0.020	0.51	0.200	5.08	0.480	12.19
0.086	2.18	0.230	5.84	1.050	26.67
0.100	2.54	0.240	6.10	1.155	29.34
0.115	2.92	0.280	7.11	1.385	35.18
0.175	4.45	0.320	8.13	1.460	37.08
				1.610	40.89

FIGURE 1. Style SRPC24 switch and panel cutout and installation data.

AMSC N/A

FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.




INCHES	MM
0.015	0.38
0.098	2.49
0.105	2.67
0.170	4.32
0.370	9.40
0.500	12.70
1.175	29.85
1.385	35.18

NOTES
1. Dimensions are in inches. Metric equivalents are for general information only.
2. Unless otherwise specified, tolerances are ± .010 (.25 mm).
3. Applicable to illuminated switches only. Allowance for lighting terminals for externally replaceable lamps, when internal lighting is specified.

FIGURE 1. Style SRPC24 switch and panel cutout and installation data - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.




INCHES	MM	INCHES	MM
0.015	0.38	0.240	6.10
0.031	0.79	0.370	9.40
0.055	1.40	0.480	12.19
0.100	2.54	1.180	29.97
0.102	2.59	1.385	35.18
0.120	3.05	1.625	41.28

NOTES
1. Dimensions are in inches. Metric equivalents are for general information only.
2. Unless otherwise specified, tolerances are ± .005 (.13 mm) for three place decimals and ±.02 (.5 mm) for two place decimals.

FIGURE 2. Panel seal gasket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based on 1 inch = 25.4 mm.

FIGURE 3. RFI shielded switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figures 1, 2 and 3.

Construction: D.

Angle of Throw: 36°

Temperature-life characteristic: B, except -55° low temperature for all switches and +71° C for lighted switches.

TABLE I. Electrical test load.

Test of condition	Resistive	
At atmospheric pressure	0.125 A	28 V dc and ac, 60 Hz
At reduced barometric pressure	0.125 A	28 V dc and ac, 60 Hz
Life (low level)	10 mA	30 mV

Vibration grade: 3 (15g, 10 - 2,000 Hz).

Shock types: M (100 g's) and H (high-impact). Methods I and II are applicable.

Altitude rating: C (70,000 feet).

Terminal design: See figure 3 and table III.

Contact resistance:
Initial: 50 milliohms, maximum.
Following life (rotational): 70 milliohms, maximum.

Luminace: Illuminated switches only.

Moisture resistance: MIL-STD-202-103, test condition A, with polarization voltage.

TABLE II. Photometric brightness.

Lamp	Switch filter	Brightness	Rating	
			Volts	Ampere
M6363/6 or equivalent	Clear	2.0 ± 1.0 foot-lamberts	5	0.115
	Red	1.0 ± 0.5 foot-lamberts	5	0.115
	Amber	2.0 ± 1.0 foot-lamberts	5	0.115

1/ MS6363/6 details are found in MIL-DTL-6363/6.

Operating force (tangential): 12 ounces minimum
36 ounces maximum


Seal: Method II, when specified in table I.

Dielectric withstanding voltage: 750 volts rms at atmospheric pressure
250 volts rms at reduced barometric pressure, test condition C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.

EMI/RFI shielding: Shielded switches (see table III) are intended for use in equipment required to meet the radiated (R) portions of MIL-STD-461. The conductive coating and conductive gasket shall be as shown in figure 3. When the switch is mounted facing outward to an electrically conductive panel, the resistance shall be measured between the RFI shielding on the switch and the mounting panel. The resistance shall not exceed 1 ohm.

Military part number: M22710/24- (dash number from table III).



Truth table 1/ Straight decimal	
Dial Marking	Common c Conn to:
0	0
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9

INCHES	MM
.100	2.54
.580	14.73
1.050	26.67
1.146	29.11


1/ Code explanation: Dial reads 0 - Common C active with terminal 0 only.
Dial reads 1 - Common C active with terminal 1 only.
Dial reads 2 - Common C active with terminal 2 only.
and so forth.

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are base upon 1 inch = 25.4 mm.

Circuit configuration 1

FIGURE 4. Module and circuit configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.



Truth table 1/ Binary coded decimal				
Dial marking	Common C Conn to:			
	1	2	4	8
0				
1	•			
2		•		
3	•	•		
4			•	
5	•		•	
6		•	•	
7	•	•	•	
8				•
9	•			•

INCHES	MM
.028	.71
.125	3.18
.580	14.73
.923	23.44
.980	24.89
1.050	26.67


1/ Code explanation: Dial reads 0 - All terminals non-active.
Dial reads 1 - Common C active with terminal 1 only.
Dial reads 2 - Common C active with terminal 2 only.
and so forth.

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are base upon 1 inch = 25.4 mm.

Circuit configuration 2

FIGURE 4. Module and circuit configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.



Truth table 1/ Binary coded octal with two commons				
Dial marking	Common X(•) Y(o) Conn to:			
	1	2	4	8
0	o	o	o	o
1	•	o	o	o
2	o	•	o	o
3	•	•	o	o
4	o	o	•	o
5	•	o	•	o
6	o	•	•	o
7	•	•	•	o
8	o	o	o	•
9	•	o	o	•

INCHES	MM
.360	9.14
.980	24.89
1.050	26.67


1/ Code explanation: Dial reads 0 - Common Y active with terminals 1, 2, 4 and 8 while common X is not connected to any terminals.
Dial reads 1 - Common X connected to terminal 1, while common Y is connected to terminals 2, 4 and 8.
Dial reads 2 - Common X connected to terminal 2, while common Y is connected to terminals 1, 4 and 8.
and so forth.

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are base upon 1 inch = 25.4 mm.
3. Where lighting is specified, terminals shall be marked L1, L2.

Circuit configuration 3

FIGURE 4. Module and circuit configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.



Truth table 1/ Binary coded decimal plus compliment								
Dial marking	Common C Conn to:							
	1	2	4	8	$\overline{1}$	$\overline{2}$	$\overline{4}$	$\overline{8}$
0					•	•	•	•
1	•					•	•	•
2		•			•		•	•
3	•	•					•	•
4			•		•	•		•
5	•		•			•		•
6		•	•		•			•
7	•	•	•					•
8				•	•	•	•	
9	•			•		•	•	

INCHES	MM
.250	6.35
.580	14.73
1.050	26.67
1.146	29.11

1/ Code explanation: Dial reads 0 - Common C active with terminals $\overline{1}$, $\overline{2}$, $\overline{4}$ and $\overline{8}$
Dial reads 1 - Common C active with terminals 1, $\overline{2}$, $\overline{4}$ and $\overline{8}$.
Dial reads 2 - Common C active with terminals 2, 1, $\overline{4}$ and $\overline{8}$.
and so forth.

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are base upon 1 inch = 25.4 mm.

Circuit configuration 4

FIGURE 4. Module and circuit configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.

Table III. Part numbers and characteristics.

Part Number M22710/24-	Circuit configuration	Dial		illumination		Special features
		Background	Marking	Color	Location	
001	1	Black Opaque	White Opaque	---	---	---
002	1	Black Opaque	White Opaque	---	---	RFI Shielded
003	1	Black Opaque	White Translucent	Red	Back	---
004	1	Black Opaque	White Translucent	Red	Back	RFI Shielded
005	1	Black Opaque	White Translucent	Clear	Back	---
006	1	Black Opaque	White Translucent	Clear	Back	RFI Shielded
007	2	Black Opaque	White Opaque	---	---	---
008	2	Black Opaque	White Opaque	---	---	RFI Shielded
009	2	Black Opaque	White Translucent	Red	Back	---
010	2	Black Opaque	White Translucent	Red	Back	RFI Shielded
011	2	Black Opaque	White Translucent	Clear	Back	---
012	2	Black Opaque	White Translucent	Clear	Back	RFI Shielded
013	3	Black Opaque	White Opaque	---	---	---
014	3	Black Opaque	White Opaque	---	---	RFI Shielded
015	3	Black Opaque	White Translucent	Red	Back	---
016	3	Black Opaque	White Translucent	Red	Back	RFI Shielded
017	3	Black Opaque	White Translucent	Clear	Back	---
018	3	Black Opaque	White Translucent	Clear	Back	RFI Shielded
019	3	Black Opaque	White Translucent	Amber	Back	---
020	3	Black Opaque	White Translucent	Amber	Back	RFI Shielded
021	4	Black Opaque	White Opaque	---	---	---
022	4	Black Opaque	White Opaque	---	---	RFI Shielded
023	4	Black Opaque	White Translucent	Red	Back	---
024	4	Black Opaque	White Translucent	Red	Back	RFI Shielded
025	4	Black Opaque	White Translucent	Clear	Back	---
026	4	Black Opaque	White Translucent	Clear	Back	RFI Shielded

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.

Reference documents:

MIL-PRF-22710	MIL-STD-202-103
MIL-STD-461	MIL-DTL-6363/6

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy- EC
Air Force - 85
DLA - CC

Preparing Activity:
DLA - CC

(Project 5930-2018-067)

Review activities:
Army - AR. CR4, MI, SM
Navy – MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:34Z
Check the source to verify that this is the current version before use.