MILITARY SPECIFICATION

RECEIVING SET, RADIO AN/ARR-66(*)

This amendment forms a part of Military Specification MIL-R-22737(WEP) dated 15 February 1961 and has been approved by the Bureau of Naval Weapons, Department of the Navy.

Page 1, paragraph 2.1, after "invitation for bids,": Add:

"except the dated document indicated below,"

Page 1, paragraph 2.1, under SPECIFICATIONS Military: Delete "MIL-I-6181 Interference Control Requirements, Aircraft Equipment" and add:

"MIL-I-6181B (29 May 1953)	Interference Limits, Test and Design Requirements, Aircraft Electrical and Electronic Equipment (See 2.2(2))
MIL-M-7793	Meter, Time Totalizing"

Page 2, paragraph 2.1, under STANDARDS Military: Delete:

"MS25245	Connections, Input Power Airborne Electronic Equipment; 28-Volt DC, 115-Volt Single Phase AC, or 115/200 Volt 3-Phase AC, or Combinations"

Page 2, paragraph 2.2: Add:

"(2) Specification MIL-I-6181B is available only from the Bureau of Naval Weapons, Washington 25, D.C. Attention RREN-63."

Page 3: Add:

"3.2.3.4 Totalizing Time Meter - The radio receiver shall include a time totalizing meter conforming to the applicable requirements of Specification MIL-M-7793."

Page 3, paragraph 3.2.4.3: Delete and substitute:

"3.2.4.3 Input Power Connector - The input power connector shall be an Amphenol Type 165-45 or an approved equivalent."

Page 3, paragraph 3.2.6: Delete and substitute:

"3.2.6 Interference Control - The generation of radio interference by the equipment and the vulnerability of the equipment to external interference shall be controlled within the limits of SpecificationMIL-I-6181B dated 29 May 1953. Antenna conducted interference on not more than 9 of the 18 total main receivers first injection frequencies shall not exceed 300 microvolts."

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 20261O-19T13:38Z
Check the source to verify that this is the currentversion before use.

Page 4, paragraph 3.2.10.1: Delete "Curves I and II" and substitute:

"Curve I"

Page 4, paragraph 3.2.12(1) and (2): Delete and substitute:

"(1) AC Power (Three-Phase) 115/200 volt
Operating Voltage Limits 108 to 121 volts
Reduced Performance Voltage Limits 102 to 108 and 121 to 124 volts
Power (3 Phase) 220 VA

(2) DC Power 28 Volts System
Operating Voltage Limits 25 to 29 volts
Reduced Performance Voltage Limits 22 to 25 volts
Power-Receive 0.5 Amp.
Power-Channel Change 7.5 Amps

Page 5, paragraph 3.3.2: Add:

"Six receiver channels (242.1 mc, 246.6 mc, 253.3 mc, 287.1 mc, 322.8 mc and 339.0 mc) may be degraded or unusable due to internally generated interference."

Page 6, paragraph 3.3.9: Delete "within 5%" and substitute:

"within ± 5%"

Page 12, paragraph 4.5, after first sentence: Add:

"The maximum rate of relay cycling should not exceed two messages per second during this test."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:38Z
Check the source to verify that this is the current version before use.