MILITARY SPECIFICATION

TRANSMITTING SET, RADIO AN/ART-36(*)

This amendment forms a part of Military Specification MIL-T-22738(WEP) dated 15 February 1961 and has been approved by the Bureau of Naval Weapons, Department of the Navy.

Page 1, paragraph 2.1, after "invitation for bids,": Add:

"except, the dated document indicated below,"

Page 1, paragraph 2.1, under SPECIFICATIONS Military: Delete "MIL-I-6181 Interference Control Requirements, Aircraft Equipment" and add:

"MIL-I-6181B (29 May 1953)	Interference Limits, Tests and Design Requirements, Aircraft Electrical and Electronic Equipment (See 2.2(2))
MIL-M-7793	Meter, Time Totalizing"

Page 2, paragraph 2.1, under STANDARDS Military: Delete:

"MS25245	Connections, Input Power Airborne Electronic Equipment; 28-Volt DC, 115-Volt Single Phase AC, or 115/200 Volt 3-Phase AC, or Combinations"

Page 2, paragraph 2.2: Add:

"(2) Specification MIL-I-6181B is available only from the Bureau of Naval Weapons, Washington 25, D. C. Attention RREN-63."

Page 3: Add:

"3.2.3.4 Totalizing Time Meter - The Radio Transmitter shall include a time totalizing meter conforming to the applicable requirements of Specification MIL-M-7793."

Page 3, paragraph 3.2.4.3: Delete and substitute:

"3.2.4.3 Input Power Connector - The input power connector shall be an Amphenol Type 165-45 or an approved equivalent."

Page 3, paragraph 3.2.6: Delete and substitute:

"3.2.6 Interference Control - The generation of radio interference by the equipment and the vulnerability of the equipment to external interference shall be controlled within the limits of Specification MIL-I-6181B dated 29 May 1953. These limits shall apply only under steady state conditions of prepared to transmit and transmit modes. Radio interference generated by the equipment when keyed at a 12 cps rate shall not exceed 20 db above Specification MIL-I-6181B steady state limits."

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:38Z
Check the source to verify that this is the current version before use.

Page 4, paragraph 3.2.10.1: Delete "Curves I and II" and substitute:

"Curve I"

Page 4, paragraph 3.2.12(1) and (2): Delete and substitute:

"(1) AC Power (Three-Phase) 115/200 volt
Operating Voltage Limits 108 to 121 volts
Reduced Performance Limits 102 to 108 and 121 to 124 volts
Power (3 Phase) 320 VA

(2) DC Power 28 Volt System
Operating Voltage Limits 25 to 29 volts
Reduced Performance Voltage Limits 22 to 25 volts
Power-Transmit 0.5 Amps.
Power-Channel Change 7.5 Amps.

Page 5, paragraph 3.3.4.4: Delete and substitute:

"3.3.4.4 Transmitter Frequency Linearity - The FSK modulator r-f frequency shall be linear within ±5% of the maximum peak-to-peak deviation of the data signal."

Page 7, paragraph 3.5: Add:

"(4) ID-902/AR Radio Frequency Monitor"

Page 11, paragraph 4.5, after first sentence: Add:

"The maximum rate of relay cycling should not exceed two messages per second during this test."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:38Z
Check the source to verify that this is the current version before use.