INCH-POUND

MIL-W-22759E
SUPPLEMENT 1
31 December 1990

MILITARY SPECIFICATION

WIRE, ELECTRICAL, FLUOROPOLYMER-INSULATED COPPER OR COPPER ALLOY

This supplement forms a part of Military Specification MIL-W-22759E, dated 31 December 1990

SPECIFICATION SHEETS

MIL-W-22759/1 - Wire, Electrical, Fluoropolymer-Insulated, TFE and TFE-Coated-Glass, Silver-Coated Copper Conductor, 600-Volt

MIL-W-22759/2 - Wire, Electrical, Fluoropolymer-Insulated, TFE and TFE-Coated-Glass, Nickel-Coated Copper Conductor, 600-Volt

MIL-W-22759/3 - Wire, Electrical, Fluoropolymer-Insulated, TFE-Glass-TFE, Medium Weight, Nickel-Coated Copper Conductor, 600-Volt

MIL-W-22759/4 - Wire, Electrical, Fluoropolymer-Insulated, TFE-Glass-FEP, Medium Weight, Silver-Coated Copper Conductor, 600-Volt

MIL-W-22759/5 - Wire, Electrical, Fluoropolymer-Insulated, Abrasion Resistant Extruded TFE, Silver-Coated Copper Conductor, 600-Volt

MIL-W-22759/6 - Wire, Electrical, Fluoropolymer-Insulated, Abrasion Resistant Extruded TFE, Nickel-Coated Copper Conductor, 600-Volt

MIL-W-22759/7 - Wire, Electrical, Fluoropolymer-Insulated, Abrasion Resistant Extruded TFE, Medium Weight, Silver-Coated Copper Conductor, 600-Volt

MIL-W-22759/8 - Wire, Electrical, Fluoropolymer-Insulated, Abrasion Resistant Extruded TFE, Medium Weight, Nickel-Coated Copper Conductor, 600-Volt

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:43Z
Check the source to verify that this is the current version before use.

MIL-W-22759/9 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Silver-Coated Copper Conductor, 1,000-Volt

MIL-W-22759/10 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Nickel-Coated Copper Conductor, 1,000-Volt

MIL-W-22759/11 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Silver-Coated Copper Conductor, 600-Volt

MIL-W-22759/12 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Nickel-Coated Copper Conductor, 600-Volt

MIL-W-22759/13 - Wire, Electrical, Fluoropolymer-Insulated, FEP-PVF_2, Medium Weight, Tin-Coated Copper Conductor, 600-Volt

MIL-W-22759/14 - Wire, Electrical, Fluoropolymer-Insulated, FEP-PVF_2, Light Weight, Tin-Coated Copper Conductor, 600-Volt

MIL-W-22759/15 - Wire, Electrical, Fluoropolymer-Insulated, FEP-PVF_2, Light Weight, Silver-Coated High Strength Copper Alloy Conductor, 600-Volt

MIL-W-22759/16 - Wire, Electrical, Fluoropolymer-Insulated, Extruded ETFE, Medium Weight, Tin-Coated Copper Conductor, 600-Volt, 150°C

MIL-W-22759/17 - Wire, Electrical, Fluoropolymer-Insulated, Extruded ETFE, Medium Weight, Silver-Coated High Strength Copper Alloy Conductor, 600-Volt, 150°C

MIL-W-22759/18 - Wire, Electrical, Fluoropolymer-Insulated, Extruded ETFE, Light Weight, Tin-Coated Copper Conductor, 600-Volt, 150°C

MIL-W-22759/19 - Wire, Electrical, Fluoropolymer-Insulated, Extruded ETFE, Light Weight, Silver-Coated High Strength Copper Alloy Conductor, 600-Volt, 150°C

MIL-W-22759/20 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Silver-Coated High Strength Copper Alloy Conductor, 1000-Volt

MIL-W-22759/21 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Nickel-Coated High Strength Copper Alloy Conductor, 1000-Volt

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:43Z
Check the source to verify that this is the current version before use.

MIL-W-22759/22 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Silver-Coated High Strength Copper Alloy Conductor, 600-Volt

MIL-W-22759/23 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Nickel-Coated High Strength Copper Alloy Conductor, 600-Volt

MIL-W-22759/24 through MIL-W-22759/27 - Canceled, 23 April 1980

MIL-W-22759/28 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Polyimide Coated, Silver-Coated Copper Conductor, 600-Volt

MIL-W-22759/29 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Polyimide Coated, Nickel-Coated Copper Conductor, 600-Volt

MIL-W-22759/30 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Polyimide Coated, Silver-Coated High Strength Copper Alloy Conductor, 600-Volt

MIL-W-22759/31 - Wire, Electrical, Fluoropolymer-Insulated, Extruded TFE, Polyimide Coated, Nickel-Coated High Strength Copper Alloy Conductor, 600-Volt

MIL-W-22759/32 - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Lightweight, Tin-Coated Copper, 150°C, 600-Volt

MIL-W-22759/33 - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Lightweight, Silver-Coated High Strength Copper Alloy, 150°C, 600-Volt

MIL-W-22759/34 - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Normal Weight, Tin-Coated Copper, 150°C, 600-Volt

MIL-W-22759/35 - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Normal Weight, Silver-Coated High Strength Copper Alloy, 150°C, 600-Volt

MIL-W-22759/41 - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Normal Weight, Nickel-Coated Copper, 200°C, 600-Volt

MIL-W-22759/42 - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Normal Weight, Nickel-Coated High Strength Copper Alloy, 200°C, 600-Volt

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:43Z
Check the source to verify that this is the current version before use.

MIL-W-22759/43C - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Normal Weight, Silver-Coated Copper, 200°C, 600-Volt

MIL-W-22759/44A - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Light Weight, Silver-Coated Copper, 200°C, 600-Volt

MIL-W-22759/45A - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Light Weight, Nickel-Coated Copper, 200°C, 600-Volt

MIL-W-22759/46A - Wire, Electrical, Fluoropolymer-Insulated, Cross-linked Modified ETFE, Light Weight, Nickel-Coated High Strength Copper Alloy, 200°C, 600-Volt

Preparing Activity:
Navy - AS

Agent:
DLA - IS

(Project 6145-1152)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:43Z
Check the source to verify that this is the current version before use.