
MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR-79/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the crystal unit described herein shall consist of this document and the latest issue of Specification MIL-C-3098.

Pertinent characteristics: 2.9 to 20 MHz; fundamental; noncontrolled; series.



INCHES	MM	INCHES	MM
.002	.05	.150	3.81
.003	.08	.175	4.45
.008	.20	.183	4.65
.010	.25	.192	4.88
.015	.38	.238	6.05
.025	.64	.402	10.21
.030	.76	.435	11.05
.040	1.02	.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. The type designation, frequency, and code designating characters shall be not less than .038 (.97 mm) in height and not less than .027 (.69 mm) in width.
© 4. The pin undercut may be omitted.

© denotes change

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:38Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements.

Requirements	Specified value or condition
Holder	HC-25/U (MIL-H-10056/11)
Dimensions, marking, and configuration	See figure
Frequency range	2.9 to 20 MHz, inclusive
Capacitance, shunt	7 pF, maximum
Frequency tolerance (operating temperature range)	±50 PPM
Equivalent resistance	See table II
Mode of oscillation	Fundamental
Test set, calibration values, and rated drive level	See table III
Operating temperature range	-55° to +105°C, inclusive
Shock (specified pulse):	
Frequency change permitted	±5 PPM
Equivalent resistance change permitted	±10 percent
Vibration: 1/	
Frequency change permitted	±5 PPM
Equivalent resistance change permitted	±10 percent
Temperature run:	
Frequency change permitted	±5 PPM
Equivalent resistance change permitted	±10 percent
Aging:	
Frequency change permitted	5 PPM

1/ Method 204 of MIL-STD-202, test condition A.

TABLE II. Test set, calibration values, and rated drive level.

Government reference standard test set	Band of specified frequencies, inclusive	Calibration values			Rated drive level
		Resistance	Crystal current	Resistor voltage drop	
	MHz	Ohms	mA	Volt	mW
TS-330/TSM	2.9 to 7.5	25	14	---	5.0 ± 1.0
	7.5+ to 10	16	18	---	5.0 ± 1.0
	10+ to 15	13	20	---	5.0 ± 1.0
TS-683/TSM	15+ to 20	12	---	0.24	5.0 ± 1.0

TABLE III. Equivalent resistance.

Frequency range, inclusive	Maximum resistance
MHz	Ohms
2.9 to 7	50
7+ to 10	30
10+ to 15	25
15+ to 20	20

NOTE: NATO guidance type NXT 52.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:38Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 84

Review activities:
Army - EL, MI, MU, SG, SM
Navy - EC
Air Force - 11, 85
DSA - ES

User activities:
Army -
Navy - AS, MC, SH
Air Force - 17, 19

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5955-0408-36)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:38Z
Check the source to verify that this is the current version before use.