INCH-POUND
MIL-PRF-3098/63G
7 January 2010
SUPERSEDING
MIL-PRF-3098/63F
19 December 2003

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR79/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 2.9 MHz to 20 MHz; fundamental; noncontrolled; series resonance.



FIGURE 1. Crystal unit - CR79/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:37Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.435	---	11.05
B	---	.183	---	4.65
C	---	.402	---	10.21
D	.027	.032	0.69	0.81
E	.184	.200	4.67	5.08
F	---	.150	---	3.81
G	---	.530	---	13.46
H	.223	.248	5.66	6.30
J	.015	.025	0.38	0.64
K	.165	.175	4.19	4.45
L	.038	.042	0.97	1.07

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.
4. The pin undercut may be omitted.

FIGURE 1. Crystal unit - CR79/U - Continued.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 2.9 MHz to 20 MHz, inclusive.

Capacitance, shunt: 7.0 pF, maximum.

Frequency tolerances (operating temperature range): ±50 parts per million (ppm).

Equivalent resistance: See table I.

TABLE I. Equivalent resistance.

Frequency range MHz	Maximum resistance Ohms
2.90 to 3.3	150
3.3+ to 3.75	80
3.75+	50

Mode of oscillation: Fundamental.

Operating temperature ranges (noncontrolled): -55°C to +105°C, inclusive.

Rated drive level: 1.0 mW maximum.

Resonance: Series.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:37Z
Check the source to verify that this is the current version before use.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 204 of MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Part or Identifying Number (PIN): CR79/U (followed by specified frequency), see 1.2 of MIL-PRF-3098.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:37Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 99
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC, SH
Air Force - 19, 84

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2009-072)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:37Z
Check the source to verify that this is the current version before use.