MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, LOW-POWER SCHOTTKY TTL,
NAND GATES, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/3000, dated 15 July 1987 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, add the following case outline:

"X C-2A (20 terminal, .350" x .350"), square chip carrier package".

PAGE 2

1.3, Thermal resistance, junction-to-case (Θ_{JC}); delete and substitute:

"Thermal resistance, junction-to-case (Θ_{JC}):
Cases A, B, C, D, 2, and X - - - - - - - - - - - - (See MIL-M-38510, appendix C)

Footnote 2/: Delete in its entirety.

PAGE 3

4.3, lines 3 and 4: Delete "see 4.4.1 through 4.4.4" and substitute "see 4.4.1 through 4.4.5".

4.4, lines 3 and 4: Delete "see 4.4.1 through 4.4.4" and substitute "see 4.4.1 through 4.4.5".

PAGE 4

* TABLE I, low-level input current, I_{IL}, delete in its entirety and substitute as follows:

"

Low-level input current	I_{IL}	V_{CC} = 5.5 V, V_{IL} = 0.4 V	01, 02, 03, 04, 05, 06	-30	-400	µA
			07	-30	-380	
			08	-30	-440	
			09	0	-400	

"

PAGE 5

TABLE III, entry for "Additional electrical subgroups for group C periodic inspections": Delete in its entirety.

TABLE II, group A test requirements, class B devices: Add "10, 11".

4.4.3b: Delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:01Z
Check the source to verify that this is the current version before use.

PAGES 6, 7, AND 8

FIGURE 1, all devices types: Delete "Case 2" and substitue "Cases 2 and X".

PAGES 17 THROUGH 34

TABLE III: Delete heading "Case 2" and substitute heading "Cases 2 and X" on all table III pages.

PAGE 23

* TABLE III, device type 04, I_{CCL}, test number 37, pin 6A: Delete "„" and substitute "5.5 V".

PAGE 25

TABLE III, device type 05, V_{OH}, test numbers 4 through 9, pin 1Y: Delete ditto marks.

TABLE III, device type 05, I_{IL}, test number 42, pin 1C: Delete ditto mark and substitute "0.4 V".

TABLE III, device type 05, I_{IL}, test number 43, pin 1C: Delete "0.4 V" and substitute "5.5 V".

PAGE 33

* TABLE III, device type 09, I_{CCH}, test number 43, pin Y: Delete "GND".

PAGE 34

* TABLE III, device type 09, footnote 2/, circuit A: Delete "-120/-360" and substitute "0/-360".

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1288)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:01Z
Check the source to verify that this is the current version before use.