MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, LOW-POWER SCHOTTKY TTL,
NOR GATES, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/303C, dated 12 November 1987 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

TABLE I, low-level input current, I_{IL}, delete in its entirety and substitute as follows:

"

Low-level input current	I_{IL}	V_{CC} = +5.5 V, V_{IN} = +0.4 V	01	0	-400	µA
			02	-30	-400	
			03	-200	-760	

"

PAGE 5

FIGURE 1, device type 03, pin numbers 1 through 14, A, B, C, and D column: Add "1A", "1B", "1Y", "2Y", "2A", "2B", "GND", "3A", "3B", "3Y", "4Y", "4A", "4B", and "V_{CC}", respectively.

PAGE 9

FIGURE 3, device type 02, upper right-hand corner of burn-in circuit: Delete "3A" and substitute "3B" and "3C" (2 places).

FIGURE 3, device type 03, upper left-hand corner of burn-in circuit, pin connected to R2: Add "V_{CC}"; pins connected to R1's: Add "1Y", "2Y", "3Y", and "4Y".

PAGE 11

TABLE III, device type 01, footnote 2/, I_{IL}, circuit A: Delete "-120/-360" and substitute "0/-360".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1287)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:03Z
Check the source to verify that this is the current version before use.