MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, LOW-POWER SCHOTTKY, TTL, AND-OR-INVERT GATES, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/3048, dated 9 August 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Title: Delete and substitute as printed above.

1.2.3, Case outline: Delete case "X" and substitute case "2". Make this same change wherever case "X" appears.

* 1.3, Absolute maximum ratings, thermal resistance, delete and substitute:

"Thermal resistance, junction-to-case ($\theta_{JC}$):
Cases A, B, C, and D - - - - - - - - - - - - - - - - (See MIL-M-38510, appendix C)
Case 2 - - - - - - - - - - - - - - - - - - - - - - 60°C/W 2/"

* 1.3, Absolute maximum ratings, Junction temperature, following ($T_J$): Add "3/".

* Bottom of page, following footnote 1/, add the following:

"2/ When a thermal resistance value is included in MIL-M-38510, appendix C, it shall supersede the value stated herein.

3/ Maximum junction temperature shall not be exceeded except for allowable short duration burn-in screening conditions per method 5004 of MIL-STD-883."

PAGE 2

* 3.2.3, delete and substitute:

"3.2.3 Schematic circuits. Schematic circuits shall be submitted to the preparing activity prior to inclusion of a manufacturer's device in the specification and shall be submitted to the qualifying activity and agent activity (DESC-ECS) as a prerequisite for qualification. All qualified manufacturers' schematics shall be maintained by the agent activity and will be available upon request."

PAGE 4

3.6, delete and substitute the following:

"3.6 Marking. Marking shall be in accordance with MIL-M-38510."

* TABLE II, MIL-STD-883 test requirements: Delete "Interim" and substitute "Initial".

* 4.2a(1), following Test condition D: Add "or E".

* 4.2b, first line: Delete "Interim" and substitute "Initial".

* 4.2b, second line: Delete "interim" and substitute "initial".


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:03Z
Check the source to verify that this is the current version before use.

PAGE 5

4.2c, delete and substitute the following:

"c. The percent defective allowable (PDA) shall be as specified in MIL-M-38510."

* 4.4.3c(1) following Test condition D: Add "or E".

* 4.4.3c(3): Delete "appendix B of MIL-M-38510 and".

PAGE 8

* NOTES, following note 2, add:

"3. Dashes refer to device type 02."

PAGE 9

* NOTES, following note 4, add:

"5. Dashes refer to device type 02."

— PAGE 13

TABLE III, $t_{PLH}$, test nos. 61 through 70, Max limits column: Add "3/".

TABLE III, footnotes, add:

"3/ $t_{PLH}$ max limit for CKT C is 25 ns."

PAGE 14

6.1: Delete in its entirety.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-0892)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:03Z
Check the source to verify that this is the current version before use.