MIL-H-3697D
29 April 1985
SUPERSEDING
MIL-H-3697C
15 July 1968

MILITARY SPECIFICATION

HARNESS, MAN'S, SLED, SINGLE TRACE TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type of single trace, man harness, fabricated of natural color cotton webbing. The harness is supported on the man by means of an adjustable strap which passes over the shoulders and around the neck. It is provided with a quick-release fastener on the waistband and a single trace of polyester rope 9 feet long with a swivel eye snap hook on each end.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
DDD-L-20	-	Label: For Clothing, Equipage and Tentage (General Use)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal, (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-B-1055 - Barrier Material, Waterproofed, Flexible
PPP-T-76 - Tape, Pressure-Sensitive Adhesive Paper, (For Carton Sealing)

MILITARY

MIL-C-496 - Clips, End, Strap
MIL-W-530 - Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543 - Buckles, Tongueless and Web Strap
MIL-R-3390 - Rings, Dee
MIL-F-11698 - Fastener and Link, Quick Release, Aluminum 1-3/4 Inch
MIL-R-30500 - Rope, Polyester
MIL-S-43770/8- Snap Hooks, Cast Body, Round Eye Swivel

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWING

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-10-35 - Harness Man's, Sled, Single Trace Type

(Copies of documents required by the manufacturer in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are available for reference from libraries. They are also distributed among using technical groups and Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2 and 6.3).

3.2 Materials (see 6.4).

3.2.1 Webbing, cotton. The webbing shall be natural (unbleached), water repellent and mildew-resistant treated, conforming to type IIb, class 1a, 1 inch width and type II, class 1a, 3-3/4 inches in width of MIL-W-530.

3.2.2 Thread, polyester. The thread for all stitching shall be type I or II, class 1, subclass A, size FF, natural of V-T-285.

3.2.3 Rope. The rope shall be natural (undyed) polyester, 3/4 inch circumference conforming to MIL-R-30500.

3.2.4 Buckle, tongueless, 1-bar. The buckle shall conform to type I, style 2, class 1, size 1 inch, construction A of MIL-B-543.

3.2.5 Clips, end, strap. The end clips shall conform to type I, class 1, size 1 of MIL-C-496.

3.2.6 Fastener and link, quick release, aluminum, 1-3/4 inch. The fastener and link shall conform to MIL-F-11698. As an alternate the body and latch assembly shall conform to United States Forgecraft Corporation part No. 44 B 26452 (body, latch) and part No. 44 B 26454 (link), or equal (see 6.5). Prior to use of the "or equal" item, the contractor shall submit to the contracting officer with supporting data for approval.

3.2.7 Rings, dee. The 3-3/4 inch by 1-3/8 inch and the 2-3/4 inch by 1-1/8 inch dee rings shall conform to configuration D class 2 of MIL-R-3390 except that the wire shall be .2253 inch nomial diameter in lieu of .1920 inch.

3.2.8 Snaphooks. The snaphooks shall be 3/4 inch round eye swivel conforming to part number M43770/8-M1Z1 of MIL-S-43770/8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

3.2 Construction. The construction shall conform in all respects to Drawing 2-10-35 and as specified herein.

3.2.1 Stitching. All stitching shall conform to type 301 of FED-STD-751, 6 to 8 stitches per inch.

3.2.1.1 Type 301 stitching. Ends of all stitching, except W-W, shall be backstitched or overstitched 1 inch minimum except where ends are turned under in a hem or held down by other stitching. On W-W- stitching, all ends shall be backstitched or overstitched 1/2 inch minimum. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.2.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch box and W-W-stitching) back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch for box and W-W stitching), continue over the defective area and continue a minimum of 1 inch (1/2 inch for box and W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs the ends of the stitching are not required to be backstitched.

3.3.2 Splicing. A snap hook shall be spliced to each end of the harness trace as shown on Drawing 2-10-35, using a 3-tuck eye splice. The ends of all strands shall be clipped and seared. The seared strand ends shall be not less than 3/8 inch nor more than 5/ inch in length.

3.3.3 Setting of end clips. The webbing shall be inserted the full depth of the clips. The clips shall be attached without cutting the webbing.

3.4 Marking. The identification marking shall conform to type IV, class 5 of DDD-L-20. In addition, the letters "US" and "FRONT" shall be applied in the size characters shown in the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness shall be as specified for class 5 labels. Location for all markings shall be as indicated on the drawing.

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:15Z
Check the source to verify that this is the currentversion before use.

3.5 Workmanship. The finished harness shall conform to the quality and grade of product established by this document. Occurrence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2, 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of harnesses. The sample unit shall be one harness. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects, 6.5 for major and minor combined defects, and 15.0 for total (major, minor A and minor B combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Webbing	Any hole, cut, or tear	X		
	Frayed or scalloped edges, not firmly or tightly woven	X		
	Needle chews:			
	- up to 1/8 inch in length		X	
	- more than 1/8 inch in length	X		
	Slub, broken end or pick		X	
Hardware (general)	Broken or malformed failing to serve intended purpose, corroded area, burr, or sharp edge	X		
	Finish omitted, partially omitted or not as specified			
	- On brass or aluminum components		X	
	- On steel components	X		
	Not assembled as specified (unless otherwise classified herein)	X		
	Not specified type, size, or style	X		
Open seams	1/2 inch or less		X	
	More than 1/2 inch	X		
	NOTE: A seam shall be classified open when one or more stitches joining a seam are broken or when two or more continuous skipped or runoff stitches occur.			
Runoffs (see open seams)				
Seam and stitch type	Wrong seam or stitch type	X		
Stitch type	Wrong stitch type.	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Stitches per inch	One stitch less than minimum specified			X
	Two or more stitches less than minimum specified		X	
	One or more stitches in excess of maximum specified			X
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams or heavy places, or in turning heavy corners shall be classified as follows: (a) Within a minor A defect classification - Minor B defect (b) Within the minor B defect classification - No defect			
Stitching margin	Not as specified		X	
Stitching ends	Not backstitched as specified, except where ends are turned under in a hem or held down by other stitching		X	
	Less than three tying, overlapping, or backstitching in cross box stitching or W-W stitching (when performed on automatic machine)		X	
Thread breaks	On stitching other than W-W stitching, overstitched less than 1 inch in each direction beyond defective stitching area			X
	On W-W stitching, overstitched less than 1/2 inch in each direction beyond the defective stitching area			X
	NOTE: Thread breaks not backstitched shall be classified as open seams			

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Components and assembly	Any required component or part of harness omitted	X		
	Any required row of stitching omitted, except on W-W or box stitching	X		
	W-W or box stitching incomplete: - one row of stitching omitted		X	
	- two or more rows of stitching omitted	X		
	W-W or box stitching less than specified length by more than 1/8 inch			X
	Turned under portion of folded ends, keeper and adjusting straps not caught in all required stitching		X	
Harness assembly	Webbing not continuous, i.e., spliced	X		
Ends of harness	Folded ends finished on outside		X	
Keeper, reinforcement	Misplaced, i.e., set on outside of waistband instead of inside		X	
Adjusting straps A and B	Attached end of either strap uneven with lower edge of body by 1/8 inch or more			X
	Straps misplaced, i.e., strap B (with clip on free end) attached to outer end of body		X	
	One or both straps set to inside of waistband instead of outside		X	
	Buckle on adjusting strap A reversed, failing to hold adjusting strap B assembly	X		
	End clip on adjusting strap B improperly clinched, i.e., webbing not flat at point of insertion into clip			X
Marking	Omitted, illegible, incorrect, misplaced, or size of characters not as specified.			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Snap hooks	Spring portion of snap hook loose or defective causing spring to jam or to remain in an open position	X		
Cleanness	Grease or oil stains clearly noticeable; thread ends not trimmed throughout			X

4.4.3 End item dimensional examination. The end item shall be examined for defects listed in table II. The lot size shall be expressed in units of harnesses. The sample unit shall be one harness. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

TABLE II. End item dimensional defects

Examine	Defect
Dimensions, overall	Smaller than nominal dimension, less applicable minus tolerance indicated on drawing Larger than nominal dimension and applicable plus tolerance
All dimensions other than overall	Not within the specified tolerances

4.4.4 End item functional examination. The end item shall be examined for functional defects listed in table III. The lot size shall be expressed in units of harnesses. The sample unit shall be one harness. The inspection level shall be III and the AQL, expressed in terms of defects per hundred units, shall be 0.10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

TABLE III. End item functional defects

Examine	Defect
Fastener, quick release and link snap, quick release	Any defect of latch, body of fastener, or body of link resulting in failure of quick release action Ends of latch pin or end of plugs on spring housing not peened. Plug on ends of spring housing omitted or loose Link on harness reversed, i.e., set to body with offset in link facing outside instead of inside of harness Fastener on harness reversed, i.e., set to body with latch portion facing inside instead of outside of harness NOTE: Each quick release fastener and link in the sample harnesses selected for inspection shall be examined thoroughly to see that: (a) Latch section of the fastener functions properly (b) Latch snaps firmly in a closed position and remains closed Hook portion of latch fails to engage link securely Latch fails to release link quickly when pulled to the open position NOTE: The quick release fastener shall be tested on the link to determine whether quick release device functions properly

4.4.5 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:15Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of component such as incomplete closure of container flap, loose strapping, inadequate stapling, improper taping Bulged or distorted container
Content	Number of bundles per shipping container is more or less than required

4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:15Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each harness shall be laid flat, with the quick release fastener secured, and placed on top of the waistband. The adjusting straps shall then be positioned along the length of the waistband. The harness trace shall be folded in half, with the snap hooks at one end, and then coiled in approximately 6 inch coils. The coiled harness trace shall be securely tied with cotton twine, placed on the waistband, and the snap hooks fastened to the small dee ring. The waistband shall be folded in thirds with the first fold made by bringing the small dee ring end over on top of the quick release fastener and the final fold made by superimposing the opposite wider end over the first fold. The folded harness shall form a compact bundle measuring approximately 10 inches in length by 4 inches in width by 2-1/2 inches in depth. The bundle shall be securely tied with cotton tape or twine and completely wrapped in waterproof barrier material conforming to class C-1 of PPP-B-1055. The warp shall be secured with 2 inch minimum width water-resistant pressure-sensitive paper tape conforming to PPP-T-76.

5.1.2 Commercial. The harnesses shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing. Forty-eight harnesses, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style FOL-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A bundles shall be packed flat two in length, four in width and six in depth within a shipping container. The inside dimensions of each shipping container shall approximate 20-1/2 inches in length, 16-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5.

5.2.2 Level B packing. Forty-eight harnesses, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style OSC-L (2-inch minimum overlap), type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A bundles shall be packed flat two in length, four in width, and six in depth within a shipping container. The inside dimensions of each shipping container shall approximate 20-1/2 inches in length, 16-1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Harnesses preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), harnesses packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The man-harness is used for manpulling a toboggan or sled over snow-covered terrain inaccessible by motor vehicle transportation. The load is pulled from the waist and a dee ring is located on both the front and back of the waistband of the harness to permit pulling in tandem when desired.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, name, and date of this document.
b. When a first article sample is required (see 3.1, 4.3, and 6.3).
c. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).
d. When weather-resistant grade shipping containers are required for level B packing (see 5.2.2.1).
e. When palletization is required (see 5.3).

6.3 First article. When a first article is required it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The first article should consist of one completed harness. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:15Z
Check the source to verify that this is the current version before use.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.5 Source of supply. A source of supply for alternate acceptable body and latch assembly, and link is the United States Forgecraft Corporation, Division of ISC Industries, Inc., P.O. Box 387, Fort Smith, Arkansas 7201.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 11, 45, 82
DLA - CT

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8465-0901

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-36977	HARNESS, MAN'S, SLED, SINGLE TRACE TYPE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:15Z
Check the source to verify that this is the current version before use.