INCH-POUND

MIL-C-48617A (AR)
AMENDMENT 2
31 October 1996
SUPERSEDING
AMENDMENT 1
28 March 1986

MILITARY SPECIFICATION

CARTRIDGE, 20MM, HIGH EXPLOSIVE, INCENDIARY
M56A4 LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-48617A (AR), dated 24 October 1983, and is approved for use by all the Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Make the following changes:

Line 5, Delete “US ARMY Armament Research and Development Command (ARRACOM)” and substitute “US Army Armament Research Development and Engineering Center (ARDEC)”.

Inspection Equipment Drawings, 11075284, Delete “Resistant” and substitute “Resistance”.

* Inspection Equipment Drawings, Add “10534010 - Waterproofness Testing Apparatus”.

PAGE 3

* 2.1.2, Under Publications, Add “SCATP-7.62 - Ammunition Ballistic Acceptance Test Methods, Test Procedures for 7.62MM Cartridges”.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

PAGE 4

* 3.5.1c., Delete in its entirety and substitute the following:

"c. Waterproofness. The cartridge shall not release more than one bubble of air from the mouth of the case when subject to a pressure differential of 7.5 psi for 30 seconds.".

4.3.1, Make the following changes:

Cartridges, Under Quantity, Delete "680´and substitute "650".

Packaging, Under Part Description, Add "(Containers)" after packaging.

PAGE 6

Table I, Delete in its entirety and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Cartridge and Components	1 OF 1	SEE BELOW
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Charged Body, Projectile (Dwg. 11075863)			
	Examination defects	125 ACC-0 REJ-1	3.2 3.7	4.4.2.1
	Projectile Assembly (Dwg. 11075862)			
	Examination for defects	125 ACC-0 REJ-1	3.2 3.7	4.4.2.2
	Cartridge (Dwg. 11075861)			
	Examination for defects	650 ACC-0 REJ-1	3.2 3.7	4.4.2.3
	Test Requirements	650 ACC-0	3.2	4.4.2.4
	Packaging			
	Examination for defects	7	3.1a	4.4.4/5.1
	Primed Cartridge Case 1/			
	Electrical resistance of primed case	650 ACC-0 REJ-1	3.4	4.5.4

NOTES:
1/ Test shall be performed on primed cartridges subsequent to primer crimping and waterproofing. Results of test shall be submitted with First Article Quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

PAGE 7

4.4.2, Make the following changes:

Delete paragraph c. in its entirety and substitute the following:

"c. Primed cartridge cases. Each primed cartridge case shall be tested for electrical resistance subsequent to primer crimping and waterproofing in accordance with paragraph 4.5.4. Primed cases which fail to meet the requirement of paragraph 3.4 shall be removed.".

Add the following paragraph:

"d. Charged body projectile. Each charged body projectile shall be visually inspected for incendiary pellet (prior to consolidation of high explosive charge). Projectiles missing pellets shall be removed.".

PAGE 8

4.4.2.1, Delete "101. Incendiary pellet missing (prior to high explosive charge), 100%, 3.2, Visual".

PAGE 9

4.4.2.2, Minor 202, Add "1/" under Paragraph Reference/Inspection Method.

PAGE 12

4.4.2.4, Make the following changes:

* Test Requirements, Functioning, (1) c., Delete in its entirety and substitute "c. Waterproofness, 23, 3.5.1.c, 4.4.3.5c/4.5.5.2".

Test Requirements, Static, c. Propellant Contamination, Under AQL or 100% column delete "0-1" and substitute "Acc-0, Rej-1".

Test Requirements, Static, d. Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

PAGE 15

4.4.3.2, Make the following changes:

Column heading, Delete “REF” and substitute “REJ”.

Defect 3, Under REJ column, delete “16 and substitute “21”.

PAGE 16

* 4.4.3.5c., Delete in its entirety and substitute the following:

“c. Waterproofness. Failure of two or more of the sample cartridges to comply with the specified waterproofness requirement shall cause rejection of the lot. If one cartridge of the sample fails to comply, a second sample of 23 cartridges shall be tested. The lot shall be rejected if two or more of the combined samples fail to comply with the waterproofness requirement.”.

PAGE 17

4.5.3, Delete “Primed cartridge cases may be used for the electrical resistance test specified in 4.5.4.2”.

4.5.4, Delete “Electrical resistance.” and substitute “Electrical resistance of primed case. The primed case shall be tested for the applicable requirement using government approved equipment and circuitry specified on Dwg. 11075284 to measure the resistance of the primer.”.

4.5.4.1, Delete in its entirety.

PAGE 18

4.5.4.2, Delete in its entirety.

* 4.5.5.1, Delete “and waterproofness” from title”.

* Add the following paragraph:

“4.5.5.2 Waterproofness. The method of test shall be as specified in SCATP-7.62. The equipment required to conduct this test is specified on drawing 10534010. The container shall be evacuated to a pressure of 7.5 psi below atmosphere, and held at that pressure for 30 seconds.”

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

PAGE 19

6.3, Delete in its entirety and substitute the following:

"6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSTA-AR-QAC-C, Picatinny Arsenal, NJ 07806-5000.".

PAGE 20

6.4, Delete in its entirety and substitute the following:

"6.4 Submission of test data. In addition to the normal distribution of records, when the cartridge is procured by AMCCOM, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commander, ARDEC, ATTN: AMSTA-AR-QAC-C and AMSTA-AR-CCL-CE, Picatinny Arsenal, NJ 07806-5000.".

6.5, Delete in its entirety and substitute the following:

"6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, U.S. Army Armament Research and Development Command (ARRADCOM) or U.S. Army Armament Research and Development Center (ARDC) drawings. Technical data originally prepared by these activities are not under the cognizance of ARDEC.".

PAGE 21

* 6.12, Make the following changes:

Line 1, Delete ", except those from the waterproofness test,".

Line 19, Delete "Misfire(s) occurring in the waterproofness test shall be handled in accordance with AMCR 715-505, Volume 8.".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-0160)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.