MIL-F-48706A(AR)
20 May 1983
SUPERSEDING
MIL-F-48706(AR)
1 August 1978

MILITARY SPECIFICATION

FUZE, PROXIMITY, ARTILLERY: M732
(Loading, Assembling, and Packing)

This specification is approved for use by USA Armament Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This military specification covers a fuze designated as FUZE, PROXIMITY, ARTILLERY: M732 for use in 4.2-inch mortar, 105mm howitzer, 155mm howitzer, 175mm gun, and 8-inch howitzer.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550 -- Ammunition and Special Weapons, General Specification for
MIL-F-50596 -- FUZE, PROXIMITY, ARTILLERY: M732 (less Booster Cup Assembly)
MIL-Q-50829 -- General Quality Assurance Provisions for Proximity Fuzes and Related Components

STANDARDS

Military

MIL-STD-105 -- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167 -- Ammunition Data Card
MIL-STD-1168 -- Lot Numbering of Ammunition

DRAWINGS

USA, Harry Diamond Laboratories (FSCM 19202)

TDPL 11716451 -- FUZE, PROXIMITY, ARTILLERY: M732 (Loaded)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, ATTN: DRSMC-TST-S, Dover, NJ, 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

AMCR-385-224 (RDM7-224) -- AMC Safety Manual

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or requests for proposal shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 171-190 -- Department of Transportation Rules and Regulations for the Transportation of Hazardous Materials

(Requests for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20402)

3. REQUIREMENTS

3.1 Design and construction. Design and construction shall be in accordance with HDL Dwg. 11716451.

3.1.1 Material. Material shall be in accordance with applicable drawings.

3.1.2 Booster. The booster cup assembly shall be as specified in HDL Dwg. 11716740.

3.2 Ballistic requirements. The loaded fuze shall function as specified in paragaph 4.3.6.

3.3 Workmanship. All parts shall be manufactured and finished in a thoroughly workmanlike manner to insure satisfactory functioning and durability. All parts shall be free from chips, dirt, rust, grease, burrs, corrosion, and other foreign material. The cleaning methods used shall not be injurious to any parts, cause corrosion, or other damage to any part of the assembly, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE SYSTEM

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Contractor quality assurance system. The contractor shall provide and maintain an adequate quality system in compliance with MIL-Q-50829.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.2 Government verification. All quality assurance operations performed by the contractor will be subject to Government verification in compliance with MIL-Q-50829.

4.3 Quality conformance inspection. Inspection shall be as specified in MIL-A-2550 and in this document.

4.3.1 Lot formation. The loaded lot shall be the same size as the lot of fuzes (less booster cup assembly).

4.3.2 Sampling. Sampling for Classification of Defects shall be in accordance with MIL-STD-105 and this document. Unless otherwise specified, inspection level II shall apply. The sample size for ballistic tests is specified in paragraph 4.3.6.

4.3.3 Lot acceptance. Lots shall be accepted on the basis of Classification of Defects (4.3.5), Ballistic tests (4.3.6), and Material and Component Certifications (4.3.7). The contractor shall notifiy the Government QA representative prior to proceeding with inspection for Classification of Defects (4.3.5).

4.3.4 Data recording. A written record of the inspection for Classification of Defects shall be made, but only the defect summary need be supplied to the Government. This summary shall be forwarded to the designated Government Agency within two working days after the Government acceptance of the lot.

4.3.5 Classification of defects. The fuze components, fuze assembly, and packing shall be inspected by using the Classification of Defects and applicable drawings. Any of the defect characteristics may be checked on a higher assembly than is indicated in the Classification, if desired by the contractor, but in no case shall be checked on a lower assembly level.

4.3.5.1 FUZE, PROXIMITY: artillery, M732 (Loaded) (11716451).

Categories	Defects	AQL	Method of Inspection
Major			
101	Booster cushion missing	0.15	X-Ray (Class II Film)
102	Booster pellet missing	0.15	X-Ray (Class II Film)
103	Seating shoulder to aft end exceeds max. dim.	0.15	Gage
104	Threads damaged 2.000 - 12 UNS - 1A max.	0.15	Gage
105	Booster cup not seated flush or below aft end of fuze sleeve	0.15	Gage
Minor			
201	Booster cup improperly sealed	0.65	Visual
202	Set line in improper position for shipping	0.65	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.5.2 Box, ammo, metal for artillery type and rocket fuzes (8864492)

Categories	Defects	AQL	Method of Inspection
Minor			
201	Dessicant bag missing	1.5	Visual
202	Marking omitted or illegible	1.5	Visual
203	Cuts or wrinkles in rubber gasket	1.0	Visual
204	Sealing edge of box damaged	1.0	Visual
205	Packing material missing	1.0	Visual
206	Seal leaking (sample size of 20)	2.5	DS-1
207	Loaded box weight incorrect (fuze missing)	1.0	Scale
208	Contents loose	1.0	DS-2

4.3.5.3 Box, wirebound, packing ammunition for artillery type or rocket fuzes (8861213)

Categories	Defects	AQL	Method of Inspection
Minor			
201	Marking omitted or illegible	0.65	Visual
202	Seal missing	0.65	Visual
203	Box broken, board loose or protruding nail	0.65	Visual/Manual
204	Contents loose	0.65	Manual

4.3.5.4 Palletizing for M732 fuze (11730165)

Categories	Defects	AQL	Method of Inspection
Minor			
201	Box missing	2.5	Visual
202	Strapping loose	2.5	Visual/Manual
203	Marking misleading or unidentifiable	2.5	Visual

4.3.5.5 Defect standards.

DS-1 -- The maximum permissible air leakage from the loaded ammunition box (P/N 8864492) shall be 0.4 atmospheric cc per second when a 3.0 psi gage minimum external vacuum is applied.

DS-2 -- When manually shaken, the package shall not rattle or give other indication of looseness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.6 Ballistic tests. The ballistic sample tests shall be performed by the Government at a Government proving ground. A sample of 16 loaded fuzes shall be set for a flight time permitting proximity function, and fired in the 155mm Howizter Gun/Zone 5 at ambient temperature. The acceptance criteria shall be acc 2/rej 3, with duds considered rejects and proximity or impact functions considered acceptable. After three consecutive lots have been accepted, a reduced sampling plan of 8 loaded fuzes with an acceptance criteria of acc 1/rej 2 shall be implemented. If a fuze lot fails on the reduced sampling plan, the initial sampling plan shall be used until three consecutive lots have been accepted.

5. PREPARATION FOR DELIVERY

5.1 Packing, packaging, preservation, and marking. The loaded fuze assembly (11716451) shall be packaged eight to a metal ammunition can in the non-propagation package described in drawing 8864492. The desiccant container (8888050) specified on drawing 8864492 is not required. The desiccant bag (MIL-D-3464) shall be replaced or reactivated in accordance with the manufacturer's instructions on the bag. For overseas shipment, use a wirebound box (8861213).

5.1.1 Unitization. The wirebound boxes (8861213) shall be packaged in accordance with unitization procedures for boxed ammunition and components on 4-way entry pallets (1948-4116).

6. NOTES

6.1 Ordering information.

6.1.1 Documents. Procurement documents shall specify the title, number, and date of this specification.

6.1.2 Data requirements. The following data are required by this specification to be furnished to the Government and should be entered on DD Form 1423 for each contract.

Paragraph	Data Requirements	Applicable DID
4.1.1	Contractor-furnished designs (MIL-Q-50829, 3.6.1)	DI-R-1713
4.3.4	Defect summary	DI-R-1721
5.2	Ammunition data cards	DI-L-1410

6.1.3 Government furnished material. FUZE, PROXIMITY, ARTILLERY: M732 (less Booster Cup Assembly) Drawing 11716452 will be supplied GFM to the Government loading plant. The metal ammunition boxes packaged in accordance with (8864492) containing the GFM fuzes (11716452) are GFM to the loading plant and are to be reused in preparation for delivery in accordance with paragraph 5 (MIL-F-48706A) in TDPL 11716451.

Preparing activity
Army - AR

Project No. 1390-A422

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.