
INCH-POUND
MIL-PRF-49137/5D
10 October 2014
SUPERSEDING
MIL-PRF-49137/5C
19 February 2009

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM, POLAR, MOLDED, NONHERMETICALLY SEALED, STYLE CX05

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-49137.



CIRCUIT DIAGRAM

Dimensions		
Case size	Diameter D ±.015 (0.38)	Length L ±.020 (0.51)
A	.085 (2.16)	.250 (6.35)
B	.100 (2.54)	.280 (7.11)
C	.170 (4.32)	.335 (8.51)
D	.170 (4.32)	.410 (10.41)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.

TABLE I. Style CX05 characteristics.

Part or identifying number (PIN) 1/	DC rated voltage (+85°C)	Capacitance (nominal)	DC leakage (max) +25°C	Dissipation factor	Case size
	Volts	µF	µA	%	
CX05D475-	6	4.7	1.0	6	A
CX05D156-	6	15	1.0	8	B
CX05D336-	6	33	1.5	8	C
CX05D476-	6	47	3.0	8	D
CX05F335-	10	3.3	1.0	6	A
CX05F106-	10	10	1.0	8	B
CX05F226-	10	22	1.5	8	C
CX05F276-	10	27	2.0	8	D
CX05F336-	10	33	3.0	8	D
CX05F396-	10	39	5.0	8	D
CX05F476-	10	47	5.0	8	D
CX05H225-	15	2.2	1.0	6	A
CX05H685-	15	6.8	1.0	6	B
CX05H156-	15	15	1.5	8	C
CX05H226-	15	22	3.0	8	D
CX05H336-	15	33	5.0	8	D
CX05J155-	20	1.5	1.0	6	A
CX05J475-	20	4.7	1.0	6	B
CX05J126-	20	12	1.0	8	D
CX05J156-	20	15	3.0	8	D
CX05K105-	25	1.0	1.0	4	A
CX05K225-	25	2.2	1.0	6	B
CX05K335-	25	3.3	1.0	6	B
CX05K685-	25	6.8	1.5	6	C
CX05K106-	25	10	1.5	8	C
CX05M334-	35	0.33	1.0	4	A
CX05M474-	35	0.47	1.0	4	A
CX05M155-	35	1.5	1.0	6	B
CX05M335-	35	3.3	1.5	6	C
CX05M395-	35	3.9	1.5	6	C
CX05M475-	35	4.7	1.5	6	C
CX05M685-	35	6.8	3.0	6	D
CX05M106-	35	10	5.0	8	D
CX05N104-	50	0.10	1.0	4	A
CX05N154-	50	0.15	1.0	4	A
CX05N224-	50	0.22	1.0	4	A
CX05N334-	50	0.33	1.0	4	B
CX05N474-	50	0.47	1.0	4	B
CX05N684-	50	0.68	1.0	4	B
CX05N105-	50	1.0	1.0	4	B
CX05N155-	50	1.5	1.5	6	C
CX05N225-	50	2.2	1.5	6	C
CX05N335-	50	3.3	2.0	6	D
CX05N475-	50	4.7	3.0	6	D

1/ Complete PIN will include an additional symbol indicating capacitance tolerance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Case material: Molded, epoxy or plastic.

Leads: Solder-coated metal.

DC rated voltage: See table I.

Operating temperature: -55°C to +85°C.

DC leakage (DCL): See table I.

Capacitance (cap.): See table I.

Cap. tolerance: ±10% (K), or ±20% (M).

Dissipation factor (DF): See table I.

Stability at low and high temperature: In accordance with MIL-PRF-49137.

Step 1 (+25°C):	DCL	-	See table I.
	Cap.	-	Within tolerance specified in table I.
	DF	-	See table I.
Step 2 (-55°C):	ΔCap.	-	Within ±15 percent of step 1 measured value.
	DF	-	200 percent of table I.
Step 3 (+25°C):	DCL	-	See table I.
	ΔCap.	-	Within ±10 percent of step 1 measured value.
	DF	-	See table I.
Step 4 (+85°C):	DCL	-	10 times +25°C limit (see table I).
	ΔCap.	-	Within ±15 percent of step 1 measured value.
	DF	-	150 percent of table I.
Step 5 (+25°C):	DCL	-	See table I.
	ΔCap.	-	Within ±10 percent of step 1 measured value.
	DF	-	See table I.

Surge voltage: In accordance with MIL-PRF-49137.

DCL	-	See table I.
ΔCap.	-	Within ±10 percent of initial value.
DF	-	See table I.

Life: In accordance with method 108 of MIL-STD-202.

1,000 hours:

At +25°C:	DCL	-	200 percent of table I.
	ΔCap.	-	Within ±10 percent of initial measured value.
	DF	-	See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.

NOTE: These capacitors are intended to be used only where supplemental moisture protection is provided or for noncritical applications where hermetic moisture protection is not required.

Reference documents. In addition to MIL-PRF-49137, this specification sheet references the following:

MIL-STD-202

Changes from previous issues. The margins of this specification are marked with vertical lines to indicate where changes from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force – 85
DLA – CC

Review activities:
Navy - AS, MC, OS, SH
Air Force - 19

Preparing activity:
Army - CR

Agent
DLA - CC

(Project 5910-2014-019)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.