The documentation and process conversion measures necessary to comply with this amendment shall be completed by 6 August 1999.

INCH POUND

MIL-PRF-19500/168E
AMENDMENT 1
6 May 1999

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, THYRISTORS (CONTROLLED RECTIFIERS), SILICON
TYPES 2N1771A, 2N1772A, 2N1774A, 2N1776A, 2N1777A, JAN, JANTX, AND JANTXV

This amendment forms a part of MIL-PRF-19500/168E, dated 17 October 1998 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

TABLE I, subgroup 3, Gate trigger voltage and current test, delete in its entirety (this page only) and substitute as follows:

"

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Gate trigger voltage and current 2N1771A, 2N1772A 2N1774A, 2N1776A 2N1777A	4221	V_2 = rated V_{DM} ; T_C = + 125°C R_e = 20 Ω maximum, R_L = 140 Ω R_L = 650 Ω	V_{GT2}	0.2		V dc

"

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AV, MI
Air Force - 19, 85, 99

Preparing activity:
DLA - CC

(Project 5961-2147)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:29Z
Check the source to verify that this is the current version before use.