
FED. SUP CLASS
4730



(a) AT OPTION OF MANUFACTURER, BASIC DIMENSION Q MAY BE MADE 1/64 LESS THAN THE DIMENSIONS SPECIFIED, WITH THE PROVISION THAT BASIC DIMENSION Y IS ALSO MADE 1/64 LESS THAN THE DIMENSION SPECIFIED.

MATERIALS: STEEL - BARS, SHAPES, OR FORGINGS.
ALUMINUM ALLOY - BARS, SHAPES, OR FORGINGS.
TITANIUM ALLOY - BARS, SHAPES OR FORGINGS.
CORROSION RESISTANT STEEL - BARS, SHAPES, OR FORGINGS.
SEE PROCUREMENT SPECIFICATION.

FINISH: SEE PROCUREMENT SPECIFICATION.

NO CODE LETTER IN PART NUMBER FOR STEEL.
ADD D AFTER DASH NUMBER FOR ALUMINUM ALLOY (EXCEPT 7075-T73).
ADD J AFTER DASH NUMBER FOR CORROSION RESISTANT STEEL, TYPE 304.
ADD K AFTER DASH NUMBER FOR CORROSION RESISTANT STEEL, TYPE 316.
ADD S AFTER DASH NUMBER FOR CORROSION RESISTANT STEEL, TYPE 347.
ADD T AFTER DASH NUMBER FOR TITANIUM
ADD W AFTER DASH NUMBER FOR 7075-T73.

EXAMPLE OF PART NUMBERS:
AN821-8 - ELBOW, 1/2 TUBING, STEEL
AN821-8D - ELBOW, 1/2 TUBING, ALUMINUM ALLOY (EXCEPT 7075-T73).
AN821-8J - ELBOW, 1/2 TUBING, CORROSION RESISTANT STEEL, TYPE 304.
AN821-8K - ELBOW, 1/2 TUBING, CORROSION RESISTANT STEEL, TYPE 316.
AN821-8S - ELBOW, 1/2 TUBING, CORROSION RESISTANT STEEL, TYPE 347.
AN821-8T - ELBOW, 1/2 TUBING TITANIUM.
AN821-8W - ELBOW, 1/2 TUBING 7075-T73.

BREAK ALL SHARP EDGES AND REMOVE ALL HANGING BURRS AND SLIVERS WHICH MIGHT BECOME DISLODGED UNDER USAGE.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS ±1/64, DECIMALS ±.005, ANGLES ±1/2°.

TITANIUM NOT TO BE USED IN OXYGEN SYSTEMS.

(8) ENTIRE STANDARD REVISED

APPROVED 13 DEC 40 REVISED (7) 16 APRIL 82 (8)

P. A. AIR FORCE - 82 Other Cust ARMY - AV NAVY - AS AIR FORCE - 99	INTERNATIONAL INTEREST	AIR FORCE-NAVY AERONAUTICAL STANDARD ELBOW - FLARED TUBE, 90°	AN821
PROCUREMENT SPECIFICATION MIL-F-5509	SUPERSEDES:		SHEET 1 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT 4730-0481

USER ACTIVITIES

REVIEWER ACTIVITIES DLA-CS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

Source: https://assist.dla.mil -- Downloaded: 202610-26T14:16Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
4730

DASH NO.	TUBING OD	THREAD T (REF)	(a) Q ±3/64 −0	R RAD	U RAD	V	W APPROX	X APPROX	Y ±3/64 −0
AN821-2	1/8	5/16-24UNJF-3A	49/64	5/32		5/16		3/16	51/64
AN821-3	3/16	3/8 -24UNJF-3A	53/64	3/16	1/16	3/8	5/16		55/64
AN821-4	1/4	7/16-20UNJF-3A	57/64	7/32		7/16	3/8	1/4	15/16
AN821-5	5/16	1/2 -20UNJF-3A	61/64	1/4		1/2		5/16	1
AN821-6	3/8	9/16-18UNJF-3A	1- 1/16	9/32		9/16	1/2		1- 1/8
AN821-8	1/2	3/4 -16UNJF-3A	1- 1/4	3/8	3/32	3/4	5/8	7/16	1- 5/16
AN821-10	5/8	7/8 -14UNJF-3A	1-29/64	7/16		7/8	3/4		1-33/64
AN821-12	3/4	1-1/16-12UNJ 3A	1-21/32	17/32		1-1/16	7/8	1/2	1-23/32
AN821-16	1	1-5/16-12UNJ 3A	1-13/16	21/32		1-5/16	1-1/16	5/8	1-15/16
AN821-20	1-1/4	1-5/8 -12UNJ 3A	2- 1/16	13/16	1/8	1-5/8	1-1/4	3/4	2- 3/16
AN821-24	1-1/2	1-7/8 -12UNJ 3A	2-21/64	15/16		1-7/8	1-7/16	7/8	2-41/64
AN821-28	1-3/4	2-1/4 -12UNJ 3A	2-13/16	1- 1/8	3/16	2-1/4	1-3/4	1-1/16	2-15/16
AN821-32	2	2-1/2 -12UNJ 3A	3- 1/16	1- 1/4	1/4	2-9/16	2	1-3/16	3- 1/4

APPROVED 13 DEC 40 REVISED (8) FOR CHANGES SEE PAGES 1 & 2. 5 AUG 83

(8) ENTIRE STANDARD REVISED

P. A. AIR FORCE-82 Other Cust ARMY - AV NAVY - AS AIR FORCE - 99	INTERNATIONAL INTEREST	AIR FORCE-NAVY AERONAUTICAL STANDARD	AN821
PROCUREMENT SPECIFICATION MIL-F-5509	SUPERSEDES:	ELBOW - FLARED TUBE, 90°	SHEET 2 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

USER ACTIVITIES

REVIEWER ACTIVITIES DLA-CS

This military standard is approved for use by all Departments and Agencies of the Department of Defense Selection for all new engineering and design applications and for repetitive use shall be made from this document

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:16Z
Check the source to verify that this is the current version before use.