REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for information on Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.
PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE *(DD-MM-YYYY)*	2. REPORT TYPE	3. DATES COVERED *(From - To)*
30-07-2013	Final	

4. TITLE AND SUBTITLE
Joint Ordnance Test Procedure (JOTP)-070
Identification Marking for Munitions

5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHORS

5d. PROJECT NUMBER

5e. TASK NUMBER

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
PEO AMMO/Product Director for Joint Services
(SFAE-AMO-JS)
1 Buffington Road
Picatinny Arsenal, Picatinny, NJ 07806

8. PERFORMING ORGANIZATION REPORT NUMBER
JOTP-070

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)
Range Infrastructure Division (CSTE-TM)
US Army Test and Evaluation Command
2202 Aberdeen Boulevard
Aberdeen Proving Ground, MD 21005-5001

10. SPONSOR/MONITOR'S ACRONYM(S)

11. SPONSOR/MONITOR'S REPORT NUMBER(S)
Same as item 8

12. DISTRIBUTION/AVAILABILITY STATEMENT

Distribution Statement A. Approved for public release; distribution is unlimited.

13. SUPPLEMENTARY NOTES
Defense Technical Information Center (DTIC), AD No.:

14. ABSTRACT
This document has been developed to address Department of Defense (DoD) identification marking of Munitions with less sensitive explosive fills, so that they can be distinguished from their more sensitive counterparts to enable appropriate application (or selection) of EOD procedures for disposal.

15. SUBJECT TERMS

joint service insensitive munitions identification marking

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	B. ABSTRACT	C. THIS PAGE			19b. TELEPHONE NUMBER *(include area code)*
Unclassified	Unclassified	Unclassified	SAR	10	

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. Z39-18

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE

JOINT ORDNANCE TEST PROCEDURE (JOTP)-070

IDENTIFICATION MARKING FOR MUNITIONS

Joint Services Munition Safety Test Working Group

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

Joint Ordnance Test Procedure (JOTP)-070
Identification Marking for Munitions

DOCUMENT COMPLETION DATE:	**TITLE AND SUBTITLE:**
30 July 2013	Joint Ordnance Test Procedure (JOTP)-070 Identification Marking for Munitions

PREPARING ACTIVITY:	**SPONSORING ACTIVITY:**
PEO AMMO/Product Director for Joint Services (SFAE-AMO-JS) 1 Buffington Road Picatinny Arsenal, Picatinny, NJ 07806	Range Infrastructure Division (CSTE-TM) US Army Test and Evaluation Command 2202 Aberdeen Boulevard Aberdeen Proving Ground, MD 21005-5001

DISTRIBUTION STATEMENT:

Distribution Statement A. Approved for public release; distribution is unlimited.

ABSTRACT:
Joint Ordnance Test Procedure (JOTP)-070 has been developed to address Department of Defense (DOD) identification marking of munitions with less sensitive explosive fills (anything other than TNT, CompB or Tritonal), so that they can be distinguished from their more sensitive counterparts to enable appropriate application (or selection) of EOD procedures for disposal.. The purpose of this document is to establish procedures and standardize the content of the identification marking to be used for munitions containing less sensitive explosive fills. It also specifies marking locations within a munition family.

COORDINATION DRAFT REVIEWED BY:
This document was coordinated with the following Standardization Offices: AR, AS, EA, MC, MI, MR, OS, TE, AF-2, AF-70, and AF-99. In addition, the document was also coordinated with the Joint Weapon Safety Working Group.


ASSIST COORDINATION DATE: 18 April 2013

IMPLEMENTATION PLAN:

1. This JOTP will be referenced in MIL-STD-709, DEPARTMENT OF DEFENSE DESIGN CRITERIA STANDARD, AMMUNITION COLOR CODING.

2. An attempt is being made to include the procedures of this JOTP into STANAG 2953, The Identification of Ammunition – AOP-2. There are differences of opinion between the US and Europe on various aspects of these procedures, but an attempt is being made to harmonize the documents and if possible eventually replace the JOTP with the STANAG. If this is not possible, the U.S. will still ratify the STANAG since the differences are fairly minor, but will not implement it, but will implement the JOTP instead.

APPROVING AUTHORITY:



Director, Land Warfare & Munitions
Office of the Under Secretary of Defense for
Acquisition, Technology and Logistics

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE
JOINT ORDNANCE TEST PROCEDURE

*Joint Ordnance Test Procedure (JOTP)-070 30 July 2013
DTIC AD No.

IDENTIFICATION MARKING FOR MUNITIONS

			Page
Paragraph	1.	INTRODUCTION	2
	2.	SCOPE	2
	2.1	Purpose	2
	2.2	Application	2
	2.3	Limitations	2
	3.	PROCEDURES	2
	4.	INSPECTION	4

Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

1. INTRODUCTION.

This Joint Ordnance Test Procedure (JOTP) has been developed to address Department of Defense (DOD) identification marking of munitions with less sensitive explosive fills, so that they can be distinguished from their more sensitive counterparts to enable appropriate application (or selection) of Explosive Ordnance Disposal (EOD) procedures for disposal. This JOTP is referenced in Military Standard (MIL-STD)-709, Department of Defense Design Criteria Standard: Ammunition Color Coding, which is the overarching document describing the requirements for marking of munitions.

2. SCOPE.

2.1 Purpose.

The purpose of this document is to establish procedures and standardize the content of the identification marking to be used for munitions containing less sensitive explosive fills. It also specifies marking locations within a munition family.

2.2 Application.

These new procedures will apply to all munitions produced after this JOTP is released that contain less sensitive explosive fills, 60 millimeter (mm) or larger, except for the exempted items found in paragraph 3.g of this JOTP. A less sensitive explosive fill is defined as any fill that is not either TNT, Comp B or Tritonal. All munitions that contain less sensitive explosive fills will need to be marked, even if the fills have not been marked before. Exceptions will be for munitions in the current inventory, and to all munitions currently in production when this JOTP is approved, including munitions under production contracts (but not to include options for additional production), in Low Rate Initial Production, and those munitions awaiting acceptance or delivery.

2.3 Limitations.

This document is only applicable to conventional (non-nuclear) munitions.

3. PROCEDURES.

a. Identification. Items will be marked with item nomenclature and explosive fill name (i.e. PBXN-109, AFX-757, etc.).

b. Location. Identification markings will be in two locations, 180 degrees apart from one another.

c. Application. Identification markings will be applied in a permanent manner, such as, but not limited to, stamping or laser etching.

d. Performance. Item identification marking shall not interfere with item performance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

e. Family of Munition. Marking will be in a common location for each family of munition. Locations will be determined by the program office responsible for that munition, with coordination with NSWC IHEODTECHDIV and ARDEC EOD.

f. Size of Marking. Dependent upon physical space limitations of munition, minimum lettering dimensions will be 3.18 mm (0.125 inch) high by 2.38 mm (0.0937 inch) wide. Nominal depth will be 0.25 mm (0.01 inch) unless physical material characteristics of munition prohibits support of this depth.

g. Exempted Items. Items listed below are exempted from this document.

(1) Cartridge Actuated Devices (CADS) and Propellant Actuated Devices (PADS): The term CAD shall be synonymous with and collectively represent FSC 1377 cartridges.

(2) Actuated Devices/Detonating Cords: Actuated devices, and explosive detonating cords used in aircraft/helicopter emergency escape systems, fire extinguisher systems, and equipment/stores jettison and separation systems. The term PAD shall be synonymous with and collectively represent FSC 1377 rocket catapults and rocket motors used in aircraft escape systems. Data sheets for existing CADS and PADS can be found in Technical Manual (TM) 43-0001-39.

(3) Military Pyrotechnics: The term military pyrotechnic shall be synonymous with photoflash cartridges, flares, signals, simulators and markers. Data sheets for existing military pyrotechnics can be found in TM 43-0001-37.

(4) Demolition Materials: The term demolition material shall be synonymous with initiating and priming devices, explosive charges, demolition kits and assemblies and incendiary devices. Data sheets for existing demolition materials can be found in TM 43-0001-38.

(5) Inert filled ordnance.

(6) Thermally Coated and Carbon Fiber Bombs: Thermally protected and carbon fiber bombs are exempt from the location requirements above but will stamp the explosive fill on the aft of the bomb (e.g. base plate).

(7) Reactive Armor.

4. INSPECTION.

Inspection of markings shall be through customary inspection methods found on item drawings and in technical data packages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

(This page is intentionally blank.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.

Comments, suggestions, or questions on this document should be addressed to Range Infrastructure Division (CSTE-TM), US Army Test and Evaluation Command, 2202 Aberdeen Boulevard, Aberdeen Proving Ground, Maryland 21005-5001; or e-mailed to:

usarmy.apg.atec.mbx.atec-standards@mail.mil

Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil. This document is identified by the accession number (AD No.) printed on the first page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:55Z
Check the source to verify that this is the current version before use.