MIL-C-11760D
6 June 1979
SUPERSEDING
MIL-C-11760C
16 May 1974

MILITARY SPECIFICATION

CLAMPS, HOSE, PNEUMATIC,

FOR UNIVERSAL COUPLINGS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two sizes of pneumatic hose clamps designed for use with universal-type hose couplings conforming to WW-C-633, Type I.

1.2 Classification. Hose clamps shall be of the following sizes, as specified (see 6.2):

Size 1 - 3/4 inch.
Size 2 - 1 inch.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or requests for proposal, form a part of this specification to the extent specified herein.

FSC 4730

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:57Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-B-626	- Brass, Leaded and Non-Leaded: Rod, Shapes, Forgings, and Flat Products with Finished Edges (Bar and Strip).
QQ-P-416	- Plating, Cadmium (Electrodeposited).
QQ-Z-325	- Zinc Coating, Electrodeposited, Requirements for.
WW-C-633	- Couplings, Hose: (Half), Pneumatic, Universal Type.

MILITARY

MIL-P-775	- Packaging of Hose, Hose Assemblies; Rubber, Plastic, Fabric or Metal (Including tubing); and Fittings, Nozzles, and Strainers.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:57Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 322 - Hot-Rolled Alloy Steel Bars

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

3. REQUIREMENTS

3.1 Description. The pneumatic hose clamp shall be of two-piece design joined by two or four bolts, to secure a universal-type pneumatic hose onto a pneumatic coupling conforming to WW-C-633, Type I.

* 3.2 First article (first produced hose clamp). The contractor shall furnish one or more hose clamps as specified (see 6.2) for examination and testing within the time frame specified (see 6.2) to prove that his production methods and choice of design detail will produce hose clamps that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

* 3.3 Material. Material shall be as specified herein. The hose clamps shall be made of forged brass conforming to QQ-B-626, copper alloy number 377; or hot-rolled alloy steel bars conforming to ASTM A 322. Bolts, nuts, or fasteners shall be of the same metal as the base clamp. Materials used that are not corrosion resistant shall be cadmium plated in accordance with QQ-P-416, Type II, Class 3, or zinc plated in accordance with QQ-Z-325, Type II, Class 3 (see 6.4).

3.4 Design. The hose clamp shall be designed to lock onto the securing ridge or throat of the coupling by preformed metal fingers, or by a beveled forward edge, as the hose is compressed onto the serrated tang. When the clamp is fully tightened, the compression of the hose shall be evenly distributed and the locking device shall be evenly engaged with the hose coupling reinforcing the joint. The secured hose, clamp, and coupling shall withstand a 500-pound vertical pull without evidence of separation. The assembly shall be capable of withstanding hydrostatic pressures up to 150 pounds per square inch gage (psig) without leakage.

Source: https://assist.dla.mil -- Downloaded: 202640-17T21:57Z
Check the source to verify that this is the currentversion before use.

3.5 Marking. Each hose clamp shall be marked with its size.

3.6 Workmanship. All surfaces, boltholes, stampings, and forgings shall be free from sharp edges, burrs, cracks, or excess metal which would reduce usefullness, damage the hose, or create a physical hazard.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

* 4.2 Classification of inspections. Inspection requirements specified herein are classified as follows:

(a) First produced hose clamp inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First produced hose clamp inspection.

4.3.1 Examination. The first produced hose clamp shall be examined in accordance with 4.5.1. One or more defects shall be cause for rejection.

4.3.2 Tests. The first produced hose clamp shall be tested as specified in 4.5.2.1 and 4.5.2.2. Failure of either test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202640-17T21:57Z
Check the source to verify that this is the currentversion before use.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, Inspection Level III.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the defects specified in 4.5.1. AQL shall be 2.5 percent defective.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.1 and 4.5.2.2. AQL shall be 1.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The hose clamps shall be examined as specified herein for the following defects:

101. Material or finish not as specified.
102. Design not as specified.
103. Marking not as specified.
104. Workmanship not as specified.

4.5.2 Tests.

4.5.2.1 Hydrostatic. The hose clamp shall be assembled and tightened around a pneumatic hose placed on a pneumatic coupling. The assembly shall be subjected to a hydrostatic pressure of 150 psi for not less than 1 hour. Any leakage between the hose and the coupling shall constitute failure of this test.

4.5.2.2 Pull. The hose coupling shall be fastened to a stationary connection, and a pull of not less than 500 pounds shall be exerted on the hose along the longitudinal axis of the hose and coupling. This force shall be maintained for not less than 1 minute. Evidence of separation of the hose and the coupling shall constitute failure of this test.

* 4.6 Inspection of packaging. Inspection of Level A preservation and marking, and Level A and Level B packing and marking, shall be in accordance with the quality assurance provisions of MIL-P-775. Commercial preservation, packing, and marking shall be examined for conformance to MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:57Z
Check the source to verify that this is the current version before use.

* 5. PACKAGING.

* 5.1 Preservation, packing, and marking. Preservation and preservation marking shall be Level A or Commercial, and packing and packing marking shall be Level A, Level B, or Commercial as specified (see 6.2). Level A preservation and marking, and Level A and Level B packing and marking shall be in accordance with MIL-P-775. Commercial preservation, packing, and marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The hose clamp is intended for use in securing universal pneumatic hose on metal quick-connect couplings in service with air compressors and pneumatic tools and compressed air distribution.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size of hose clamp required (see 1.2).
(c) Time frame required for submission of the first produced clamp and number of clamps required (see 3.2).
(d) Degree of preservation and degree of packing required (see 5.1).

* 6.3 First produced hose clamp. Any changes or deviations of production hose clamps from the approved first produced hose clamp during production will be subject to the approval of the contracting officer. Approval of the first produced hose clamp will not relieve the contractor of his obligation to furnish hose clamps conforming to this specification.

* 6.4 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification.

* 6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 202610-17T21:57Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review acitivity:
DLA - CS

User activities:
Army - AT, CE
Navy - MC

Preparing activity:
Army - ME

Project 4730-0943

Source: https://assist.dla.mil -- Downloaded: 202610-17T21:57Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-C-11760D Clamps, Hose, Pneumatic, for Universal Couplings

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-17T21:57Z
Check the source to verify that this is the currenversion before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-17T21:57Z
Check the source to verify that this is the current version before use.