INCH-POUND

MIL-C-11796C
AMENDMENT 1
26 April 2000

MILITARY SPECIFICATION

CORROSION PREVENTIVE COMPOND,
PETROLATUM
HOT APPLICATION

This amendment forms a part of MIL-C-11796C, dated 4 November 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.12.1: Delete and substitute:

"3.12.1 Humidity cabinet. Class 3 compound shall be capable of protecting test panels against corrosion during continuous condensation at temperatures up to 120°F (49°C) for a minimum of 30 days. (see 4.6.8.1)

PAGE 5

3.15.1: Delete.

3.15.2: Delete.

PAGE 6

4.5.2: Delete and substitute:

"4.5.2 Acceptance tests. Acceptance tests shall consist of all the tests of this specification except 4.6.8.1, Humidity Cabinet, and 4.6.8.2, Accelerated Weathering.

Custodians:
Army – AR
Navy – SH
Air Force – 99

Preparing activity:
Army – AR

(Project 8030-XXXX)

Review activities;
Army – AL, SM

AMSC N/A
Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:59Z
Check the source to verify that this is the current version before use.
FSC 8030
DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.