TT-I-556F
AMENDMENT-1
November 4, 1975

FEDERAL SPECIFICATION

INK, STAMP PAD

This amendment, which forms a part of Federal Specification TT-I-556F dated October 15, 1972, was approved by the Commissioner Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Paragraph 2.1, under "Federal Specifications", add:

"ZZ-R-1414 - Rubber Stamp, Fixed and Removable Type"

PAGE 4

Paragraph 4.3.5. delete and substitute the following:

"4.3.5 Effect on rubber stamp (class 2). The type face of a new rubber stamp meeting the requirements of Federal Specification ZZ-R-1414, shall be immersed for 10 days in the sample of class 2 ink. Surplus ink shall then be removed from the stamp and immpressions shall be made with the stamp on white bond paper conforming to type III of Federal Specification UU-P-121. There shall be no evidence of swelling or softening of the rubber. The impressions shall be sharp and regular in outline."

DOD COORDINATION HAS BEEN WAIVED

Preparing activity:

GSA-FSS

User Interest:

Army - GL

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:17Z
Check the source to verify that this is the current version before use.