[INCH-POUND]
A-A-3152
January 8, 1998
SUPERSEDING
GGG-S-1808
April 23, 1973

COMMERCIAL ITEM DESCRIPTION

SCREWDRIVER, JEWELERS', SWIVEL KNOB

The General Services Administration has authorized the use of this Commercial Item Description for procurement of the Type I jewelers' screwdrivers and bits specified in Federal Specification GGG-S-1808 for all federal agencies.

1. SCOPE

This Commercial Item Description covers swivel knob jewelers' screwdrivers with interchangeable or fixed blades, jewelers' screwdriver bits, and sets. It is the intent of this CID to provide the purchaser a vehicle to procure traditional jewelers' swivel knob screwdrivers and swivel knob micro fixed blade screwdrivers with any commercially available tip style.

2. CLASSIFICATION

2.1 Type 1 - Swivel knob, metal handle body, interchangeable blades.

2.2 Type 2 - Swivel knob, plastic handle body, fixed blades.

2.3 Type 3 - Swivel knob, plastic handle body, interchangeable blades.

3. SALIENT CHARACTERISTICS

3.1 Illustration. Screwdrivers shall be similar to Figure I, II, or III in construction. The illustrations shown are for identification and not intended to preclude the purchase of screwdrivers which are otherwise in accordance with the requirements of this commercial item description.



Figure I. Type 1 - Swivel knob, metal handle body, interchangeable blades.

Comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Center (6FET), Building 6, 1500 E. Bannister Road, Kansas City, MO 64131.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.



Figure II. Type 2 - Swivel knob, plastic handle body, fixed blades.



Figure III. Type 3 - Swivel knob, plastic handle body, interchangeable blades.

3.2 Material.

3.2.1 Screwdriver Bits. The screwdriver bits shall be made of high grade alloy steel hardened and tempered to comply with the specified physical and mechanical requirements.

3.2.2 Type 1 Handle Screwdriver Body. The body shall be of steel or aluminum. The swivel knob shall be fabricated of metal or plastic. The chuck shall be made of steel.

3.2.3 Type 2 Handle Screwdriver Body. The body and swivel knob shall be fabricated of plastic such as but not limited to cellulose acetate. When specified by the purchaser, the body and swivel knob shall be made of anti-static plastic.

3.2.4 Type 3 Handle Screwdriver Body. The body and swivel knob shall be fabricated of plastic such as but not limited to cellulose acetate. When specified by the purchaser, the body and swivel knob shall be made of anti-static plastic. The chuck shall be made of steel.

3.3 Construction.

3.3.1 Screwdriver Bits. The purchaser shall specify screwdriver bit tip style and size. The screwdriver bits shall be hardened and tempered to comply with the specified physical and mechanical requirements. The cross-sectional shape of the blade shall be round. The blades shall be free from visible defects such as scale, seams, laps, and cracks.

3.3.1.1 Type 1 and Type 3 Interchangeable Screwdriver Bits. The extreme shank end of each blade shall be flattened on two sides to seat firmly and shall be a good fit in the chuck jaw. The bit shank shall have a nominal diameter of 0.100 inch $\pm$ 0.002 inches. The nominal bit lengths shall be 1.75 +/- 0.25 inch.

3.3.1.2 Flat Tip Screwdriver Bit. The blade tip(s) shall be of the type known commercially as cabinet tip, the straight sides being approximately parallel to the blade shank. Traditional jewel's screwdriver flat tip dimensions (not covered by ASME B107.15-1993) shall be as shown in Table I Flat Tip Screwdriver Dimensions. Additional and/or larger flat tip sizes shall be in accordance with ASME B107.15-1993.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

FLAT TIP DIMENSIONS	
Width of tip ±0.005 Inch	Thickness of tip at end +0.003 -0.002 Inch
0.025	0.004
0.040	0.004
0.055	0.006
0.070	0.006
0.080	0.008
0.100	0.010

Table I. Flat Tip Screwdriver Dimension.

3.3.1.3 Phillips cross tip screwdriver bit. The blade tip(s) shall be of the type known commercially as Phillips tip and be manufactured in accordance with ASME B107.15-1993 for sizes included ASME B107.15-1993.

3.3.1.3 Hex and spline screwdriver bit. The blade tip(s) shall be of the type known commercially as male hexagonal tip or male spline tip and be manufactured in accordance with ASME/ANSI B18.3 or ASME/ANSI B18.3.2 for sizes included with ASME/ANSI B18.3 or ASME/ANSI B18.3.2.

3.3.1.5 Other tip styles and sizes. Other tip styles such as but not limited to Torx, Pozidrive, Square Recess, Clutch Head, Frearson, Torq-Set; and other tip sizes not includes in applicable above mentioned industry standards shall be in accordance with acceptable industry practice and be functionally and dimensionally compatible with the fasteners they are designed to remove and install. It is the intent of this CID to provide the purchaser a vehicle to procure traditional jeweler's swivel knob screwdrivers and swivel knob micro fixed blade screwdrivers with any commercially available tip style.

3.3.2 Screwdriver Body.

3.3.2.1 Type 1 Swivel Knob, Metal Handle Body, Interchangeable Blades. The body shall be cylindrical in shape, and neatly knurled to provide a comfortable hand grip. The handle shall have a minimum nominal diameter of ¼ inch and shall have a minimum length of 2-3/4 inches. One end of the body shall have a chuck which will securely hold interchangeable blades. The other end shall have a swivel-type knob. The swivel knob shall be not less than ½ inch across flats.

3.3.2.2 Type 2 Swivel Knob, Plastic Handle Body, Fixed Blades. The body shall be shaped to provide a comfortable hand grip. The handle shall have a minimum nominal diameter of ¼ inch and shall have a minimum length of 2-1/2 inches. One end of the body shall have a blades securely attached. The other end shall have a swivel-type knob. The swivel knob shall be not less than ½ inch across flats or in diameter.

3.3.2.3 Type 3 Swivel Knob, Plastic Handle Body, Interchangeable Blades. The body shall be shaped to provide a comfortable hand grip. The handle shall have a minimum nominal diameter of ¼ inch and shall have a minimum length of 2-1/2 inches. One end of the body shall have a chuck which will securely hold interchangeable blades. The other end shall have a swivel-type knob. The swivel knob shall be not less than ½ inch across flats or in diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3.5 Finish.

3.5.1 Screwdriver Bits. The screwdriver bits shall have a smooth, bright polish finish that will produce a 63 microinch roughness height rating, or better. When tested in accordance with B46.1, the roughness height rating shall be as specified on all exposed portions other that the tip vicinity. The blades shall be treated in a manner to prevent rust or corrosion. Plating, if any, shall be adherent. There shall be no evidence of plating peeling, or chipping. Cadmium plating will not be acceptable.

3.5.2 Screwdriver Body Assembly. All parts subject to corrosion shall be protected by nickel plating or other suitable and equally effective means, except cadmium plating will not be acceptable.

3.6 Blade hardness. The blade hardness shall be 48 to 62 on the Rockwell C scale. When tested in accordance with ASTM E-18, the hardness will be measured as close to the tip as possible and shall be as specified.

3.7 Sets. The components of sets shall conform to the specified requirements for the individual items. Sets shall be provided in an indexed case or pouch unless otherwise specified by the purchaser.

3.8 Identification marking. The jewelers' screwdriver shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.9 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Coatings and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free from tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects(e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety or appearance.

4. REGULATORY REQUIREMENTS

4.1 Recovered Materials. The offeror/contractor is encouraged to use recovered materials to maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pounds units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor certification. The contractor shall provide certification and maintain substantiating evidence that all items being offered for acceptance meet the requirements of the Commercial Item Description and conform to the manufacturer's drawings. Specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Inspection responsibility. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid samples(s). When a bid sample requirement is specified in the solicitation, the bid samples(s) shall be inspected for all salient characteristics. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article samples(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING

6.1 Packaging. Requirements for preservation, packing, packaging, and marking of containers shall be as specified in the contact or order.

7. NOTES

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Address for obtaining copies of referenced documents.

Federal Acquisition Regulation (FAR): Government Printing Office. Superintendent of Documents, Washington, DC 20402-9371.

ASTM: American Society for Testing Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

ASME/ANSI B18.3, ASME/ANSI B18.3.2, ASME B107.15: American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, NY 10017.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

Federal Specifications: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and shall include the following information in procurements documents.

(a) Title, number, and date of this Commercial Item Description.
(b) The appropriate NSN.
(c) The type, tip style, and size of each individual screwdriver.
(d) The type, tip style, and size of each screwdriver within each set.
(e) Individual blades or handles as required.
(f) If anti-static plastic handles are required (Type 1 and Type 3 only).
(g) If bid samples are required and the number of samples required.
(h) If first article samples are required the number of samples required.
(i) If lot inspection and the applicable lot sampling requirements.
(j) Specify level of preservation, packaging, and packing.

For example, the following typical lot sampling requirements would be specified in the contract:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

Sampling for Inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample key shall be examined and tested for all salient characteristics. The inspection Level shall be Level I with an Acceptable Quality Level of 4.0 expressed in percent defective.

7.3 National Stock Numbers (NSN's). The following list of NSN's corresponds to the types, classes, and sizes specified in this CID. This list may not be indicative of all possible NSN's associated with this CID.

TYPE	TIP SIZE	NSN SCREWDRIVER WITH 1 EA BIT	NSN BIT ONLY NOMINAL LENGTH 1.75 +/- 0.25 INCH
1	0.025	5120-00-180-0705	5120-00-293-2055
1	0.040	5120-00-180-0706	5120-00-293-2050
1	0.055	5120-00-180-0727	5120-00-293-2051
1	0.070	5120-00-180-0728	5120-00-293-2052
1	0.080	5120-00-180-0729	5120-00-180-0887
1	0.100	5120-00-180-0730	5120-00-446-2860

TYPE	HANDLE, SCREWDRIVER JEWELERS WITHOUT BIT
1	5120-01-060-9243

COMPONENTS OF SET 5120-00-288-8739 6 SCREWDRIVERS WITH BITS	COMPONENTS OF SET 5120-01-119-2570 1 HANDLE, 6 BITS	COMPONENTS OF SET 5120-00-446-2890 1 HANDLE, 2 BITS
5120-00-180-0705	5120-01-060-9243	5120-01-060-9243
5120-00-180-0706	5120-00-293-2055	5120-00-293-2052
5120-00-180-0727	5120-00-293-2050	5120-00-446-2860
5120-00-180-0728	5120-00-293-2051	
5120-00-180-0729	5120-00-293-2052	
5120-00-180-0730	5120-00-180-0887	
	5120-00-446-2860	

MILITARY INTERESTS:

NOTE: DOD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

Preparing Activity

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.