COMMERCIAL ITEM DESCRIPTION

DOGS, LATHE

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification 00-D-565.

This description covers straight tail, bent tail, and clamp type lathe dogs. The standard lathe dogs shall be suitable for driving cylindrical work pieces held between centers. Clamp type lathe dogs shall be designed to hold hexagonal, square, or irregular shaped workpieces.

Salient characteristics.

Classification. The lathe dogs covered by this CID shall be of the following types, classes, and styles and of the sizes specified in Table I. The type, class, style, size, and quantity of lathe dogs to be furnished shall be as specified in the contract or order.

Type I - Standard lathe dogs

Class A - Straight tail

Style 1 - Single screw, hexagon socket (safety)

Style 2 - Single screw, square-head

Class B - Bent tail

Style 1 - Single screw, hexagon socket (safety)

Style 2 - Single screw, square-head

Type II - Parallel (clamp) lathe dogs

Class A - Bent tail

Style 1 - Standard

Style 2 - Safety

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:49Z
Check the source to verify that this is the current version before use.

Workpiece capacity. The lathe dogs shall meet the size and capacity requirements of Table I. The requirements of Table I are not less than the figures shown. Where a range is shown, the requirement is from the smaller figure or less to the larger figure or more.

TABLE I - Size and workpiece capacity

Size	Workpiece capacity - inches		
	Type I Class A and B	Type II Class A-Style 1	Type II Class A-Style 2
1	3/8	1-5/8	3/8 to 1
2	1/2	1-7/8	5/8 to 1-1/2
3	3/4	2-1/2	7/8 to 2
4	1	3-1/4	1-1/4 to 3
5	1-1/4	-----	----------
6	1-1/2	-----	----------
7	1-3/4	-----	----------
8	2	-----	----------
9	2-1/2	-----	----------
10	3	-----	----------
11	3-1/2	-----	----------
12	4	-----	----------
13	5	-----	----------
14	6	-----	----------

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:49Z
Check the source to verify that this is the current version before use.

Material. The bodies of standard lathe dogs and clamping bars of clamp lathe dogs shall be constructed of the same material as the manufacturers standard product and shall meet the manufacturer's current design standards.

Surface finish. Surface finishes shall be smooth and edges shall be rounded or beveled. Surfaces shall be coated or finished according to the manufacturer's standard design.

Set screws. Square head screws and hexagon socket type set-screws shall be hardened to not less than C45 Rockwell. The screws shall have a full or half dog point and shall conform to standards for socket screws in accordance with ANSI B18.3.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in Table II that is applicable to the quantity of items being puchased. Each sample shall be visually inspected, measured, and tested by the supplier, to determine conformance with the salient characteristics specified herein. Any sample failing to meet these characteristics shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, Number Defective" in column of Table II, the supplier shall replace the defective samples with acceptable items and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals, or exceeds, the quantity specified in the "Rejection, Number Defective" column of Table II, the entire lot shall be considered defective.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:49Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling plan

Quantity of items being purchased	Sample size	Acceptance, number defective	Rejection, number defective
2-8	2	1	2
9-15	5	1	2
16-25	8	2	3
26-50	13	3	4
51-90	20	5	6
91-150	32	7	8
151-280	50	10	11
281-500	80	14	15

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Cross reference. The types, classes and styles listed in this CID are cross referenced to those listed in specification 00-D-565 as shown in Table III.

TABLE III. Cross reference

00-D-565	A-A-50961
Type I, Class A, Style 1	Type I, Class A, Style 1
Type I, Class A, Style 2	---
---	Type I, Class A. Style 2
Type I, Class B, Style 1	Type I, Class B, Style 1
Type I, Class B, Style 2	---
---	Type I, Class B, Style 2
Type II, Class A	---
Type II, Class B	Type II, Class A
---	Type II, Class A, Style 1
---	Type II, Class A, Style 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:49Z
Check the source to verify that this is the current version before use.

Notes. The purchaser should specify the type, class, style, size and quantity of lathe dogs required for a specific procurement.

American National Standard Institute ANSI B18.3, "Socket Cap, Shoulders and Set Screws" is available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS:

Custodians

Army - AL
Air Force - 99

Review Activities

DLA - GS
Air Force - 84

User Activity

Navy - MC, SH

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY

DLA - IP

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:49Z
Check the source to verify that this is the current version before use.