[INCH-POUND]
A-A-50962A
7 July 1998
SUPERSEDING
A-A-50962
24 February 1984

COMMERCIAL ITEM DESCRIPTION

FORMING MACHINE, SHEET METAL, SLIP ROLL, HAND OPERATED AND ELECTRICAL MOTOR DRIVEN

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers hand operated and electrical motor driven, slip roll, sheet metal forming machines which are intended for producing cylindrical or conical sheet metal sections.

2. CLASSIFICATION. The forming machine shall be of the following types, styles, and sizes. Size refers to the nominal roll diameter and the mild-steel work piece capacity the machine and accommodate. The type, style, and size to be furnished shall be as specified (see 7.2(b)).

Type I - Manual (hand cranked)
Type II - Powered (electrical motor driven)

Style A - Bench mounted
Style B - Floor mounted

Size – (See table I)

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Supply Center Richmond, ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3441

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

TABLE I. Machine sizes and capacities, inches.

Size	Roll diameter, nominal	Capacity in mild steel: Formed cylinder inside diameter	Capacity in mild steel: Width	Capacity in mild steel: Gage	Type I: Style A	Type I: Style B	Type II: Style A	Type II: Style B	Horsepower (Minimum)
2	1	1 1/2	12	22	X	-	-	-	
3	1	1 1/2	16	30	X	-	-	-	
5	2	3	12	16	X	-	-	X	1
7	2	3	24	20	X	X	-	X	1
8	2	3	30	22	X	X	-	-	
9	2	3	36	18	-	-	-	X	1
10	2	3	36	22	X	X	-	X	1
11	2	3	42	24	X	X	-	-	
12	2	3	48	22	-	-	-	X	1
13	2 1/2	3 3/4	36	18	X	X	-	X	1
14	2 1/2	3 3/4	48	22	X	X	-	X	1
15	3	4 1/2	36	16	X	X	X	X	1.5
16	3	4 1/2	42	18	-	-	-	X	1.5
17	3	4 1/2	48	16	X	X	X	X	1.5
18	3	4 1/2	48	18	X	X	-	-	
19	4	6	48	14	-	X	-	X	1.5
20	4	6	72	18	-	X	-	X	1.5

NOTE: The “X” denotes the availability of a machine size to the applicable classification.

3. SALIENT CHARACTERISTICS

3.1 General requirements. The forming machine shall meet the requirements of American National Standards Institute (ANSI) B11.12 and the requirements shown in table I. The machine shall be new and one of the manufacturer’s current models capable of operation in accordance with the requirements herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.1.1 Rolls. The rolls shall be made of steel and shall be capable of forming sheet metal of the specified gage and width as shown in table I without permanent deformation of the rolls. The pinch roll shall be gear-driven on all machines. The top roll shall be gear-driven on machines using rolls larger than 1-1/2 inches and less than 3 inches in diameter. All rolls shall be gear-driven on machines using top rolls 3 inches or larger in diameter.

3.1.2 Pinch roll. The pinch roll shall be adjustable to accommodate different material thickness.

3.1.3 Rear roll. The rear roll shall be adjustable to form cylinders, alternate cylindrical and flat areas, and areas of differing radii. The rear roll shall be equipped with indicators to allow duplication of work.

3.1.4 Top roll. The top roll shall be capable of swinging out, or up, to allow for easy removal of formed cylinders.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

3.1.5 Circular grooves. When specified (see 7.2(c)), circular grooves shall be provided on machines with roll diameters of 2 inches or larger.

3.1.6 Longitudinal grooves. Longitudinal grooves shall be provided in one or more rolls on machines with roll diameters of 3 inches or larger.

3.1.7 Hand crank. Type I, forming machines shall be provided with a hand crank to impart rotary motion (forward and reverse) to the gear driven rolls without binding or marring the work.

3.2 System of units. The U.S. Customary System of Units (US) or the International System of Units (SI) shall be used to graduate measuring and indicating devices. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 7.2(d)). Regardless of the measurement system used, all measuring and indicating devices on the machine shall be graduated in the same system. When specified (see 7.2(e)), measuring and indicating devices shall be graduated in both the US and SI system of measurements.

3.3 Machine dimensions and weight. If required, the maximum machine dimensions (length, width, and height) shall not exceed the specified restrictions (see 7.2(f)).

3.4 Lubrication. All bearings (except sealed-for-life type), mating gears, and sliding parts shall be provided with a means for lubrication.

3.5 Electrical system. The electrical system shall conform to the National Fire Protection Association (NFPA) ANSI/NFPA-79. The machine shall operate from a dual 230/460-volt, 3-phase, 60-hertz circuit and shall be initially wired for the volt specified (see 7.2(g)).

3.6 Optional equipment. Optional equipment shall be furnished as specified (see 7.2(h)).

3.7 Performance. Unless otherwise specified (see 7.2(i)), the forming machine shall meet the performance requirements shown in table I when tested in accordance with section 5.3.

3.8 Nameplate. A nameplate shall be securely attached to the machine. Unless otherwise specified (see 7.2(j)), the nameplate shall contain the following information:

a. Nomenclature.
b. Manufacturer’s name.
c. Manufacturer’s model designation.
d. Manufacturer’s serial number.
e. Power Input (volts, total amps, phase, frequency).
f. Short-circuit/over-current protection rating.
g. Contract number or order number.
h. National stock number.
i. Date of manufacture.

3.9 Lubrication plate or chart. When specified (see 7.2(k)), a lubrication plate or chart shall be attached to the machine. The information provided on the plate or chart shall include:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

a. Points of lubricant application.
b. Servicing interval.
c. Type of lubricant(s) with SAE number or lubricant identifier.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Environmental protection. The item shall meet all applicable Environmental Protection Agency restrictions in effect on the date of the contract. These regulations apply to the emission of materials hazardous to the environment or the user's health and shall be met during the manufacturing, service, transportation, storage, and operation/use of the item.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5.2 Inspection. The forming machine shall be inspected to determine compliance with all requirements specified in this CID.

5.3 Testing. Unless otherwise specified (see 7.2(l)), the forming machine shall be tested in accordance with requirements herein. The forming machine shall be operated in accordance with the manufacturer's standard operating procedures. The test results will be compared to the performance requirements shown in table I. The material shall be a piece of annealed sheet steel with a thickness equal to the capacity of the machine and a width equal to the effective working length of the rolls. The cylinder shall be formed with no more than two passes through the rolls and shall not deviate from a true cylinder by more than 1/16 inch.

5.4 Acceptance. Unless otherwise specified (see 7.2(m)), preliminary and final acceptance tests shall be conducted at the manufacturer's site. The results of the performance tests shall be compared to the performance requirements shown in table I. Failure of the machine to meet the performance requirements shown in table I shall be cause for rejection.

6. PACKAGING. Preservation, packing, and marking shall be as specified (7.2(n)).

7. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

7.1 Sources of documents.

7.1.1 Government documents. Copies of Federal documents may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

7.1.2 Non-government documents. Copies of industry (voluntary) standards may be obtained from the following addresses:

American National Standards Institute (ANSI)

ANSI B11.12 Machine Tools - Roll - Forming and Roll - Bending Machines - Safety Requirements for the Construction, Care, and Use.

Applications for copies should be sent to the American National Standards Institute, 11 West 42nd Street, New York, NY 10036.

National Fire Protection Association (NFPA)

ANSI/NFPA 79 Electrical Standards for Industrial Machinery

Applications for copies should be sent to the National Fire Protection Association, One Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101.

7.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document
b. Type, style, and size required (see 2)
c. Circular grooves and sizes if required (see 3.1.5)
d. System of units, as specified (see 3.2)
e. Dual graduation of indication device, if required (see 3.2)
f. Machine dimensions (length, width, and height) and weight, if different (see 3.3)
g. Electrical system voltage requirement, as specified (see 3.5)
h. Optional equipment - specify, if required (see 3.6)
i. Performance requirements, if different (see 3.7)
j. Nameplate, if different (see 3.8)
k. Lubrication plate, if different (see 3.9)
l. Testing requirements, if different (see 5.3)
m. Acceptance criteria, if different (see 5.4)
n. Packaging if different (see 6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.

7.3 Part identification number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

AA50962A–XXXX

- Size: Sizes 2 through 20 (see table I)
- Style: A – Bench mounted
B – Floor mounted
- Type: 1 – Type I (Manual, hand cranked)
2 – Type II (Powered, electrical motor driven)
- CID number

7.4 Cross-reference of classification changes. Classification changes from the previous issue are as follows:

A-A-50962	A-A-50962A
Not listed	Added - Type I (Manual - hand cranked)
Not listed	Added - Type II (Powered - electric motor driven)
Style I	Changed - Style A
Style II	Changed - Style B
Size 1	Deleted
Size 4	Deleted
Size 6	Deleted

MILITARY INTERESTS:

Custodians
Army - AL
Air Force - 99

Reviewer
Air Force - 84

PREPARING ACTIVITY:
DLA - GS

(Project 3441-0164)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:48Z
Check the source to verify that this is the current version before use.