[METRIC]

A-A-896C
March 29, 1994
SUPERSEDE
A-A-896B
November 19 1992

COMMERCIAL ITEM DESCRIPTION

PAPER SET, MANIFOLD AND CARBON (CORRESPONDENCE SET)

The General Services Administration has authorized the use of this Commercial Item Description, for all Federal Agencies

1. Scope: This commercial item description covers paper sets; each set consisting of one sheet of manifold paper overlaid with a sheet of onetime carbon paper, for use in preparing copies of typed correspondence. Sets attached to each other or in pads are not covered by this description.

2. Salient characteristics:

2.1 Manifold paper. The paper shall conform to the requirements of JCP F10. The paper shall be uniformly white, blue, green, pink, salmon, or yellow, as specified in the ordering document. The paper shall be free from holes, tears, cuts, folds, scuff marks, lint, or loose particles. There shall be no splices within a sheet and there shall be no partial sheets.

2.2 Carbon paper. Shall be onetime carbon to make a permanent black reproduction. The carbon paper and manifold paper shall be equal in dimensions. The carbon paper shall be free from hard spots, wrinkles, welts, and lumps.

2.3 Paper sets. Each set shall be assembled with the coated side of the carbon sheet facing the manifold paper. The carbon sheet shall be attached to the manifold sheet such that it will remain attached during normal handling and will permit easy extraction of carbon sheets (or manifold sheets) assembled and typed at one time without tearing either the carbon or manifold copies. The paper set size shall be based upon the dimensions of the manifold paper. The alignment of the carbon sheet with the side edges of the manifold sheet shall be within +/- 0.79mm (1/32 inch). The top and bottom offset positioning of the paper set shall be such as to assure that the manifold paper is fully covered by carbon area to within 12.7mm (1/2 inch) of one end and 15.88mm (5/8 inch) of the other end. The offset shall provide a 7.9mm (5/16 inch) minimum overhang of the carbon paper on one end, and the manifold paper on the other end for the purpose of allowing easy "snap out" removal of carbon paper.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, N.Y. 10278.

Distribution Statement A:
Approved for public release
Distribution is unlimited

FSC 7530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

2.3.1 Paper Set Performance. The paper sets shall provide at one time not less than eight manifold copies. The intensity and sharpness of the images produced on all manifold copies shall be clear and legible. The carbon paper coating shall not separate or flake off when tested. There shall be no smudge marks on the manifold copies after the paper sets have been subjected to the manifolding performance test.

2.4 Bleaching: To obtain an acceptable brightness, in accordance with the performance standards of this document, a chemical bleaching process may be used. When specified in the ordering data (See Ordering Data), the bleaching process shall not include the use of chlorine, chlorine dioxide, or other chlorine compounds. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

2.5 Workmanship. The end item shall be free of any defects such as, paper dust, grit spots, wrinkles, folds, holes, tears and smudges or any other defects that may affect appearance or serviceability. The edges of the end item shall not be nicked or uneven and shall be clean cut and lint free. The paper sets shall be clean, uniformly coated, and free from pinholes, uncoated areas, or other defects which might affect the appearance or quality of reproduction.

3. Quality Assurance Provisions. Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.1 Visual and Dimensional Characteristics: Sampling for visual characteristics shall be in accordance with MIL-STD-105. Inspection Level shall be S-3 with an AQL of 2.5 defects per hundred unit. The sample unit shall consist of 1 paper set. Sampling for dimensional characteristics shall be in accordance with MIL-STD-105. Inspection Level shall be S-3 with an AQL of 2.5 defects per hundred unit. The sample unit shall consist of 1 paper set.

3.2 Testing of manifold paper shall be in accordance with Part 2, Testing Standards and Definitions, of the Government Paper Specification Standards published by the Joint Committee on Printing. (Note: See individual TAPPI's for specific sampling instructions).

3.2.1 Acceptance criteria shall be as specified in Part 4, Acceptance Criteria, of the Government Paper Specification Standards published by the Joint Committee on Printing.

3.3 Paper Set Performance Test: Sampling shall be in accordance with MIL-STD-105. The Inspection Level shall be S-2 with an AQL of 4.0 percent defective. The sample unit shall consist of one box, and shall be represented by 8 consecutive paper sets selected from it.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

3.3.1 Manifolding performance test: Typewriter or printer adjustment - Eight paper sets shall be assembled together and tested at one time in an electric typewriter or word processor printer with pica type. The typewriter shall be equipped with a ribbon recommended by the manufacturer and a platen having a hardness reading of 89 to 93, as measured with a Type A Shore durometer. The type shall be thoroughly cleaned before each test. The typewriter key force or printer shall be adjusted so that lower case letters shall barely emboss one sheet of $60g/m^2$ (16 lb. (17 x 22-500)) 25 percent cotton fiber bond paper.

3.3.1.1 Test procedure - One top sheet of $75g/m^2$ (20 lb. (17 x 22-500)) 25 percent cotton fiber bond paper and eight paper sets shall be assembled for typing. The typewriter or printer impression indicator setting and the platen setting shall be set, as recommended by the machine manufacturer, for eight copies. The sets shall be inserted in the typewriter or word processor, and the entire keyboard, both upper and lower cases, shall be typed or printed twice, followed by completed sentences to provide coverage of not less than 75 percent of the carbon area. The bond first sheet and paper sets shall be removed from the machine. The paper sets shall be disassembled by simultaneously separating the eight carbons and manifold papers using the bare hands and grasping the top and bottom overhang areas of the manifold sets.

3.3.1.2. Evaluation - Examine for: ease and complete separation of the eight carbon papers from the manifold papers (without tearing of either carbon or manifold copies), carbon paper coating (flaking or smudging) and readability of manifold copies (lightness or incomplete formations of images on the manifold copies).

4. Regulatory requirements. The contractor shall certify that the minimum content standard for the manifold paper shall be no less than 50% recovered materials including 20% post consumer materials in accordance with Executive Order 12873, section 504 (b), dated October 20, 1993 (See definition of post consumer materials and recovered materials in sections 203 and 205). As an alternative to meeting the standards of section 504(b) for all printing and writing papers, the minimum content standard shall be no less than 50% recovered materials that are a waste material byproduct of a finished product other than a paper or textile product which would otherwise be disposed of in a landfill, as determined by the State in which the facility is located, in accordance with Executive Order 12873, section 504 (c), dated October 20, 1993. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.1 Recycled Content Labeling. The recycled content shall be marked on the product or unit pack.

5. Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

6. Application for copies of technical documents referenced herein: The issue date in effect on date of invitation for bids or request for proposal shall be apply.

(1) TAPPI test methods are available from the Technical Association of the Pulp and Paper Industry, P.O. Box 105113, Atlanta, GA 30348.
(2) MIL-STD-105 is available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Ave., Philadelphia, PA 19111-5094.
(3) JCP specifications are for sale from Chief Paper Procurement Section, MMPP, U.S. Government Printing Office, North Capital and "H" St., NW, Wash DC 20401.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T08:11Z
Check the source to verify that this is the currentversion before use.

(4) Copies of Executive Order 12873, dated October 20, 1993 may be obtained from: The White House Publications Office, New Executive Office Building, White House, Att: Publications, Washington, DC. 20500 (202) 395-7332

7. Ordering Data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

A) Dimensions.
B) Packaging, packing, labeling and marking.
C) Whether bleaching without use of chlorine, chlorine dioxide, or chlorine compound is required.

MILITARY INTERESTS:
DOD has waived coordination of this document

PREPARING ACTIVITY:
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.