INCH-POUND

MIL-C-63133 (AR)
AMENDMENT 3
8 September 2000
SUPERSEDING
AMENDMENT 2
31 August 1993

MILITARY SPECIFICATION

CARTRIDGE CASE LOADING ASSEMBLY, M118
LOADING, ASSEMBLING AND PACKING

MIL-C-63133 was inactivated on 12 February 1996 for new design.

This amendment forms a part of Military Specification MIL-C-63133 (AR), dated 14 March 1977, and is approve for use by the U.S. Army Armament, Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

* Table I:

Delete:

"Functioning 300 * 3.3 4.5.8"

Substitute:

"Functioning 300 1/ * 3.3 4.5.8"

Add under Notes:

"1/ The 300 samples shall be fired in 3 approved M203 Launchers, 100 samples per launcher."

PAGE 13

4.5.2, Delete "hourly" and substitute "per shift"

Delete "hour's" and substitute "shift's"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:18Z
Check the source to verify that this is the current version before use.

4.5.2, Delete in its entirety.

PAGE 14

4.5.4, Delete in its entirety and substitute the following:

"4.5.4 Propellant weight of case, cartridge alternate method. Acceptance shall be in accordance with the Government approved Statistical Process Control (SPC) Management Plan. Initial studies will be made to determine the capabilities of the propellant loading process. A Cp and Cpk of 1.33 or greater shall be verified using the approved SPC Management Plan. Once an acceptable Cp and Cpk are obtained, a minimum of three (3) consecutive samples shall be used to maintain control charts for each weighing station at each machine, and samples shall be taken in accordance with the approved SPC Management Plan. If the process goes out of control, production will cease. Necessary corrective action will be taken. If correction cannot be made, use original method."

PAGE 15

4.5.8.1, Delete:

"The sample loaded cartridge case assembly shall be assembled (using the same method as specified in Note 2 of Dwg. 9207987) to an inert projectile."

Substitute:

"The sample loaded cartridge case assembly shall be assembled to a projectile for which it is standard."

PAGE 16

* 4.5.8.1, Line 19, delete "15 and 25 feet from the launcher. Note:" and substitute "15 and 25 feet from the launcher. The velocity may be measured with a radar system if it has been approved per 4.4.4 and 6.2. Note:"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:18Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-0604)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:18Z
Check the source to verify that this is the current version before use.