INCH-POUND
MIL-PRF-55182G
AMENDMENT 1
19 August 1997

PERFORMANCE SPECIFICATION

RESISTORS, FIXED, FILM,
NONESTABLISHED RELIABILITY, ESTABLISHED RELIABILITY, AND SPACE LEVEL,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-55182G, dated 9 June 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 16 and PAGE 17

TABLE XI, delete and substitute:

"TABLE XI. Qualification inspection.

Inspection	Requirements paragraph	Method paragraph	Number of samples	Number of defects permitted
Certification requirements				
Aqueous-extract-conductivity 2/	3.5.1	4.8		
Flux 2/	3.5.4			1/
Outgassing (space level only)	3.32	4.8.26		
Group I				
Visual and mechanical examination 3/	3.1, 3.4, 3.5, 3.5.1.1 through 3.5.3.2 inclusive, 3.5.5, 3.31, 3.31.1, and 3.32	4.8.1	All sample units	N/A
Thermal shock 4/	3.8	4.8.2		
Overload 4/	3.9	4.8.3		
DC resistance 4/	3.11	4.8.5		
Hermetic seal (when applicable) 4/	3.12	4.8.6		
Group IA				
Solderability	3.13	4.8.7	12 sample units	0
Resistance to solvents	3.14	4.8.8		
Group II				
Resistance temperature characteristics	3.15	4.8.9		
Low temperature storage	3.29	4.8.23	10 highest	
Low temperature operation	3.16	4.8.10	30 10 critical	
Terminal strength	3.17	4.8.11	10 lowest	
Hermetic seal (when applicable)	3.12	4.8.6		
Group III				
Dielectric withstanding voltage	3.18	4.8.12	10 highest	
Insulation resistance	3.19	4.8.13	30 10 critical	
Resistance to soldering heat	3.20	4.8.14	10 lowest	5/ 1
Moisture resistance	3.21	4.8.15		
Group IV				
Shock (specified pulse)	3.22	4.8.16	10 highest	
Vibration, high frequency	3.23	4.8.17	30 10 critical	
Hermetic seal (when applicable)	3.12	4.8.6	10 lowest	

See footnotes at end of table.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:35Z
Check the source to verify that this is the current version before use.

"TABLE XI. Qualification inspection - Continued.

Inspection	Requirements paragraph	Method paragraph	Number of samples	Number of defects permitted
Group V Life	3.24	4.8.18	34 highest 102 34 critical 34 lowest	1
Group VA 6/ +70°C power rating	3.24.3	4.8.18	34 highest 102 34 critical 34 lowest	1
Group VI High temperature exposure	3.25	4.8.19	34 highest 7/ 102 34 critical 34 lowest	1
Group VII Voltage coefficient (applicable to resistors of 1,000 ohms and over) Fungus Mechanical shear (when applicable)	3.26 3.27 3.28	4.8.20 4.8.21 4.8.22	10 highest	0
Group VIII (space level only) Thermal shock (100 cycles)	3.8	4.8.2	10 highest 30 10 critical 10 lowest	0

1/ Failure of a resistor in one or more tests of a group shall be charged as a single defect.
2/ The manufacturer shall verify by certification that these requirements have been met in fabricating resistors furnished to this specification.
3/ Marking shall be considered defective if the marking is illegible or incorrect. The two additional unenclosed sample units shall be subjected to the visual and mechanical examination of group I only. Marking shall remain legible at the end of all tests.
4/ As an option, the manufacturer may perform group A, subgroup 1 tests with the required PDA in lieu of these tests.
5/ For characteristic C and characteristic E, zero failures are permitted in moisture resistance.
6/ The power rating shall be +70°C. Qualification inspection only.
7/ Ten sample units shall be subjected to dielectric withstanding voltage and insulation resistance following this test."

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR
Navy - AS, CG, MC, OS
Air Force - 17, 19, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5905-1492)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:35Z
Check the source to verify that this is the current version before use.